

LIGHTHOUSE FOR BLIND OF HOUS -- REMOVER, FLOOR POLISH
=====

MSDS Safety Information
=====

FSC: 7930
NIIN: 00-045-6923
MSDS Date: 06/25/1991
MSDS Num: BLJDX
Product ID: REMOVER, FLOOR POLISH
MFN: 01
Responsible Party
Cage: 1A862
Name: LIGHTHOUSE FOR THE BLIND OF HOUSTON
Address: 3530 W DALLAS
Box: 130435
City
: HOUSTON TX 77021-0435
Info Phone Number: 713-268-9319
Emergency Phone Number: 713-268-9319
Preparer's Name: IAN SANGREE
Review Ind: Y
Published: Y
=====

Preparer Co. when other than Responsible Party Co.
=====

Cage: 1A862
Name: LIGHTHOUSE FOR THE BLIND OF HOUSTON
Address: 3530 W DALLAS
Box: 130435
City: HOUSTON TX 77021-0435
=====

Contractor Summary
=====

Cage: 1A862
Name: LIGHTHOUSE FOR THE BLIND OF HOUSTON
Address: 3530 W DALLAS
Box: 130435
City: HOUSTON TX 77021-0435
Phone: 713-268-9319
=====

Item Description Information
=====

Item Manager: GSA
Item Name: REMOVER,FLOOR POLISH
Specification Number: A-A-861
Unit of Issue: GL
UI Container Qty: 0
=====

=====

Ingredients

=====

Cas: 141-43-5
RTECS #: KJ5775000
Name: ETHANOLAMINE
% Wt: .3-2
Other REC Limits: NONE SPECIFIED
OSHA PEL: 3 PPM/6 STEL
ACGIH TLV: 3 PPM/6 STEL; 9192

Cas: 111-76-2
RTECS #: KJ8575000
Name: 2-BUTOXYETHANOL
% Wt: 1-4
Other REC Limits: NONE SPECIFIED
OSHA PEL: S, 50 PPM
ACGIH TLV: S, 25 PPM; 9293

Cas: 1310-73-2
RTECS #: WB4905000
Name: SODIUM HYDROXIDE (SA
RA 313)
% Wt: .5-2
Other REC Limits: NONE SPECIFIED
OSHA PEL: 2 MG/M3
ACGIH TLV: C 2 MG/M3; 9293
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

=====

Health Hazards Data

=====

Route Of Entry Inds - Inhalation: NO
Skin: YES
Ingestion: NO
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: MAY CAUSE EYE DAMAGE. MAY CAUSE CONTACT DERMATITIS TO
SKIN.
Signs And Symptions Of Overexposu

re: RED, DRY, IRRITATED SKIN.
Medical Cond Aggravated By Exposure: ANY PRE-EXISTING SKIN IRRITATION OR SKIN
CONDITION.
First Aid: EYE: REMOVE ANY CONTACT LENSES. IMMEDIATELY FLUSH WITH WATER AND SEE
A DOCTOR. ORAL: DRINK A LARGE QUANTITY OF WATER OR MILK & SEE A DOCTOR.
SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR.

=====
Handling and Disposal
=====

Spill Release Proce
dures: SMALL QUANTITIES MAY BE FLUSHED TO THE SEWER WITH
LARGE QUANTITIES OF WATER. LARGE QUANTITIES SHOULD BE PICKED UP WITH
ABSORBENT. FOLLOW ALL FEDERAL, STATE AND LOCAL GUIDELINES.
Neutralizing Agent: DILUTE WITH WATER.
Waste Disposal Methods: UNDILUTED PRODUCT IS REGULATED UNDER RCRA (40 CFR
261.22) AS A CORROSIVE WASTE. REGULATED QUANTITIES SHOULD BE NEUTRALIZED AT A
PERMITTED FACILITY IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL LAWS AND
REGULATIONS.

Handling And Storage Precaut
ions: PRODUCT FOR INDUSTRIAL OR INSTITUTIONAL USE
ONLY.
Other Precautions: KEEP OUT OF REACH OF CHILDREN. READ & FOLLOW LABEL
DIRECTIONS AND CAUTIONS.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: >200F,>93C
Extinguishing Media: WATER, CARBON DIOXIDE OR DRY POWDER.
Fire Fighting Procedures: SCUBA IS RECOMMENDED, PRODUCT CONTAINS CAUSTIC (LYE)
& "BUTYL" &
mp; MONOETHANOLAMINE. DIKE FIRE CONTROL WATER FOR LATER
DISPOSAL.
Unusual Fire/Explosion Hazard: NONE

=====
Control Measures
=====

Ventilation: NORMAL
Protective Gloves: IMPERVIOUS SAFETY GLOVES
Eye Protection: SAFETY GOGGLES (CHEMICAL TYPE)

=====
Physical/Chemical Properties
=====

HCC: B1
B.P.

Text: >200F,>93C
Vapor Pres: APPROX 20
Spec Gravity: 1.02
PH: 11.5-
Solubility in Water: INFINITE
Corrosion Rate: 12.5

=====

Reactivity Data

=====

Stability Indicator: YES
Stability Condition To Avoid: KEEP FROM FREEZING.
Materials To Avoid: STRONG OXIDIZING AGENTS AND STRONG ACIDS.
Hazardous Decomposition Products: OXIDES OF CARBON AND NITROGEN.
Hazardous Polymerization Indicator: NO

=====
=====

Toxicological Information

=====

Ecological Information

=====

MSDS Transport Information

=====

Regulatory Information

=====
=====

Other Information

=====

Transportation Information

=====

Responsible Party Cage: 1A862
Trans ID NO: 44586
Product ID: REMOVER, FLOOR POLISH
MSDS Prepared Date: 06/25/1991
Review Date: 08/27/1991
MFN: 1
Tech Entry NOS Shipping Nm: CORROSIVE

LIQUIDS N.O.S., 2% SODIUM HYDROXIDE SOL

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: GL

Container QTY: 0

=====
Detail DOT Information
=====

DOT PSN Code: XXX
=====

Detail IMO Information
=====

IMO PSN Code: ESH

IMO Proper Shipping Name: CORROSIVE LIQUID, N.O.S. o

IMDG Page Number: 8147

UN N

umber: 1760

UN Hazard Class: 8

IMO Packaging Group: I/II/III

Subsidiary Risk Label: -

EMS Number: 8-15

MED First Aid Guide NUM: 760
=====

Detail IATA Information
=====

IATA PSN Code: HKR

IATA UN ID Num: 1760

IATA Proper Shipping Name: CORROSIVE LIQUID, N.O.S. *

IATA UN Class: 8

IATA Label: CORROSIVE

UN Packing Group: II

Packing Note Passenger: 808

Max Quant Pass: 1L

Max Quant Cargo: 30L

Packaging

Note Cargo: 812
=====

Detail AFI Information
=====

AFI PSN Code: HKR

AFI Symbols: *

AFI Proper Shipping Name: CORROSIVE LIQUID, N.O.S.

AFI Hazard Class: 8

AFI UN ID NUM: UN1760

AFI Packing Group: II

Special Provisions: P4

Back Pack Reference: A12.3
=====

HAZCOM Label
=====

Product ID: REMOVER, FL

00R POLISH

Cage: 1A862

Company Name: LIGHTHOUSE FOR THE BLIND OF HOUSTON

Street: 3530 W DALLAS

PO Box: 130435

City: HOUSTON TX

Zipcode: 77021-0435

Health Emergency Phone: 713-527-9561

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: MAY CAUSE EYE DAMAGE. MAY CAUSE CONTACT DERMATITIS TO SKIN.

RED, DRY, IRRITATED SKIN.

=====

Disclaimer (provi

ded with this information by the compiling agencies): This

information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or

viability by or to any person or persons outside the Department of Defense

nor any person or persons contracting with any instrumentality of the United

States of America and disclaims all liability for

such use. Any person

utilizing this instruction who is not a military or civilian employee of the

United States of America should seek competent professional advice to verify

and assume responsibility for the suitability of this information to their

particular situation regardless of similarity to a corresponding Department

of Defense or other government situation.