

TACC INTERNATIONAL CORP. -- NEOPRENE SOLVENTBORNE ADHESIVE, MA-212 --
8040-00-290-4301

=====
===== Product Identification =====

Product ID:NEOPRENE SOLVENTBORNE ADHESIVE, MA-212

MSDS Date:07/01/1989

FSC:8040

NIIN:00-290-4301

MSDS Number: BLJHN

=== Responsible Party ===

Company Name:TACC INTERNATIONAL CORP.

Address:AIR STATION INDUSTRIAL PARK

Box:390

City:ROCKLAND

State:MA

ZIP:02370

Country:US

Info Phone

Num:617-878-7015

Emergency Phone Num:617-878-7015

CAGE:0HZU1

=== Contractor Identification ===

Company Name:TACC INTERNATIONAL CORP

Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:781-878-7015

CAGE:0HZU1

=====
===== Composition/Information on Ingredients =====

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 37-58%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Q

ty:1 LB

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 16-25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 9-15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:
108-88-3
RTECS #:XS5250000
Fraction by Wt: 2-5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:ACUTE: HEADACHE, DIZZINESS, NAUSEA,
UPPER RESPIRATORY DRYNESS, IRRITATION, DROWSINESS, MENTAL
DEPRESSION, NARCOSIS, DIFFICULTY IN BREATHING. CHRONIC: COULD LEAD
TO PERMANENT EFFECTS TO THE NERVOUS SYS TEM, BODY ORGANS OR THE
BRAIN. USE WITHADEQUATE VENTILATION.
Effects of Overexposure:EYES: IRRITATION. SKIN: REMOVAL OF SKIN OILS,
IRRITATION, DERMATITIS, EVEN SENSITIZATION WITH OVEREXPOSURE.
INGESTION: MAY BE HARMFUL OR FATAL IF SWALLOWED.

=====
===== First Aid Measures =====

First Aid:INHALATION: GET FRESH AIR. EYES: FLUSH WITH WATER FOR AT
LEAST 15 MINUTES. IF NECESSARY, CALL A PHYSICIAN. SKIN: WASH

WITH
SOAP AND WATER. INGESTION: CALL POISON CENTER IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:1 (BUTYL ACETATE = 1)
Solubility in Water:NIL
Appearance and Odor:NEUTRAL, TYPICAL ODOR.
Percent Volatiles by Volume:63

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS AND BASES.
Stability Condition to Avoid:FIRE, SPARKS, S
TATIC ELECTRICITY.
Hazardous Decomposition Products:CO AND CO2.

===== Disposal Considerations =====

Waste Disposal Methods:LIQUID MATERIAL IS DESIGNATED AS HAZARDOUS WASTE
UNTIL ALL SOLVENTS AND VAPORS HAVE EVAPORATED. DISPOSE OF IN
ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DRIED
ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use
by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.