

===== Product Identification =====

Product ID:INNERBOND 2010 FLUID,50 CST

MSDS Date:04/10/1989

FSC:9150

NIIN:01-313-9025

MSDS Number: BLJQQ

=== Responsible Party ===

Company Name:INLAND PACKAGING

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Info Phone Num:502-737-6758

Emergency Phone Num:502-737-6757

Preparer's Name:MORTON FIELD

CAGE:66172

=== Contracto

r Identification ===

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

===== Composition/Information on Ingredients =====

Ingred Name:POLYDIMETHYLSILOXANE

CAS:9016-00-6

RTECS #:TQ2690000

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO

IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-EYES:MAY CAUSE TEMPORARY
DISCOMFORT SIMILAR TO WIND BURN.SKIN:NON-IRRITATING.INHALATION:NOT
LIKELY TO INHALE.ORAL:VERY LOW TOXICITY.CHRONIC-UNKNOWN.
Effects of Overexposure:EYE DISCOMFORT/WIND BURNS
Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:SEEK MEDICAL CARE IF NECESSARY.INHALATION:REMOVE TO FRESH
AIR.EYES:IMMEDIATELY FLUSH WITH PLENTY OF WA
TER FOR 15 MINUTES
HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP AND WATER.
INGESTION:INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:570F,299C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.
Unusual Fi
re/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL (VERMICULITE) TO
COLLECT FOR SALVAGE OR PROPER DISPOSAL.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-KEEP CONTAINERS TIGHTLY CLOSED
IN A COOL, DRY PLACE AWAY FROM HEAT AND MOISTURE.
Other Precautions:DO NOT TAKE INTERNALLY. AVOID DIRECT OR PROLONG
ED
CONTACT WITH EYES AND SKIN. AVOID BREATHING ANY VAPORS. STORE AT
AMBIENT TEMPERATURES (5 TO 25 DEGREES C). WASH HANDS THOROUGHLY
AFTER HANDLING. DO NO T DRINK, EAT OR SMOKE IN WORK ROOM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.
Ventilation:LOCAL EXHAUST FANS
Protective Gloves:RUBBER/PLASTIC
Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER, WORK

CLOTHING AND APRON AS REQUIRED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.
Supplemental Safety and Health
FORMULA CHANGED. FOR OLD FORMULATION, SEE P/N A SAME NSN.

===== Physical/Chemical Properties =====

HCC:V6
Melt/Freeze Pt:M.P/F.P Text:-65F,-54C
Vapor Pres:0.01
Spec Gravity:0.96
Solubility in Water:INSOLUBLE
Appearance and Odor:CLEAR, COLORLESS PASTE-LIKE P
OLYMER

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
MINERAL ACIDS, STRONG BASE
Stability Condition to Avoid:FLAMES AND HIGH HEAT
Hazardous Decomposition Products:OXIDES OF CARBON AND SILICA MAY BE
EMITTED ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE DONE IN ACCORDANCE WITH
FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided
with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.