

JET-LUBE INC. -- LEAD-FREE MIL-A-907E ANTI-SEIZE LUBRICANT -- 8030-00-597-5367

===== Product Identification =====

Product ID:LEAD-FREE MIL-A-907E ANTI-SEIZE LUBRICANT

MSDS Date:04/22/1992

FSC:8030

NIIN:00-597-5367

MSDS Number: BLJVV

=== Responsible Party ===

Company Name:JET-LUBE INC.

Address:4849 HOMESTEAD ROAD

Box:21258

City:HOUSTON

State:TX

ZIP:77226

Country:US

Info Phone Num:713-674-7617

Emergency Phone Num:713-674-7617/713-370-6206

Preparer's Name:DONALD

A OLDIGES

CAGE:JO923

=== Contractor Identification ===

Company Name:JET-LUBE INC

Address:4849 HOMESTEAD RD

Box:21258

City:HOUSTON

State:TX

ZIP:77026

Country:US

CAGE:0A307

Company Name:JET-LUBE INC.

Address:4849 HOMESTEAD ROAD

Box:21258

City:HOUSTON

State:TX

ZIP:77226

Country:US

Phone:713-674-7617

CAGE:JO923

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM OIL

CAS:64741-96-4

RTECS #:PY8040000

Fraction by Wt: 70% MAX

Other REC Limits:NONE SPECIFIED

OSHA

PEL:5 MG/M3 (OIL MIST)

Ingred Name:COPPER POWDER (SARA III)

CAS:7440-50-8

RTECS #:GL5325000

Fraction by Wt: 10%M

Other REC Limits:NONE SPECIFIED

ACGIH TLV:1 MG/M3

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:THIS PRODUCT IS ESSENTIALLY  
NONHAZARDOUS. POOR PERSONAL HYGIENE PRACTICE MIGHT PRODUCE  
IRRITATION OR ILL EFFECTS WITH OVER-EXPOSU

RE. EFFECTS OF

OVEREXPOSURE: REPEATED SKIN CONTACT FOR PERSONS HYPERSEN SITIVE TO  
PETROLEUM PRODUCTS CAN CAUSE REDNESS AND IRRITATION OF SKIN.

Effects of Overexposure:REDNESS AND IRRITATION OF SKIN.

===== First Aid Measures =====

First Aid:INHALATION: CLEAR AIR PASSAGE, CALL PHYSICIAN. INGESTION: IF  
INGESTED, CALL PHYSICIAN. EYES: WASH WITH COPIOUS QUANTITIES OF  
WATER. SKIN: REMOVE BY WIPING OR WATERLESS HAND CLEANER, FOLLOWED  
BY WASHIN

G.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>430F,>221C

Autoignition Temp:Autoignition Temp Text:500F

Extinguishing Media:USE FOAM, DRY CHEMICAL, WATER SPRAY (FOG), CARBON  
DIOXIDE OR VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS.

Fire Fighting Procedures:USE SUPPLIED-AIR BREATHING EQUIPMENT FOR  
ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

=

Spill Release Procedures:SCOOP UP EXCESS, WIPE UP WITH RAGS, PICK-UP  
RESIDUE WITH DIATOMACEOUS EARTH TO AVOID WALKING HAZARD.

===== Handling and Storage =====

Handling and Storage Precautions:NORMAL PRECAUTIONS AS WITH ANY  
PETROLEUM PRODUCT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED.  
Ventilation:NOT REQUIRED.  
Protective Gloves:NOT REQUIRED.  
Eye Protection:NOT REQUIRED.  
Other Protective  
Equipment:PERSONS WITH HYPERSENSITIVE SKIN SHOULD USE  
GLOVES.  
Work Hygienic Practices:WASH HANDS BEFORE EATING.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1  
Boiling Pt:B.P. Text:624F,329C  
Vapor Pres:5  
Spec Gravity:1.20 (WATER=1)  
Evaporation Rate & Reference: