

DEFENSE GENERAL SUPPLY CENTER -- DENATURED ALCOHOL -- 6810-00-205-6786

===== Product Identification =====

Product ID:DENATURED ALCOHOL

MSDS Date:01/02/1992

FSC:6810

NIIN:00-205-6786

MSDS Number: BLRQM

=== Responsible Party ===

Company Name:DEFENSE GENERAL SUPPLY CENTER

Address:8100 JEFFERSON DAVIS HIGHWAY

City:RICHMOND

State:VA

ZIP:23297-5000

Country:US

Emergency Phone Num:804-275-4371

Preparer's Name:DGSC-SSH

CAGE:13873

=== Contractor Identification ===

Compa

ny Name:DEFENSE GENERAL SUPPLY CENTER

Address:8000 JEFFERSON DAVIS HWY

Box:City:RICHMOND

State:VA

ZIP:23297-5000

Phone:804-279-4371

CAGE:13873

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:RQ6300000

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 8990

Ingred Name:N-HEPTANE

C

AS:142-82-5
RTECS #:MI7700000
OSHA PEL:500 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====
=====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 7060 MG/KG (ETHANOL)
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: MAY BE HARMFUL IF INHALED. MAY
BE HARMFUL IF ABSORBED THROUGH THE SKIN. LIQUID OR VAPOR MAY CAUSE
IRRITATION TO THE EYES. CHRONIC: MAY BE FATAL OR CAUSE BLINDNESS IF
SWALLOWED.
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS
LISTED BY IA
RC, NTP, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:PROLONGED EXPOSURE TO EXCESSIVE CONCS. OF
ETHANOL MAY RESULT IN IRRITATION OF MUCOUS MEMBRANES, HEADACHE,
DROWSINESS, FATIGUE AND NARCOSIS. METHANOL IS ALSO A CUMULATIVE
NARCOTIC. OVEREXPOSURE OF METH ANOL CAN RESULT IN ACIDOSIS AND
VISUAL DISTURBANCES WHICH MAY PROGRESS TO PERMANENT LOSS OF VISION.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DISEASE INVOLVING THE SKIN,

EYE, RESPIRATORY
TRACT, LIVER OR KIDNEY MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:INHALATION-REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING.
GET MEDICAL ATTENTION. EYES-IMMEDIATELY FLUSH WITH PLENTY OF WATER
FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN-REMOVE CONTAMINATED
CLOTHIN G. FLUSH WITH WATER. IF IRRITATION PERSISTS, GET MEDICAL
ADVICE. INGESTION-INDUCE VOMITING IMMEDIATELY. GIVE NOTHING
BY
MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=12.8C, 55.F
Lower Limits:3.5
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, "ALCOHOL" FOAM, OR
DRY CHEMICAL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosi
on Hazard:FLAMMABLE LIQUID. VAPORS ARE HEAVIER THAN
AIR AND MAY TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION
AND FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SMALL SPILLS
MAY BE COLLECTED WITH ABSORBENT MATERIALS. FOR LARGE SPILLS, FLUSH
AREA WITH WATER SPRAY, PREVENT RUN OFF FROM ENTERING DRAINS, SEWERS
OR STREAMS.
Neutralizing Agent:NOT APPLICABLE.

===== H
andling and Storage =====

Handling and Storage Precautions:STORE IN A FLAMMABLE LIQUID STORAGE
ROOM OR CABINET. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.
PROTECT CONTAINERS FROM PHYSICAL DAMAGE.
Other Precautions:MAKE FREQUENT CAREFUL LEAKAGE INSPECTIONS. ISOLATE
FROM OXIDEZERS, CHEMICALS CAPABLE OF SPONTANEOUS HEATING, MATERIALS
REACTING WITH AIR OR MOISTURE TO LIBERATE HEAT, IGNITION SOURCES
AND EXPLOSIVES. KEEP OUT OF DIRECT SUN & AWAY FROM HEAT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED RESPIRATORS. RESPIRATORS SHOULD BE SELECTED BASED ON THE FORM AND CONCENTRATION OF CONTAMINANT IN AIR & IN ACCORDANCE WITH OSHA (29 CFR 1910.134).

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE. LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.

Protective Gloves:SOLVE
NT RESISTANT.

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.
INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS. CAUTION: FOR MANUFACTURING,

PROCESSING, REPACKING OR INDUSTRIAL USE. NOT FOR HOUSHOLD USE.
CONTAINER HAZARDOUS WHEN EMPTY. EMPTIED CONTAINERS RETAIN RESIDUAL LIQUID AND VAPOR.

===== Physical/Chemical Properties =====

HCC:F5

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:=73.9C, 165.F

Vapor Density:>1

Spec Gravity:0.81

Evaporation Rate & Reference: