View NSN Online: https://aerobasegroup.es/nsn/8010-00-597-8225

ASPEN PAINT -- STAIN, OIL TYPE, WOOD INTERIOR, WALNUT -- 8010-00-597-8225

======== Product Identification ============

Product ID:STAIN, OIL TYPE, WOOD INTERIOR, WALNUT

MSDS Date:10/01/1991

FSC:8010

NIIN:00-597-8225

MSDS Number: BLTZQ
=== Responsible Party ===
Company Name: ASPEN PAINT

Address:1128 S.W. SPOKANE STREET

City:SEATTLE State:WA ZIP:98134 Country:US

Info Phone Num:206-682-4603 (M-F 8:30 - 5:00)

Em

ergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name: DKIER

CAGE:DO051

=== Contractor Identification === Company Name: ASPEN PAINT

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134-1197

Phone: (303) 573-1014

CAGE:DO051

Company Name: ASPEN PAINTS/ASAMIPEN AMERICA INC

Address:1128 SPOKANE STREET

Box:City:SEATTLE

State:WA

ZIP:98134-1187

Country:US

Phone:303-573-1014(MED ONLY)

CAGE:0AL09

======= Composition/Information on Ingredients ========

Ingred Name: SK SOLVENT, MIN

ERAL SPIRITS MIXTURE (SOLVENT 390) CAS:8052-41-3 RTECS #:WT8925000 Fraction by Wt: 100% Other REC Limits: NONE SPECIFIED OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9293 ========== Hazards Identification =============== LD50 LC50 Mixture:SK SOLVENT:RAT/ORAL=>8 ML/KG. DERMAL=74* Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHALATION: NASAL/RESPIRATORY IRRIT, ASPHIXIATION. SKIN: PROLO NGED/REPEATED--DEFATTING & DRYING, IRRIT, DERMATITIS. EYE: SEVERE IRRIT. INGESTION: IRRITATION. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUS E CHEM PNEUMONITIS (CAN BE FATAL). PERMANENT BRAIN & NERVOUS SYS DAMAGE. CONCENTRATING AND INHALING PROD CAN BE FATAL. Explanation of Carcinogenicity: NONE OF THE MATERIALS IN THIS PRODUCT IS ON THE IARC, NTP OR OSHA CARCINOGEN LIST. Effects of Overexposure: INHAL: DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS AND ASPHI XIATION. EYE: REDNESS, TEARING & BLURRED VISION. INGEST: NAUSEA, VOMITING & DIARRHEA. *ML/KG INHALATION +71400 PPM 4 HRS. BENZENE: RAT/ORAL=>5600 ML/KG. INHALATION=13700 PPM First Aid:INHAL: REMOVE FROM EXPOSURE--RESTORE BREATHING, IF NEEDED. EYE: FLUSH W/WATER--15 MIN, HOLDING EYELIDS OPEN. SKIN: WASH CONTAM SKIN W/MILD SOAP & WATER. INGEST: DON'T INDUCE VOMITING. OBTAIN MEDICAL A TTENT ION IMMEDIATELY. NOTE TO PHYSISIAN: MAIN HAZARD FOLLOWING ACCIDENTAL INGESTION IS ASPIRATION OF LIQ INTO LUNGS (CHEM PNEUMONITIS). CARDIAC ARRYTGMIAS HAVE BEEN REPORTED W/SOLVENT EXPOSURE. ============= Fire Fighting Measures ======================== Flash Point Method:TCC Flash Point:112F,44C

Extinguishing Media: DRY CHEMICAL, CO2, FOAM, AND WATER FOG.

Fire Fighting Procedures: IN CONFINED FIRE SPACE USE ADEQUATE PROTECT

Lower Limits: 0.8 Upper Limits: 5.0

CLOTHING & APPRO

- VED POSITIVE PRESS SCBA. EXCLUDE AIR. DON'T USE WATER EXCEPT AS FOG TO COOL FIRE EXPOSED CONTAINERS.
- Unusual Fire/Explosion Hazard:AVOID EXCESSIVE HEAT, OPEN FLAMES AND ALL IGNITION SOURCES. VAPOR FORMS AN EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER AND LOWER FLAMMABLE LIMITS.

========= Accidental Release Measures ===========

- Spill Release Procedures:NO IGNIT SOURCES. VENT AREA. ABSORB SPILL W/ABSORBENT (SAWDUST/SAND/VERMICULITE), PLACE IN CLOSED CNTNR. LRG S
- PILL, DIKE AREA TO PREVENT MAT'L ENTERING WATER SYSTEMS/SEWERS.
 WEAR PROTECT EQUIP. NOTIFY APPROP ENVIRNMT AGENCY IF SPILL EXCEEDS 220 LBS.

- Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENT AREA AWAY FROM HEAT/IGNITION SOURCES. AVOID CONTACT W/SKIN. AVOID BREATH VAPOR/MIST. KEEP AWAY FROM CHILDREN.
- Other Precautions:GROUND CONTAINERS WHEN POURING & LIMIT FREE FALL TO MINIMIZE STATIC ELECTRICITY
- . EMPTY CONTAINERS MAY BE HAZARDOUS FROM RESIDUES OF PRODUCT/VAPOR. ALL CAUTIONS ON THIS MSDS APPLY TO THEM. CLOSE CONTAI NER AFTER USE. DON'T INGEST.

===== Exposure Controls/Personal Protection ========

- Respiratory Protection: A CANISTER RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPORS OR SPRAY MISTS WHEN THE TLV PEL IS EXCEEDED.
- Ventilation:GENERAL VENT REQUIRED DURING NORMAL USE. LOCAL VENT MAY BE NEEDED TO KEEP EXPOSURE LEVEL BELOW LIMITS LISTED IN INGREDS.
- Protective Gloves: CHEM RESISTANT NITRILE/NEOPRENE/RUBBER
- Eve Protection: FACE SHIELD OR CHEMICAL GOGGLES
- Other Protective Equipment: WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE.
- Work Hygienic Practices:LAUNDER CONTAMINATED CLOTHING PRIOR TO REUSE. USE GOOD PERSONAL HYGIENE.
- Supplemental Safety and Health
- TOXICITY TESTS CARRIED OUT FOR CARCINOGENICITY, TERATOGENICITY AND MUTAGENICITY HAVE BEEN NEGATIVE. DATA IS I

NSUFFICIENT TO FUTHER CLASSIFY ACCORDING TO WHMIS CRITEREA.

======== Physical/Chemical Properties ==========

HCC:F4

Boiling Pt:B.P. Text:301 TO 402F

Vapor Pres:>7.0 @ 38C

Vapor Density:4.8

Spec Gravity: 0.87 (WATER=1)

Viscosity:10"-- 25"#4FC

Evaporation Rate & Presence: SLOWER N-BUTYL ACETATE

Solubility in Water: NEGLIGIBLE

Appearance and Odor:THIN LIQUID, MILD ODOR.

Percent Volatiles by Volume:65-69

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS. Stability Condition to Avoid:AVOID EXCESSIVE HEAT, OPEN FLAME AND ALL IGNITION SOURCES.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE ARE PRODUCED ON COMBUSTION.

Conditions to Avoid Polymerization: AVOID EXCESSIVE HEAT, OPEN FLAME AND ALL IGNITION SOURCES.

======= Disposal Considerations ============

Waste Disposal Methods:RECL

AIM MAT'L OR TREAT AS HAZARD WASTE

(#D001)(MAT'L & CNTNR). DISPOSE AT A LICENSED WASTE DISPOSAL CO OR INCINERATE W/APPROVAL OF ENIVORNMNTL AUTHORITY. ALL DISPOSAL PROCEDURES MUST COMPY W/FEDERAL, STATE & LOCAL REGULATIONS. REFER TO HZDCAUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warra

nts this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.