

DAVLIN PAINT CO INC -- TT-E-508C ALKYD SG TINT BASE B508TB IVORY 2 -- 8010-00-597-8195

===== Product Identification =====

Product ID:TT-E-508C ALKYD SG TINT BASE B508TB IVORY 2

MSDS Date:02/25/1991

FSC:8010

NIIN:00-597-8195

MSDS Number: BLYZB

=== Responsible Party ===

Company Name:DAVLIN PAINT CO INC

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Info Phone Num:415-848-2863

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:PATRICIA SHAW

CAGE:3Z26

8

=== Contractor Identification ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Phone:510-848-2863

CAGE:3Z268

===== Composition/Information on Ingredients =====

Ingred Name:HYDROCARBON MIXTURE (VAPOR PRESSURE 2.0 MM HG @ 68F)

CAS:64741-41-9

Fraction by Wt: 25%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:SILICA, QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 0.26%

Oth

er REC Limits:NONE SPECIFIED
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:MANY PETROLEUM HYDROCARBONS AND
SYNTHETIC LUBRICANTS POSE POTENTIAL HUMAN HEALTH RISKS WHICH MAY
VARY FROM PERSON TO PERSON. MINIMIZE EXPOSURE TO LIQUIDS, VAPORS,
MISTS OR FUMES. CHRONIC EXP
OSURE MAY DAMAGE THE CENTRAL NERVOUS
SYSTEM, RESPIRATORY SYSTEM, LUNGS, EYES, SKIN, GASTROINTEST TRACT,
LIVER, SPLEEN, KIDNEYS.
Effects of Overexposure:INHALE: NASAL & RESPIRATORY IRRIT, DIZZINESS,
WEAKNESS, FATIGUE, NAUSEA, HEADACHE & NARCOSIS. EYE: SEVERE IRRIT,
TEARING, REDNESS & BLURRED VISION. SKIN: MODERATE IRRITATION,
DEFATTING, DERMATITIS. IN GESTION: DIGESTIVE TRACT IRRITATION &
SIGNS OF CENTRAL NERVOUS SYSTEM DEPRESSION. ASPIRATION HAZARD &
LUNG INFLAMMATIO
N.
Medical Cond Aggravated by Exposure:RESPIRATORY TRACT IRRITATION,
DERMATITIS, NAUSEA.

===== First Aid Measures =====

First Aid:EYE: FLUSH EYES W/WATER-15 MIN, OCCAS LIFTING EYELIDS. GET
MEDICAL AID. SKIN: REMOVE CONTAM CLOTHING, WASH THOROUGHLY W/SOAP &
WATER. IF IRRIT PERSISTS, SEE DOCTOR. INHALED: REMOVE TO FRESH AIR.
GIVE CPR OR OXYGEN IF NEEDED. SEE DOCTOR. INGESTION: GIVE WATER OR
MILK TO DRINK. CALL FOR MEDICAL ADVICE. DO NOT
INDUCE VOMIT UNLESS
O.K. W/DOCTOR. IF CANNOT GET MEDICAL AID, TAKE TO NEAREST EMERG
HOSP.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:104F,40C
Lower Limits:1
Upper Limits:6.1
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL, ALCOHOL FOAM.
Fire Fighting Procedures:EXTINGUISHERS FOR NFPA FLAMMABLE LIQUID FIRE.
WATER MAY BE INEFFECTIVE BUT MAY BE USED AS A FOG FOR COOLING. FIRE
FIGHTERS FULL PR

OTECTIVE CLOTHING/SCBA.

Unusual Fire/Explosion Hazard:VAPORS FORM EXPLOS MIX W/AIR BETWEEN
LOWER/UPPER LIMITS CAN IGNITE-MANY SOURCES. CLOSED CONTAINERS
EXPLODE-EXTREME HEAT. NO HEAT/ELEC EQUIP/SPARKS/OPEN FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE
ALL IGNITION SOURCES. VENTILATE THE AREA. PROVIDE APPROPRIATE
PROTECTIVE EQUIPMENT. DIKE AROUND THE SPILL AREA. COVER SPILL WITH

INERT ABSORBENT AND TRANSF ER USING NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80 F IN ORIGINAL
CONTAINER. AVOID FLAME & HIGH TEMP. DO NOT STORE NEAR OXID
AGENTS/ACIDS. VAPOR MAY TRAVEL TO IGNITE SOURCE/FLASHBACK.
Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED/REPEATED
INHALATION OF HEATED VAPORS OR SPRAY MIST. GROUND ALL CONNECTIONS,
CONTAINERS, ETC. WHEN POURING OR TRANSFERR
ING TO MINIMIZE STATIC
ELECTRICITY. USE NO N-SPARKING TOOLS. KEEP CONTAINER CLOSED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED EQUIP WHEN AIRBORNE
EXPOSURE LIMITS ARE EXCEEDED. CONSULT RESPIRATOR MANUFACTURER TO
DETERMINE APPROPRIATE EQUIPMENT FOR GIVEN APPLICATION. HIGH
AIRBORNE CONC MAY REQUIRE THE U SE OF A SUPPLIED-AIR RESPIRATOR OR
SCBA.

Ventilation:PROVIDE SUFF VENT TO CONTROL EXPOSURE LEVELS BELO
W AIRBORNE
EXPOSURE LIMITS. VENTILATION EQUIP MUST BE EXPLOSION-PROOF.

Protective Gloves:WEAR PROTECTIVE GLOVES.

Eye Protection:USE CHEMICAL SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:WEAR IMPERMEABLE APRONS AND PROTECTIVE
CLOTHING WHENEVER POSSIBLE. USE OF HEAD CAPS WHENEVER POSSIBLE.

Work Hygienic Practices:AFTER USING, WASH BEFORE EATING, TOILETING OR
SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Bo

iling Pt:B.P. Text:315F,157C
Vapor Density:>AIR
Spec Gravity:1.4 (WATER=1)
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NOT WATER SOLUBLE
Appearance and Odor:PIGMENTED LIQUID. SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:DO NOT EXPOSE TO HEAT OR IGNITION SOURCES.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON

DIOXIDE AND/OR MONOXIDE, LOW MOLECULAR WEIGHT HYDROCARBONS AND
ORGANIC ACIDS.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP OUT OF DRAINS, SEWERS AND WATERWAYS.
DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner
whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.