

MOBIL OIL CORP -- DELVAC 1210 -- 9150-00-189-6727

===== Product Identification =====

Product ID:DELVAC 1210

MSDS Date:01/07/1992

FSC:9150

NIIN:00-189-6727

MSDS Number: BMPZD

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-662-4525/800-227-0707 X3265

Emergency Phone Num:609-737-4411/CHEMTREC 800-424-9300

CAGE:3U728

=== Contractor Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWES ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (TOTAL % OF ING  
1, 2 AND 3 IS >90)

CAS:64742-54-7

RTECS #:PY8035500

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

ngred Name:MINERAL OIL  
CAS:64742-65-0  
RTECS #:PY8038500  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:5 MG/M3 AS OIL MIST  
ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC  
CAS:64742-56-9  
RTECS #:PY8039500  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:300 PPM  
ACGIH TLV:300 PPM

Ingred Name:BUTENE HOMOPOLYMER  
CAS:9003-29-6  
Fraction by Wt: 405F,>207C  
Lower Limits:0.6  
Upper Limits:7.0  
Extinguishing Media:USE WATER FOG, CO2, FOAM, OR DRY CHEMICAL. DO NOT  
USE A DIRECT  
STREAM OF WATER. PRODUCT WILL FLOAT & CAN BE  
REIGNITED.  
Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND  
NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL  
FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.  
Unusual Fire/Explosion Hazard:CARBON MONOXIDE AND CARBON DIOXIDE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF HEAT/IGNITION,PROVIDE  
ADEQUATE VENTILATION,CONTAIN LEAK.ABSORB ON FIRE RETARDANT  
TREATED  
SAWDUST,DIATOMACEOUS EARTH,ETC. SHOVEL UP AND TRANSFER TO A  
CONTAINER FOR DISPOSAL. REPORT SP ILLS AS REQUIRED TO AUTHORITIES  
(800-424-8802).

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN COOL PLACE.KEEP AWAY  
FROM HEAT,FLAME & STRONG OXIDANTS.  
Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH  
THOROUGHLY AFTER HANDLING. DO NOT BREATHE MISTS OR VAPORS.

===== Exposure Con

trois/Personal Protection =====

Respiratory Protection:NON REQUIRED UNDER NORMAL CONDITIONS. IF HIGH VAPOR OR MIST CONCENTRATIONS EXPECTED, USE RESPIRATOR APPROVED FOR ORGANIC VAPORS AND MISTS.

Ventilation:MECHANICAL VENTILATION.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL SPLASH GOGGLES/SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.  
INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND

RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres: