Product ID:VVP-216A & CID A-A-50493 MSDS Date:09/01/1990 FSC:9150 NIIN:00-261-7899 **MSDS Number: BMQBB** === Responsible Party === Company Name: UNI-KEM INTERNATIONAL INC. Address:513 HICKORY AVE **City:HARAHAN** State:LA ZIP:70123 Country:US Info Phone Num:504-738-1623 Emergency Phone Num:504-738-1623 CAGE:4S446 === Contractor Identification === **Company Name: UNI-KEM INTERNATIONAL** Address:1001 HARIMAW COURT EAST Box:City:METAIRIE State:LA ZIP:70001 Country:US Phone:504-835-7600/FAX:504-835-7608 CAGE:4S446 

Ingred Name:OXYGENATED HYDROCARBON Fraction by Wt: 10% Other REC Limits:NONE SPECIFIED

Ingred Name:PETROLEUM HYDROCARBON MIXTURE Fraction by Wt: 90% Other REC Limits:NONE SPECIFIED

LD50 LC50 Mixture:ORAL RAT

LD50: Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:LIQUID IS IRRITATING TO EYES. VAPOR MAY CAUSE EYE IRRITATION. LIQUID IS SLIGHTLY IRRITATING TO SKIN. PROLONGED OR REPEATED CONTACT CAN RESULT IN DERMATITIS. VAPORS MAY BE IRRITATING TO NOSE, THROAT & RESPIRATORY TRACT. INGESTION OF PRODUCTMAY RESULT IN VOMITING. ASPIRATION OF VOMITUS INTO LUNGS MAY CAUSE PNEUMONITIS. Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS. Effects of Overexposure: MAY CAUSE EYE, SKIN & RESPIRATORY TRACT IRRITATION. MAY ALSO CAUSE HEADACHE, DIZZINESS AND NAUSEA. ASPIRATION PNEUMONITIS MAY CAUSE COUGHING, LABORED BREATHING, CYANOSIS, AND IN SEVERE CASES, DEATH. Medical Cond Aggravated by Exposure: PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING T HE SKIN MAY BE AT INCREASED RISK FROM EXPOSURE. First Aid: EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ADVICE. INHALATIO N: REMOVE TO FRESH AIR. GIVE MOUTH-TO-MOUTH RESUSCITATION IF NOT BREATHING, GET MEDICAL ATTENTION, INGESTION: DO NOT INDUCE VOMITING, RINSE MOUTH & DRINK LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. 

Flash Point Method:TCC

Flash Point:125F,52C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HA ZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

Spill Release Procedures:WIPE UP SMALL SPILLS WITH PAPER TOWEL. WEAR GLOVES, GOGGLES & RESPIRATOR. VENTILATE AREA. DO NOT BREATHE VAPOR. ELIMINATE IGNITION SOURCES. DIKE TO RETAIN RUNOFF. VACUUM OR PUMP FREE LIQUID. ABSORB RE SIDUE WITH INERT MATERIAL & PLACE IN SALVAGE DRUM.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

================== Handling and Storag

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. KEEP CONTAINERS CLOSED WHEN MATERIAL IS NOT IN USE. KEEP AWAY FROM IGNITION SOURCES. AVOID PROLONGED OR REPEATED CONTACT. Other Precautions:NONE

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED CHEMICAL CARTRIDGE RESPIRATOR WITH FULL FACEPIECE AND ORGANIC VAPOR CARTRIDGES IN COMBINATION WITH A HIGH-EFFICIENCY PARTICULATE FI LTER.

Ventilation:LOCAL AND MECHANICAL(GENERAL) EXHAUST TO PROVIDE ADEQUATE VENTILATION.

Protective Gloves: NEOPRENE OR NITRILE RUBBER GLOVES

Eye Protection: SAFETY GLASSES - CHEMICAL SPLASH GOGGLES

Other Protective Equipment:WEAR INDUSTRIAL WORK CLOTHING. USE RUBBER APRON OR BOOTS IF NEEDED. HAVE EMERGENCY EYE WASH AND SAFETY SHOWER AVAILABLE.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REU

SE.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MIST. DO NOT INGEST. READ PRECAUTIONS ON LABEL BEFORE USE.

HCC:F4 Boiling Pt:B.P. Text:258F,126C Vapor Pres:1 MM HG Vapor Density:4.5 Spec Gravity:0.8 Appearance and Odor:CLEAR, BROWN LIQUID

Stability Indicator/Materials t

o Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

Waste Disposal Methods:DISPOSAL OF WASTE AND HAZARDOUS MATERIAL SHALL COMPLY WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL PROTECTION AGENCY REGULATIONS. SEND WASTE MATERIAL TO AN APPROVED RECYCLING FACILITY IF FEASIBLE. CITY, ST ATE AND FEDERAL REGULATIONS MUST

BEFOLLOWED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitabilit y of this information to their particular situation.