

ASPEN PAINTS -- STAIN, OIL TYPE, WOOD INTERIOR RED MAHOGANY -- 8010-00-281-2071

=====  
Product Identification  
=====

Product ID:STAIN, OIL TYPE, WOOD INTERIOR RED MAHOGANY

MSDS Date:06/01/1991

FSC:8010

NIIN:00-281-2071

MSDS Number: BMSLD

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 S.W. SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Info Phone Num:206-682-4603

Emergenc

y Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:D. KIER

CAGE:0AL09

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0AL09

Company Name:ASPEN PAINTS/ASAMIPEN AMERICA INC

Address:1128 SPOKANE STREET

Box:City:SEATTLE

State:WA

ZIP:98134-1187

Country:US

Phone:303-573-1014(MED ONLY)

CAGE:0AL09

=====  
Composition/Information on Ingredients  
=====

Ingred Name:S K SO

LVENT, MINERAL SPIRITS MIXTURE IS MADE OF THE  
FOLLOWING: SOLVENT 390 AND BENZENE (SEE BELOW)

Other REC Limits:NONE SPECIFIED

OSHA PEL:525 MG/M3

ACGIH TLV:100 PPM

Ingred Name:S K SOLVENT: (RAT) ORAL > 8.0 ML/KG; DERMAL: 74.0 ML/KG;

INHALE: +71400.0 PPM 4 HOURS

RTECS #:9999999ZZ

Other REC Limits:NONE SPECIFIED

Ingred Name:SOLVENT 390

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:PPM BENZENE ( RAT

ORAL: > 5600.0 ML/KG; INHALE: 13700.0  
PPM 4 HOURS)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: < 10%

Other REC Limits:NONE SPECIFIED

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL:78ML/KG DERM:74ML/KG INHAL:13700PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALE: NASAL AND RESPIRATORY

IRRITATION, DI

ZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE,

POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION. SKIN: CAN CAUSE

DEFATTING, DRYING, IRRITATION & DERMATITIS. EY E: CAN CAUSE SEVERE

IRRITATION, REDNESS, TEARING AND BLURRED VISION. INGEST: CAN CAUSE

GASTROINTESTINAL IRRITATION,

Explanation of Carcinogenicity:NONE OF THE MATERIALS IN THIS PRODUCT IS

ON THE IARC, NTP OR OSHA CARCINOGEN LIST.

Effects of Overexposure:NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF

MATERIAL INTO LUNGS

CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

Medical Cond Aggravated by Exposure:REPORTS STATE REPEATED & PROLONGED OCCUPATIONAL OVER-EXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING/INHALING CAN BE HARMFUL/FATAL.

=====  
===== First Aid Measures =====

First Aid:INHALE: REMOVE VICTIM FROM FURTHER EXPOSURE AND RESTORE BREATHING, IF REQUIRED. EYE: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN: WASH CONTAMINATED SKIN WITH MILD SOAP AND WATER. INGEST: DO NOT INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:112F,44C  
Lower Limits:0.8  
Upper Limits:5.0  
Extinguishing Media:DRY CHEMICAL, CO2, FOAM AND WATER FOG  
Fire Fighting Procedures:DO NOT ENTER CONFINED SPACE W/OUT PROTECTIVE CLOTHING & POSI PRESS SCBA. EXCLUDE AIR. DO NOT USE WATER EXCEPT FOR FOG. USE WATER TO COOL FIRE EXPOSED CONTAINERS  
Unusual Fire/Explosion Hazard:AVOID EXCESSIVE HEAT, OPEN FLAMES AND ALL IGNITION SOURCES. VAPOR FORMS AN EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER AND LOWER FLAMMABLE LIMITS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITE SOURCES. VENTILATE AREA. ABSORB SPILL W/ABSORB MAT'L (SAWDUST,SAND,VERMIC). PUT MAT'L IN CLOSED CNTNRS. LARGE SPILL: DIKE AREA. DO NOT LET INTO WATERWAYS. USE PROTECT EQUIPMENT. SPILLS GREATER THAN 220 LBS NOTIFY PROPER AUTHORITIES.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL-VENTILATED AREA, AWAY FROM HEAT & IGNITION SOURCES. AVOID PROLONGED OR REPEATED CONTACT W/ SKIN. AVOID BREATHING VAPORS/MIST.  
Other Precautions:LAUNDER CONTAMINATED CLOTHES PRIOR TO REUSE. USE GOOD PERSONAL HYGIENE. GROUND CONTAIN

ERS WHEN POURING & LIMIT FREE FALL

TO MINIMIZE STATIC CHARGE BUILD-UP. EMPTY CONTAINERS MAY BE  
HAZARDOUS FROM RESIDUES & VAPOR & ALL CAUTIONS APPLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER-TYPE RESPIRATOR MUST BE WORN TO  
PREVENT THE INHALATION OF VAPORS OR SPRAY MISTS WHEN THE TLV/PEL IS  
EXCEEDED.

Ventilation:GENERAL VENTILATION FOR NORMAL USE. LOCAL VENTILATION MAY  
BE NEEDED IN TO KEEP EXPOSURE LEVELS BELOW LIMITS.

Protective Gloves:CHEM RESIST NITRILE, NEOPRENE OR RUBBER

Eye Protection:FACESHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN  
CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.

Supplemental Safety and Health

"COMBUSTIBLE LIQUID". DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER  
EACH USE. KEEP AWAY FROM CHILDREN.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:301 TO 402F

Vapor Pressure:

>7.0 @ 38C

Vapor Density:4.8

Spec Gravity:0.87

pH:NA

Viscosity:10"-25" #4FC

Evaporation Rate & Reference:SLOWER THAN N-BU AC

Solubility in Water:NEGLIGIBLE

Appearance and Odor:THIN LIQUID, MILD ODOR

Percent Volatiles by Volume:65-69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT, OPEN FLAME AND ALL  
IGNITION

ION SOURCES.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE ARE PRODUCED ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: IF UNRECLAIMABLE, MATERIAL & CONTAINERS ARE CONSIDERED HAZARDOUS WASTE (EPA D001). DISPOSE OF AT LICENSED WASTE DISPOSAL COMPANY OR INCINERATE W/ APPROVAL OF ENVIRONMENTAL AUTHORITY. DISPOSAL MUST BE IN ACCORDANCE W/ FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with

this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.