View NSN Online: https://aerobasegroup.es/nsn/8010-00-281-2072

ASPEN PAINTS -- STAIN, OIL TYPE, WOOD INTERIOR DARK OAK -- 8010-00-281-2072

Product ID:STAIN, OIL TYPE, WOOD INTERIOR DARK OAK

MSDS Date:06/01/1991

FSC:8010

NIIN:00-281-2072

MSDS Number: BMSLF === Responsible Party === Company Name: ASPEN PAINTS

Address:1128 S.W. SPOKANE STREET

City:SEATTLE State:WA ZIP:98134

Country:US

Info Phone Num: 206-682-4603

Emergency Phone

Num:800-424-9300 (CHEMTREC)

Preparer's Name:D. KIER

CAGE:0ALO9

=== Contractor Identification === Company Name: ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA ZIP:98134 Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0ALO9

Company Name: ASPEN PAINTS/ASAMIPEN AMERICA INC

Address:1128 SPOKANE STREET

Box:City:SEATTLE

State:WA

ZIP:98134-1187 Country:US

Phone:303-573-1014(MED ONLY)

CAGE:0AL09

====== Composition/Information on Ingredients ========

Ingred Name: S K SOLVENT, M

INERAL SPIRITS MIXTURE IS MADE OF THE

FOLLOWING: SOLVENT 390 AND BENZENE (SEE BELOW)

Other REC Limits: NONE SPECIFIED

OSHA PEL:525 MG/M3 ACGIH TLV:100 PPM

Ingred Name: S K SOLVENT: (RAT) ORAL > 8.0 ML/KG; DERMAL: 74.0 ML/KG;

INHALE: +71400.0 PPM 4 HOURS

RTECS #:9999999ZZ

Other REC Limits: NONE SPECIFIED

Ingred Name: SOLVENT 390

CAS:8052-41-3

RTECS #:WJ8925000 Fraction by Wt: 100%

Other REC Limits: NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:PPM BENZENE (RAT ORAL:

> 5600.0 ML/KG; INHALE: 13700.0

PPM 4 HOURS)

CAS:71-43-2

RTECS #:CY1400000 Fraction by Wt: < 10%

Other REC Limits: NONE SPECIFIED

EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

============= Hazards Identification =======================

LD50 LC50 Mixture:ORAL:78ML/KG DERM:74ML/KG INHAL:13700PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALE: NASAL AND RESPIRATORY IRRITATION, DIZZINESS,


IRRITATION, DIZZINESS,

WEAKNESS, FATIGUE, NAUSEA, HEADACHE,

POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION. SKIN: CAN CAUSE DEFATTING, DRYING, IRRITATION & DERMATITIS. EY E: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING AND BLURRED VISION. INGEST: CAN CAUSE GASTROINTESTINAL IRRITATION,

Explanation of Carcinogenicity: NONE OF THE MATERIALS IN THIS PRODUCT IS ON THE IARC, NTP OR OSHA CARCINOGEN LIST.

Effects of Overexposure:NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUS



Handling and Storage Precautions:STORE IN COOL, DRY, WELL-VENTILATED AREA, AWAY FROM HEAT & IGNITION SOURCES. AVOID PROLONGED OR REPEATED CONTACT W/ SKIN. AVOID BREATHING VAPORS/MIST.

Other Precautions:LAUNDER CONTAMINATED CLOTHES PRIOR TO REUSE. USE GOOD PERSONAL HYGIENE. GROUND CONTAINERS WHEN

POURING & LIMIT FREE FALL
TO MINIMIZE STATIC CHARGE BUILD-UP. EMPTY CONTAINERS MAY BE
HAZARDOUS FROM RESI DUES & VAPOR & ALL CAUTIONS APPLY.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: A CANISTER-TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPORS OR SPRAY MISTS WHEN THE TLV/PEL IS EXCEEDED.

Ventilation: GENERAL VENTILATION FOR NORMAL USE. LOCAL VENTILATION MAY BE NEEDED IN TO KEEP EXPOSURE LEVELS BELOW LIMITS.

Pro

tective Gloves: CHEM RESIST NITRILE, NEOPRENE OR RUBBER

Eye Protection: FACESHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.

Supplemental Safety and Health

"COMBUSTIBLE LIQUID". DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM CHILDREN.

======== Physical/Chemical Properties ==========

HCC:F4

Boiling Pt:B.P. Text:301 TO 402F

Vapor Pres:>7.0

@ 38C

Vapor Density:4.8

Spec Gravity:0.87

AN:Ha

Viscosity:10"-25" #4FC

Evaporation Rate & Dr. Reference: SLOWER THAN N-BU AC

Solubility in Water: NEGLIGIBLE

Appearance and Odor:THIN LIQUID, MILD ODOR

Percent Volatiles by Volume:65-69

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT, OPEN FLAME AND ALL IGNITION SOUR

CES.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE ARE PRODUCED ON COMBUSTION.

======= Disposal Considerations ===========

Waste Disposal Methods:IF UNRECLAIMABLE, MATERIAL & CONTAINERS ARE CONSIDERED HAZARDOUS WASTE (EPA D001). DISPOSE OF AT LICENSED WASTE DISPOSAL COMPANY OR INCINERATE W/APPROVAL OF ENVIRONMENTAL AUTHORITY. DISPOSAL MUST BE I N ACCORANCE W/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this in formation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.