

CHEMTRONICS INC -- PLAST-N-GLAS C6400 C8400 -- 6850-00-852-6569

===== Product Identification =====

Product ID:PLAST-N-GLAS C6400 C8400

MSDS Date:08/01/1991

FSC:6850

NIIN:00-852-6569

MSDS Number: BMTXQ

=== Responsible Party ===

Company Name:CHEMTRONICS INC

Address:8125 COBB CENTER ROAD

City:KENNESAW

State:GA

ZIP:30144

Country:US

Info Phone Num:404-424-4267

Emergency Phone Num:404-424-4888(800-424-9300 CHEMTREC)

Preparer's Name:M. WATKINS

CAGE:2M589

=== Contract

or Identification ===

Company Name:CHEMTRONICS INC

Address:8125 COBB CENTER DRIVE

Box:City:KENNESAW

State:GA

ZIP:30152

Country:US

Phone:770-424-4888/800-645-5244

CAGE:21267

Company Name:CHEMTRONICS INC (CANCELLED USE 21267)

City:HAUPPAUGE

State:NY

ZIP:11760

Country:US

CAGE:2M589

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Other REC Limits:NONE SPECIFIED

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/5

00STEL;9192

Ingred Name:CHLORODIFLUOROMETHANE

CAS:75-45-6

RTECS #:PA6390000

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000PPM; 9192

Ozone Depleting Chemical:2

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE: OVEREXPOSURE MAY LEAD TO CNS DEPRESSION. EYE: MAY LEAD TO IRRITATION AND CAN INJURE EYE TISSUE

SKIN: DEFATTING. INGESTION: IRRITATION OF GI TRACT. CHRONIC: PROLONGED EXPOSURE CAN BE IRRITATING TO MUCOUS MEMBRANES.

Explanation of Carcinogenicity:ISOPROPYL ALCOHOL IS LISTED BY IARC, NTP.

Effects of Overexposure:INHALATION: HEART IRREGULARITIES, HEADACHE, DIZZINESS, STUPOR, COUGHING, WHEEZING, GIDDINESS. EYES: REDNESS, TEARING. SKIN: DRY SKIN, REDNESS, RASH. INGESTION: NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure:PERSONS WITH SKIN, HEART, RESPIRATORY, OR ANY OTHER MEDICAL CONDITION SHOULD USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

===== First Aid Measures =====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION AS REQUIRED. INHALATION: IMMEDIATELY REMOVE VICTIM TO FRESH AIR. GIVE OXYGEN OR ARTIFICIAL RESPIRATION AS NEEDED. GET PROMPT MEDICAL ATTENTION. EYE: IMMEDIATELY FLUSH WITH WATER FOR 20 MINUTES WITH EYELIDS HELD OPEN. GET PROMPT MEDICAL ATTENTION. INGESTION: GET PROMPT MEDICAL ATTENTION. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:FIRE EXPOSED AEROSOL CANS MAY EXPLODE. COMBUSTION

OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION
PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures: VENTILATE AREA. REMOVE SOURCES OF IGNITION.
ABSORB MATERIAL WITH INERT MATERIAL AND PLACE IN A CONTAINER FOR
LATER DISPOSAL.

Neutralizing Agent: DILUTE WITH WATER

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE NEAR SOURCES OF HEAT, IN
DIRECT SUNLIGHT,

OR WHERE TEMPERATURES EXCEED 120°F. DO NOT PUNCTURE
OR DAMAGE CONTAINERS. ROTATE STOCK.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NONE NORMALLY REQUIRED.

Ventilation: MECHANICAL (GENERAL) EXHAUST RECOMMENDED. NO SPECIAL
VENTILATION IS USUALLY REQUIRED TO MEET EXPOSURE STANDARDS.

Protective Gloves: RUBBER

Eye Protection: CHEMICAL SPLASH GOGGLES &/OR FACESHIELD

Other Protective Equipment: NONE
SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: WASH HANDS BEFORE EATING, DRINKING, SMOKING, OR
USING TOILET FACILITIES. WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MFGR SAYS PRODUCT IN 8 OZ AEROSOL CANS; TOTAL ITEM RECORD SAYS QUART
CANS??!!

===== Physical/Chemical Properties =====

HCC: V2

Boiling Pt: =97.2°C, 207°F

Vapor Pres: 760MM@20°F

Vapor Density: >1 (AIR=1)

Spec Gravity: 0.95

Evaporation Rate & Reference: