

KINDT COLLINS CO -- MEASUR-WAX (ALL COLORS) -- 9160-01-086-0132

===== Product Identification =====

Product ID:MEASUR-WAX (ALL COLORS)

MSDS Date:02/15/1992

FSC:9160

NIIN:01-086-0132

MSDS Number: BMWKX

=== Responsible Party ===

Company Name:KINDT COLLINS CO

Address:12651 ELMWOOD AVENUE

City:CLEVELAND

State:OH

ZIP:44111-5911

Country:US

Info Phone Num:216-252-4122

Emergency Phone Num:216-252-4122

CAGE:33629

=== Contractor Identification ===

Company Name:KINDT COLL

INS CO

Address:12651 ELMWOOD AVENUE

Box:City:CLEVELAND

State:OH

ZIP:44111-5911

Country:US

Phone:216-252-4122/CHEMTREC 800-424-9300

CAGE:33629

===== Composition/Information on Ingredients =====

Ingred Name:PROPRIETARY INGREDIENT

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acut

Acute and Chronic: EYE-MOLTEN WAX FUMES MAY BE SLIGHTLY IRRITATING TO EYES. SKIN-MOLTEN WAX WILL CAUSE BURNS ON CONTACT WITH SKIN. INHALATION-MOLTEN WAX FUMES MAY CAUSE (UPPER) RESPIRATORY IRRITATION. INGESTION-NO SPECIFIC INFORMATION IDENTIFIED.

Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure: IRRITATION AS NOTED ABOVE.

Medical Condition Aggravated by Exposure:

None specified by manufacturer.

===== First Aid Measures =====

First Aid: EYES: FLUSH WITH WATER FOR AT LEAST 15 MIN. SEEK MEDICAL ATTENTION. SKIN: IF HOT WAX GETS ON SKIN, DRENCH OR IMMERSE AREA IN WATER TO COOL, IF AVAILABLE APPLY ICE WATER/PACKS TO AREA. DO NOT REMOVE WAX. SEEK MEDICAL ATTENTION. INHALATION-REMOVE VICTIM FROM FRESH AIR; SEEK MEDICAL ATTENTION. INGESTION-CONSULT MEDICAL PERSONNEL.

===== Fire Fighting Measures =====

Flash Point Method: COC

Flash Point: 435F, 224C

Extinguishing Media: USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT & REIGNITE.

Fire Fighting Procedures: DO NOT ENTER CONFINED SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES, RUBBER BOOTS), INCLUDING A POSITIVE PRESSURE NIOSH SCBA.

Unusual Fire/Explosion Hazard: MATERIAL WILL NOT BURN UNLESS PREHEATED.

COOL FIRE EXPOSED CONTAINERS WITH WATER.

===== Accidental Release Measures =====

Spill Release Procedures: MAY BURN ALTHOUGH NOT READILY IGNITABLE. USE CAUTIOUS JUDGEMENT WHEN CLEANING UP LARGE MOLTEN SPILLS. SMALL MOLTEN SPILLS: ALLOW WAX TO COOL AND REMOVE AS A SOLID.

===== Handling and Storage =====

Handling and Storage Precautions: NONE SPECIFIED BY MANUFACTURER.

Other Precautions: MINIMIZE BREATHING OF VAPORS, FUMES OR MIST

IST. AVOID  
CONTACT WITH HOT METERIAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A NIOSH/MSHA APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVEREXPOSURE, IN ACCORDANCE WITH 29 CFR 1910.134, USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AN AIR PURIFYING RESPIRATOR FOR PARTICULA TES.

Ventilation:USE VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS.

Protective Gloves:WEAR PROTECTIVE GLOVES

Eye Protection:SAFETY GLASSES  
OR GOGGLES

Other Protective Equipment:USE PROTECTIVE CLOTHING AS APPROPRIATE TO PROTECT SKIN AGAINST HOT MATERIAL. EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

THIS PRODUCT MEETS REQUIREMENTS FOR INDIRECT AND DIRECT FOOD USES.

\*\*100 STRIPS PER BOX, AMBER COLOR\*\*

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>650F,>343C

Melt/Freeze Pt:M.P/F.P Text:168F,76C

V

apor Pres: