

ALLEN-BRADLEY CO -- 150 CENTISTOKES SILICONE DASH POT FLUID -- 9150-01-091-9706

===== Product Identification =====

Product ID:150 CENTISTOKES SILICONE DASH POT FLUID

MSDS Date:02/16/1994

FSC:9150

NIIN:01-091-9706

MSDS Number: BMWLC

=== Responsible Party ===

Company Name:ALLEN-BRADLEY CO

Address:1201 S 2ND ST

Box:2086

City:MILWAUKEE

State:WI

ZIP:53204

Country:US

Info Phone Num:414-382-2000

Emergenc

y Phone Num:414-382-2000

CAGE:01121

=== Contractor Identification ===

Company Name:ALLEN-BRADLEY CO

Address:1201 S 2ND ST

Box:2086

City:MILWAUKEE

State:WI

ZIP:53204

Country:US

Phone:414-382-2000

CAGE:01121

===== Composition/Information on Ingredients =====

Ingred Name:POLYDIMETHYL SILOXANE

CAS:9016-00-6

RTECS #:TQ2690000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Sk

in:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-THERE IS NO EVIDENCE OF ADVERSE
EFFECTS FROM AVAILABLE INFORMATION FOR ANY ROUTE OF EXPOSURE.
CHRONIC-NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION.
Explanation of Carcinogenicity:MANUFACTURER GAVE NO INFORMATION ABOUT
CARCINOGENICITY. HMIS DOES NOT EXPECT IT TO BE CARCINOGENIC.
Effects of Overexposure:NONE CURRENTLY KNOWN.
Medical Cond Aggravated by Exposure:A K
KNOWLEDGE OF THE AVAILABLE
TOXICOLOGY INFORMATION, PHYSICAL & CHEMICAL PROPERTIES OF THE
MATERIAL SUGGESTS THAT OVEREXPOSURE IS UNLIKELY TO AGGRAVATE
EXISTING MEDICAL CONDITIONS.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER. SKIN:WASH W/SOAP & WATER. SWALLOWING:NO
HARMFUL EFFECTS EXPECTED. **NOTE TO PHYSICIAN** THERE IS NO
SPECIFIC ANTIDOTE. TREATMENT OF OVEREXPOSURE SHOULD BE DIRECTED AT
THE CONTROL OF SYMPTOMS & THE
CLINICAL CONDITION OF THE PATIENT.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:>300F,>149C
Lower Limits:NOT DETERMIN
Upper Limits:NOT DETERMIN
Extinguishing Media:ALCOHOL/UNIVERSAL TYPE FOAMS APPLIED BY MFR'S
RECOMMENDED TECHNIQUES FOR LARGE FIRES; CO2, DRY CHEMICAL FOR SMALL
FIRES.
Fire Fighting Procedures:DO NOT SPRAY SOLID STREAM OF WATER OR FOAM
INTO HOT BURNING LIQUIDS AS THIS MAY CAUSE FROTHING & INTENSIFY
FIRE
. USE SCBA TO FIGHT FIRES IN ENCLOSED AREAS.
Unusual Fire/Explosion Hazard:IN EXTREME FIRE CONDITIONS, THIS MATERIAL
MAY PRESENT A FLOATING FIRE HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures:COLLECT FOR DISPOSAL.
Neutralizing Agent:MFR GAVE NO INFORMATION ON MSDS.

===== Handling and Storage =====

Handling and Storage Precautions:NORMAL PRECAUTIONS COMMON TO GOOD
MANUFACTURING PRACTICE SHOULD BE

FOLLOWED IN HANDLING & STORAGE.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED IN NORMAL USE.

Ventilation:MECHANICAL (GENERAL) VENTILATION IS EXPECTED TO BE SATISFACTORY.

Protective Gloves:PVC COATED

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE WASH STATION AND EMERGENCY SHOWERS.

Work Hygienic Practices:MFR:? HMIS:USE GOOD INDUSTRIAL HYGIENE PRACTICES. MINIMIZE CONTACT & WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:>392F,>200C

Melt/Freeze Pt:M.P/F.P Text: