

OIL REFINERIES LTD -- NAVAL DISTILLATE;DIESEL FUEL MARINE -- 9140-00-273-2377

=====  
Product Identification  
=====

Product ID:NAVAL DISTILLATE;DIESEL FUEL MARINE

MSDS Date:10/07/1991

FSC:9140

NIIN:00-273-2377

MSDS Number: BMZSN

=== Responsible Party ===

Company Name:OIL REFINERIES LTD

Address:SDEROT HAHISTADRUT

City:HAIFA

ZIP:31000

Country:YD

Info Phone Num:972-4-788303

Emergency Phone Num:972-4-788

111

CAGE:0N507

=== Contractor Identification ===

Company Name:DEFENSE FUEL SUPPLY CTR

Box:City:CAMERON STATION

State:VA

ZIP:22314

Country:US

Phone:202-545-6700

CAGE:52838

Company Name:OIL REFINERIES LIMITED

Address:SDEROT HAHISTAGRUT

Box:City:HAIFA 31000 ISREAL

Phone:972-4-788111

CAGE:0N507

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DIESEL FUEL MARINE (COMPLEX MIXTURE OF PARAFFINIC, OLEFINIC  
AND NAPHTHENIC HYDROCARBONS)

Fraction by Wt: >95%

Other REC L

imits:NONE SPECIFIED  
OSHA PEL:5 MG/M3 OIL MIST  
ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:SULFUR COMPOUNDS  
Fraction by Wt: 60C  
Autoignition Temp:Autoignition Temp Text:>500F  
Lower Limits:0.6  
Upper Limits:7.5

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.

Fire Fighting Procedures:USE WATER SPRAY TO COOL FIRE EXPOSED  
CONTAINERS. USE A SMOTHERING TECHNIQUE FOR EXTINGUISHING FIRE. DO  
NOT USE A FORCED WATER STREAM DIRECTLY ON OIL FIRE.

Unusual Fire/Explosion Hazard  
:COMBUSTION OR HEAT OF FIRE MAY PRODUCE  
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. FIREFIGHTERS SHOULD  
WEAR SCBA AND FULL PROTECTIVE CLOTHING.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PERSONNEL. ELIMINATE IGNITION SOURCES.  
VENTILATE AREA. WEAR PROTECTIVE CLOTHING AND EQUIPMENT. ABSORB IN  
INERT MATERIAL AND PLACE IN APPROPRIATE DISPOSAL CONTAINER AND  
COVER. WASH AREA WITH PLEN TY OF SOAP AND WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED  
AREA. PROTECT FROM PHYSICAL DAMAGE, HEAT, IGNITION SOURCES AND  
OXIDIZING AGENTS. KEEP CONTAINERS CLOSED.  
Other Precautions:PROTECT CONTAINERS FROM PHYSICAL DAMAGE. USE  
NON-SPARKING TOOLS AND EXPLOSION-PROOF EQUIPMENT. PREVENT STATIC  
ELECTRIC SPARKS. NO SMOKING IN AREAS OF USE.

===== Exposure Controls/Personal Protection =====

Respiratory Pr  
otection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED  
RESPIRATOR OR SCBA AS APPROPRIATE FOR EXPOSURE OF CONCERN.  
Ventilation:EXPLOSION-PROOF MECHANICAL (GENERAL) VENTILATION.  
Protective Gloves:RUBBER GLOVES.  
Eye Protection:CHEMICAL SAFETY GOGGLES.  
Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO MINIMIZE  
EXPOSURE FROM PROLONGED OR REPEATED CONTACT. EYE BATH AND SAFETY  
SHOWER.  
Work Hygienic Practices:DO NOT WEAR OIL CONTAMINATED CLOTHING. DO NOT  
PUT OILY RAGS INTO POCKE

TS. WASH AFTER HANDLING AND BEFORE EATING.

Supplemental Safety and Health

NONE.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:338F,170C

Vapor Pres:NEGLIGIBLE

Vapor Density:>1

Spec Gravity: