

DAVLIN PAINT CO INC -- TT-S-223B FLOOR SEALER, EMUL -- 8010-00-530-8371

=====
Product Identification
=====

Product ID:TT-S-223B FLOOR SEALER, EMUL

MSDS Date:02/26/1991

FSC:8010

NIIN:00-530-8371

MSDS Number: BNCDY

=== Responsible Party ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Info Phone Num:510-848-2863

Emergency Phone Num:510

-848-2863

Preparer's Name:PATRICIA SHAW

CAGE:3Z268

=== Contractor Identification ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Phone:510-848-2863

CAGE:3Z268

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE GLYCOL (SARA III) (PROP 65)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 4%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====

= Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL: NASAL/RESP IRRIT. NARCOSIS
(CENTRL NERV SYS DEPRESS). EYE: SEVERE IRRIT. SKIN: MOD IRRIT,
DERMATITIS. INGEST: DIGEST TRACT IRRIT, CENTRL NERV SYS DEPRESS.
ASPIRATN HZD. ENTER LUNG (SWALLOW/INGS T) CAUSE LUNG INFLAMM.
CHRONIC: CENTRL NERV SYS, RESP SYS, LUNG, EYES, SKIN, GASTRO TRACT,

LIVER, SPLEEN, KIDNEY DAMAGE.

Effects of Overexposure:INHALATION: DIZZINESS, WEAKNESS, FATIGUE,
NAUSEA AND HEADACHE. SKIN: DEFATTING.

Medical Cond Aggravated by Exposure:RESPIRATORY TRACT IRRITATION,
DERMATITIS, NAUSEA.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER 15 MIN, OCCASIONALLY LIFTING EYELIDS. GET
MED AID. SKIN: REMOVE CONTAMINATED CLOTHING, WASH W/SOAP AND WATER.
IF IRRIT PERSISTS, SEE DR. INHAL: REMOVE TO FRESH
AIR. APPLY ARTIF
RESP /ADMIN OXYGEN IF NEEDED. CONSULT DR. INGESTION: GIVE WATER OR
MILK TO DRINK & PHONE FOR MED ADVICE. DON'T INDUCE VOMIT UNLESS
DIRECTED BY MED PERSONNEL. IF MED ADVICE UNOBTAINABLE, TAKE TO
EMERG HOSP.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:241F,116C
Lower Limits:3.2
Upper Limits:15.3
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:USE EXTINGUISH
ERS (NFPA FLAMMABLE LIQUID
FIRE). WATER MAY BE INEFFECTIVE BUT MAY BE USED AS FOG FOR COOLING.
WEAR FULL PRODUCT CLOTH/BREATHING APP.
Unusual Fire/Explosion Hazard:VAPORS FORM AN EXPLOS MIX W/AIR (LEL TO
UEL), CAN BE IGNITED. CLOSED CNTNRS MAY EXPLODE WHEN EXPOSED TO
EXTREME HEAT. ISOLATE FROM HEAT/IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE NON-ESSENTIAL PERSONNEL. REMOVE
IGNITION SOURCES. VENTILAT

E AREA. PROVIDE APPROPRIATE PROTECTIVE EQUIPMENT. DIKE AROUND SPILL AREA. COVER SPILL WITH INERT ABSORBENT AND TRANSFER USING NON-SPARKING TOOLS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80 F IN CLOSED CONTAINER. STORE IN ORIGINAL CONTAINER. AVOID FLAME & HIGH TEMPERATURES. DO NOT STORE NEAR OXIDIZING AGENTS OR ACIDS.

Other Precautions:VAPOR IS HEAVIER THAN AIR, MAY TRAVEL DISTANCE TO IGNIT SOURCE & FL

ASHBACK. DON'T INGEST. AVOID INHAL. KEEP AWAY FROM HEAT. GROUND CONNECTIONS, CONTAINERS, ETC WHEN POURING OR TRANSFERING TO MINIMIZE STATIC ELEC. USE NON-SPARKING TOOLS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA EQUIPMENT WHEN AIRBORN EXPOSURE LIMITS EXCEEDED. CONSULT RESPIRATOR MFR TO DETERMINE EQUIPMENT FOR GIVEN APPLICATION. HIGH AIRBORN CONC MAY REQUIRE SUPPLIED AIR RESPIRATOR OR SELF-CONTAINED BREATHING APPARATUS.

Ventilation:PROVIDE SUFF VENT TO CONTROL EXPOSURE LEVELS BELOW TLV. VENTILATION EQUIP MUST BE EXPLOSION PROOF.

Protective Gloves:WEAR PROTECT GLOVES-PREVENT SKIN CONTACT

Eye Protection:CHEM SAFETY GOGGLES AGAINST SPLASH/MIST

Other Protective Equipment:IMPERMEABLE APRON & PROTECT CLOTH TO PREVENT REPEATED/EXTENDED EXPOSURE OF SKIN. HEAD CAPS STRONGLY RECOMMENDED.

Work Hygienic Practices:AFTER USING, WASH BEFORE EATING, TOILETING OR SMOKING.

Supplemental Safety and Health

=

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:388F,198C

Vapor Density:> AIR

Spec Gravity:1.0 (WATER=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NOT WATER SOLUBLE

Appearance and Odor:AMBER LIQUID. SOLVENT ODOR.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:DO NOT EXPOSE TO HEAT OR IGNITION SOURCES.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON DIOXIDE AND/OR LOW MOLECULAR WEIGHT HYDROCARBONS AND ORGANIC ACIDS.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP OUT OF DRAINS, SEWERS AND WATERWAYS.
DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.