EXXON INTERNATIONAL CO, CARGO TRADING DEPT -- AVIATION TURBO FUEL (KEROSENE) -- 9130-01-031-5816

Product ID:AVIATION TURBO FUEL (KEROSENE) MSDS Date:09/01/1991 FSC:9130 NIIN:01-031-5816 MSDS Number: BNKRM === Responsible Party === Company Name: EXXON INTERNATIONAL CO, CARGO TRADING DEPT Address:200 PARK AVE **City:FLORHAM PARK** State:NJ ZIP:07932-1002 Country:US Info Phone Num:201-765-5000, 908-966-7893 Emergency Phone Num:201-765-5000, 908-966-7893 CAGE:9X193 === Contractor Identification === Company Name: EXXON COMPANY U.S.A. Box:2180 **City:HOUSTON** State:TX ZIP:77252-2180 Country:US Phone:713-656-5949 / 713-656-3424 CAGE:29700 Company Name: EXXON INTERNATIONAL CO, CARGO TRADING DEPT Address:200 PARK AVE Box:City:FLORHAM PARK State:NJ ZIP:07932-1002 Country:US Phone:201-765-5000, 908-966-7893 CAGE:9X193

Ingred Name:KEROSENE CAS:64742-81-0 Fraction by Wt: LD50 LC50 Mixture: ORAL LD50 (RAT) IS UNKNOWN. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYES: SLIGHTLY IRRITATING. DOES NOT INJURE EYE TISSUE, SKIN: MAY DRY AND DEFAT SKIN, LEADING TO IRRITATION AND DERMATITIS. INHALATION: HIGH CONC. OF VAPORS ARE **IRRITATING TO MUCOUS MEMBRANES** , MAY CAUS E HEADACHES, DIZZINESS, ACT AS AN ANESTHETIC, CAUSE CENTRAL NERVOUS SYSTEM EFFECTS. INGESTION: LOW ORDER OF TOXICITY. Explanation of Carcinogenicity: PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA. Effects of Overexposure: EYES: IRRITATION. SKIN: IRRITATION, SKIN DEFATTING, DERMATITIS. INHALATION: MUCOUS MEMBRANE IRRITATION, HEADACHE, DIZZINESS, ANESTHETIC EFFECT, CENTRAL NERVOUS SYSTEM EFFECTS. INGESTION: VOMITING. Medi

cal Cond Aggravated by Exposure:PERSON WITH PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN OR RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AREA WITH SOAP AND WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING GIVE

CPR. IF BREATHING DIFFICULT GIVE OXYGEN. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point:100F,38C Extinguishing Media:FOAM, DRY CHEMICAL POWDER, CARBON DIOXIDE. Fire Fighting Procedures:USE WATER FOG OR SPRAY TO COOL FIRE-EXPOSED SURFACES AND TO PROTECT PERSONNEL. SHOULD ONLY BE USED BY PERSONNEL TRAINED IN FIRE FIGHTING. Unusual Fire/Ex

| plosion Hazard:LIQUID CAN RELEASE VAPORS THAT READILY |
|---|
| FORM FLAMMABLE MIXTURES AT OR ABOVE THE FLASH POINT. STATIC CHARGES |
| CAN ACCUMULATE AND MAY CAUSE INCENDIARY DISCHARGE. |

Spill Release Procedures:STOP LEAK. ELIMINATE ALL IGNITION SOURCES. DIKE SPILL TO KEEP OUT OF SEWERS AND WATERWAYS. VENTILATE CONFINED AREAS. RECOVER FREE LIQUID. ABSORB RESIDUE WITH SUITABLE ABSORBENT. PLACE ABSORBED WASTE I N CONTAINER S FOR DISPOSAL. USE NON-SPARKING

TOOLS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN COOL, VENTILATED AREA AWAY FROM HEAT, SPARKS, FLAME, STRONG OXIDANTS. KEEP CONTAINERS CLOSED. DO NOT SIPHON BY MOUTH. DO NOT SMOKE IN AREA.

Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EX

POSE CONTAINERS TO HEAT, FLAME, SPARKS, STATIC EKECTRICITY, OR OTHER SOURCES OF I GITION; THEY MAY EXPLODE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED RESPIRATOR IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL/TLV. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:PROVIDE SUFFICIENT VENTILATION TO PREVENT EXCEEDING RECOMMENDED EXPOSURE LI

MIT OR BUILDUP OF EXPLOSIVE CONCENTRATIONS.

Protective Gloves: CHEMICAL IMPERVIOUS GLOVES IF NEEDED.

Eye Protection: USE GOGGLES OR FACE SHIELD IF NEEDED.

Other Protective Equipment: PROVIDE EYE WASH STATION AND SAFETY SHOWER. USE CHEMICAL RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING IF NEEDED.

Work Hygienic Practices: WASH AFTER HANDLING AND BEFORE EATING,

DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health

DO NOT ATTEMPT TO CLEAN CONTAINERS

SINCE RESIDUE IS DIFFICULT TO REMOVE. "EMPTY" DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, ALL OTHER CONTAINERS SHOULD BE DISPOSED OF IN AN ENVIRONMENTALLY SAFE MANNER AND IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

HCC:F4 Boiling Pt:B.P. Text:572F,300C Spec Gravity:0.775-0.84 Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR AND BRIGHT ; NO SPECIFIED LIMITS FOR COLOR.

Stability Indicator/Materials to Avoid:YES AVOID CONTACT WITH STRONG OXIDANTS SUCH AS LIQUID CHLORINE AND CONCENTRATED OXYGEN. Stability Condition to Avoid:EXTREME TEMPERATURES, STATIC ELECTRICITY, SPARKS, OPEN FLAMES.

Hazardous Decomposition Products:SMOKE AND CARBON MONOXIDE MAY BE FORMED IN THE EVENT OF INCOMPLETE COMBUSTION.

====== Disposal Considerations ======

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS, WATERCOURSES, OR EXTENSIVE LAND AREAS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate a nd

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.