

DEL PAINT MFG. -- MIL-L-81352 NO. 26373 LACQUER P.N. 56907 -- 8010-01-303-0237
===== Product Identification =====

Product ID:MIL-L-81352 NO. 26373 LACQUER P.N. 56907

MSDS Date:03/09/1989

FSC:8010

NIIN:01-303-0237

MSDS Number: BNNKK

=== Responsible Party ===

Company Name:DEL PAINT MFG.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

Country:US

Info Phone Num:405-672-1431

Emergency Phone Num:800-42

4-9300 CHEMTREC

CAGE:DELPA

=== Contractor Identification ===

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

Company Name:DEL PAINT MFG.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

Country:US

Phone:405-672-1431

CAGE:DELPA

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 44.05%

Other REC Limits:200 PPM

OSHA P

EL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ALCOHOL, 1-BUTANOL (VAPOR PRESSURE 4.4 MM HG @ 20 C)

CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 2.86%
Other REC Limits:100 PPM
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:P M ACETATE (VAPOR PRESSURE 3.7 MM HG @ 20 C)

CAS:108-65-6
RTECS #:AI8925000
Fraction by Wt: 7.67%
Other REC Limits:NONE SPECIFIED
OSHA PEL:NONE ESTABLISHED
ACG
IH TLV:NONE ESTABLISHED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Effects of Overexposure:IF TLV'S ARE EXCEEDED, VAPORS ARE INTOXICATING AND NARCOTIC. THEY ALSO CAUSE IRRITATION TO THE MUCOUS MEMBRANES OF THE LUNG. SKIN CONTACT PRODUCES REDNESS. EYE CONTACT PRODUCES REDNESS AND PAIN. INHALATION GIVES LABORED BREATHING, DULLNESS AND DROWSINESS. INGESTION CAN CAUSE ABDOMINAL PAIN AND NAUSEA.

Medica

I Cond Aggravated by Exposure:DISEASES OF THE RESPIRATORY SYSTEM.

=====
===== First Aid Measures =====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. SHOWER OR RINSE SKIN WITH PLENTY OF WATER. EYE: RINSE WITH COPIUS AMOUNTS OF WATER, TRANSPORT TO PHYSICIAN IF NECESSARY. INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICAL RESPIRATION IF NECESSARY AND CONTACT A PHYSICIAN. INGESTION: RINSE MOUTH AND DRINK PLENTY OF WATER. DO NOT INDUCE VOMITING. SE

EK MEDICAL ASSISTANCE.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:45 F

Lower Limits:1.2

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE MODE.

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR, MAY TRAVEL ALONG GROUND & IGNITED BY PILOT LIGHTS/OTHER

FLAMES/SPARKS/HEATERS/SMOKING/ELE

C MOTORS/STATIC DISCHARGE/OTHER

IGNIT SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLEAN DRY AREA. KEEP AWAY FROM PRODUCTS, KEEP AWAY FROM SPARKS, FIRES AND REMOTE IGNITION SOURCES.

===== Exposure

Controls/Personal Protection =====

Respiratory Protection:IF TLV OF PRODUCT/ANY COMPONENT IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATOR UNDER SPECIFIED CONDITIONS.**

Ventilation:PROVIDE VENTILATION SUFF TO MAINTAIN EXPOSURE BELOW TLV'S.

Protective Gloves:RESISTANT GLOVES: BUNA-N

Eye Protection:SPLASH GOGGLES OR SAFETY GLASSES.

Other Protectiv

e Equipment:WEAR IMPERVIOUS CLOTHING AND BOOTS.

Work Hygienic Practices:WASH HANDS AND FACE BEFORE EATING.

Supplemental Safety and Health

** (SEE YOUR SAFETY EQUIPMENT SUPPLIER). ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:230 F

Vapor Density:> THAN AIR

Spec Gravity:9.27

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:71.66

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: DO NOT STORE NEAR HEATED SURFACES, OPEN FLAMES, OR IGNITION SOURCES.

Hazardous Decomposition Products: CARBON DIOXIDE AND WATER ARE FORMED ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSAL OF WASTE MATERIAL MUST COMPLY WITH FEDERAL, STATE AND LOCAL REGULATION. IF APPROVED, IT MAY BE REMOVED TO A LICENSED LAND FILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.