

DAVLIN PAINT CO INC -- 600 INDUSTRIAL ENAMEL 11105 -- 8010-00-616-7486

===== Product Identification =====

Product ID:600 INDUSTRIAL ENAMEL 11105

MSDS Date:02/25/1991

FSC:8010

NIIN:00-616-7486

MSDS Number: BNPRD

==== Responsible Party ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Info Phone Num:510-848-2863

Emergency Phone Num:510-8

48-2863

Preparer's Name:PATRICIA SHAW

CAGE:3Z268

==== Contractor Identification ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Phone:510-848-2863

CAGE:3Z268

===== Composition/Information on Ingredients =====

Ingred Name:HYDROCARBON MIXTURE (VAPOR PRESSURE 2.0 MM HG @ 68 F)

CAS:64741-41-9

Fraction by Wt: 30%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

===== Hazards Identi

fication =====

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: INHAL: NASAL, RESP IRRIT. EYE: SEVERE

IRRIT. SKIN: PROLONG/REPEAT: MOD IRRIT, DEFATTING, DERMATITIS.

INGEST: DIGEST TRACT IRRIT, CENTRL NERV SYS DEPRESS. ASPIRATION

HZD. MAT'L CAN ENTER LUNGS DURING S WALLOW/VOMIT--CAUSE LUNG INFLAMMATION. CHRONIC: RESPIR SYS, LUNGS, EYE, SKIN, GI TRACT,

LIVER, SPLEEN,

KIDNEY DAMAGE.

Effects of Overexposure: INHAL: DIZZINESS, WEAKNESS, FATIGUE, NAUSEA AND HEADACHE. HIGH CONCENTRATIONS MAY RESULT IN NARCOSIS (CENTRAL NERVOUS SYSTEM DEPRESSION). EYE: TEARING, REDNESS, AND BLURRED VISION.

Medical Cond Aggravated by Exposure: RESPIRATORY TRACT IRRITATION, DERMATITIS, AND NAUSEA.

===== First Aid Measures =====

First Aid: EYE: FLUSH W/WATER 15 MIN, LIFTING EYELID. GET MED AID. SKIN: REMOVE CONTAM CLOTHING, WAS

H W/SOAP & WATER. IF IRRIT PERSISTS, SEE

DR. INHAL: REMOVE TO FRESH AIR. APPLY ARTIF RESPIRATION OR ADMIN OXYGE N IF NEEDED. SEE DR. INGEST: GIVE WATER/MILK TO DRINK & TELEPHONE FOR MED ADVICE. DO NOT INDUCE VOMITING UNLESS DIRECTED TO BY MED PERSONNEL. IF MED ADVICE UNAVAILABLE, TAKE TO NEAREST EMERG HOSPITAL.

===== Fire Fighting Measures =====

Flash Point Method: SCC

Flash Point: 104F, 40C

Lower Limits: 1.0

Upper Limits: 6.1

Extinguishing Medi

a: FOAM, ALCOHOL FOAM, CO₂, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures: USE EXTINGUISHERS (NFPA FLAMM LIQ). WATER MAY BE INEFFECTIVE BUT MAY BE USED AS FOG FOR COOLING. FIRE FIGHTERS SHOULD WEAR FULL PROTECT CLOTH & BREATHING APP.

Unusual Fire/Explosion Hazard: VAPOR FORM EXPLOSIVE MIX W/AIR (LEL TO UEL), CAN BE IGNITED BY MANY SOURCES. CLOSED CNTNRS MAY EXPLODE W/HEAT. ISOLATE FROM HEAT/IGNITION SOURCES.

===== Accidental Release Measures =====

S

pill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL IGNITION SOURCES. VENTILATE THE AREA. PROVIDE APPROPRIATE PROTECTIVE EQUIPMENT. DIKE AROUND THE SPILL AREA. COVER SPILL WITH INERT ABSORBENT AND TRANSFER USING NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80F IN CLOSED CONTAINER. STORE IN ORIGINAL CONTAINER. AVOID FLAME & HIGH TEMPERATURES. DO NOT STORE NEAR OXIDIZING AGENTS OR ACIDS.

Other Precautions:VAPOR IS HEAVIER THAN AIR, MAY TRAVEL DISTANCE TO IGNIT SOURCE & FLASHBACK. DON'T INGEST. AVOID INHAL OF HEATED VAPOR/SPRAY MIST. KEEP FROM HEAT. GROUND CONNECTIONS, CONTAINERS WHEN POURING TO MINIMIZE STATIC ELEC. USE NON-SPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA EQUIP WHEN AIRBORN EXPOSURE EXCEEDS TLV. CONSULT RESPIRATOR MFR TO DETERMINE EQUIPMENT FOR GI

VEN APPLICATION. HIGH AIRBORN CONCENTRATIONS MAY REQUIRE USE OF SUPPLIED-AIR RESPIRATOR OR SELF-CONTAINED BREATHING APPARATUS.

Ventilation:PROVIDE SUFFICIENT VENT TO CONTROL EXPOSURE LEVELS BELOW TLV/PEL. VENTILATION EQUIPMENT MUST BE EXPLOSION PROOF.

Protective Gloves:PROTECTIVE GLOVES (SEE MFR FOR TYPE)

Eye Protection:CHEMICAL SAFETY GLASSES, GOGGLES

Other Protective Equipment:WEAR IMPERMEABLE APRONS & PROTECT CLOTH WHEN POSSIBLE TO PREVENT SKIN CONTACT. HEAD CAP WHEN POSSIBLE STRONGLY RECOMMEND

Work Hygienic Practices:AFTER USING, WASH BEFORE EATING, TOILETING OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:315F,157C

Vapor Density:> AIR

Spec Gravity:1.1 (WATER=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NOT WATER SOLUBLE

Appearance and Odor:PIGMENTED LIQUID. SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: DO NOT EXPOSE TO HEAT OR IGNITION SOURCES.

Hazardous Decomposition Products: THERMAL DECOMPOSITION MAY YIELD CARBON DIOXIDE AND/OR MONOXIDE, LOW MOLECULAR WEIGHT HYDROCARBONS AND ORGANIC ACIDS.

===== Disposal Considerations =====

Waste Disposal Methods: KEEP OUT OF DRAINS, SEWERS, AND WATERWAYS.

DISPOSE OF PRODUCT IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS. IGNITABLE D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.