

DIAL CORP THE -- XEA 9396, PART A -- 8040-00-209-1286

===== Product Identification =====

Product ID:XEA 9396, PART A

MSDS Date:09/29/1989

FSC:8040

NIIN:00-209-1286

Kit Part:Y

MSDS Number: BNRND

=== Responsible Party ===

Company Name:DIAL CORP THE

Address:1865 DIAL TOWER

Box:312

City:PHOENIX

State:AZ

ZIP:85077-1865

Country:US

Info Phone Num:602-991-3000

Emergency Phone Num:602-991-3000

Preparer's Name:SUZANNE FRANZ

CAGE:0EK45

=== Contractor Identification ===

C

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

Company Name:DIAL CORP THE

Address:111 W CLARENDON AVE

Box:3223

City:PHOENIX

State:AZ

ZIP:85077

Country:US

Phone:602-991-3000

CAGE:0EK45

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY RESIN SYSTEM

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 300F,>149C

Extinguishing Media:DRY

CHEMICAL, HALON FIRE EXTINGUISHER, WATER SPRAY,  
FOAM, OR FOG.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN  
FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASES MAY BE  
LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY  
GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP  
REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY  
CAUTIONS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL  
INSTRUCTIONS. STORE AT 40 F FOR 12 MONTHS. FOLLOW RECOMMENDED  
CURING SCHEDULE.

Other Precautions:AVOID CONTACT WITH EYES OR SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.  
Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective

Gloves:IMPERVIOUS PLASTIC OR RUBBER.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. DO NOT HANDLE  
OR USE UNTIL MSDS HAS BEEN READ AND UNDERSTOOD.

Supplemental Safety and Health

KEY1:T6. FAILURE TO OBSERVE CAUTIONS MAY RESULT IN EXCESSIVE HEAT  
BUILDUP WITH THE RELEASE OF TOXIC GASES.

===== Physical/Chemical Properties =====

HCC:B2

Boiling P

t:B.P. Text:DECOMPOSES

Vapor Pres:1

Evaporation Rate & Reference:NIL

Solubility in Water:NIL

Appearance and Odor:BLUE PASTE WITH SLIGHT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS AND  
UNDETERMINED ORGANICS.

Conditions to Avoid Polymerization:AVOID MIXING RESIN/CURING AGENT IN  
BATCHES >1 LB. DON'T

HEAT MIXED ADHESIVE >125 F UNLESS CURING  
SURFACES TO BE BONDED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO  
LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this inform

ation to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.