

UNITED TECHNOLOGIES AUTO GROUP/PRESTITE PRODUCTS -- 579.60 PLASTIC SEALER --  
8030-00-683-9014

===== Product Identification =====

Product ID:579.60 PLASTIC SEALER

MSDS Date:06/12/1987

FSC:8030

NIIN:00-683-9014

MSDS Number: BNRQS

=== Responsible Party ===

Company Name:UNITED TECHNOLOGIES AUTO GROUP/PRESTITE PRODUCTS

Address:1218 CENTRAL INDUSTRIAL DRIVE

City:ST LOUIS

State:MS

ZIP:63110

Country:US

Info Phone Num:314-577-1100

Emergency Phone Num:314-577-1100

Prepa

rer's Name:DHANSUKH M CHEVLI

CAGE:DO719

=== Contractor Identification ===

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

Company Name:UNITED TECHNOLOGIES AUTOMOTIVE GROUP

Address:1218 CENTRAL INDUSTRIAL DRIVE

City:ST LOUIS

State:MO

ZIP:63110

Phone:314-577-1100

CAGE:DO719

===== Composition/Information on Ingredients =====

Ingred Name:POLYISOBUTYLENE

CAS:9003-27-4

RTECS #:VD1010000

Fraction

by Wt: 20-60%  
Other REC Limits:NONE SPECIFIED

Ingred Name:CALCIUM CARBONATE  
CAS:471-34-1  
RTECS #:FF9335000  
Fraction by Wt: 20-60%  
Other REC Limits:10 MG/M3

Ingred Name:TALC  
CAS:14807-96-6  
RTECS #:MW2700000  
Fraction by Wt: 10-30%  
Other REC Limits:2 MG/M3  
OSHA PEL:0.2 FIBERS/CC  
ACGIH TLV:0.2 FIBERS/CC

Ingred Name:PIGMENTS  
Fraction by Wt: TRACE  
Other REC Limits:NONE SPECIFIED

Ingred Name:OCTADECANOIC ACID, ALUMINUM SALT  
CAS:637-12-7  
RTECS #:WI2820000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Effects of Overexposure:NO SIGNIFICANT SIGNS OF ANY ADVERSE HEALTH  
HAZARDS ARE EXPECTED TO OCCUR AS A RESULT OF INHALATION OR SKIN  
CONTACT. EYE AND SKIN CONTACT: LOW HAZARDS.

===== First Aid Measures =====

First Aid:EYE: TAKE OUT AS ANY OTHER FOREIGN MATERIAL. WASH WITH PLENTY  
OF WATER FOR AT LEAST 10 MINUTES. IF ANY SYMPTOMS ARE PRESENT AFTER  
WASHING, GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:>200F,>93C  
Extinguishing Media:CO2, DRY CHEMICALS, WATER SPRAY, FOAM.  
Fire Fighting Procedures:RESPIRATORY AND EYE PROTECTION REQUIRED FOR  
FIRE FIGHTING PERSONNEL.  
Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER SPILLED MATERIAL AND PLACE IN AN  
APPROPRIATELY MARKED CONTAINER FOR REUSE OR DISPOSAL.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. SELF-CONTAINED BREATHING APPARATUS REQUIRED IF EXPOSURE TO DECOMPOSITION PRODUCTS IS LIKELY.  
Ventilation:GENERAL DILUTION VENTILATION - 9000 CFM DILUTION AIR.  
Protective Gloves:RECOMMENDED.  
Eye Protection:SAFETY GLASSES.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity:1.27 + 0.07  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:LIGHT GREEN OLIVE BEAD; NEGLIGIBLE ODOR.  
Percent Volatiles by Volume:< 1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Hazardous Decomposition Products:CO<sub>2</sub>, CO, HYDROCARBONS, SMOKE, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MATERIAL CAN BE DISPOSED OF IN AN APPROVED LANDFILL OR MAY BE INCINERATED UNDER CONDITIONS WHICH MEET FEDERAL, STATE AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.