

UNITED TECHNOLOGIES AUTOMOTIVE GROUP -- 579.60 PLASTIC SEALER -- 8030-00-683-9014

===== Product Identification =====

Product ID:579.60 PLASTIC SEALER

MSDS Date:05/13/1988

FSC:8030

NIIN:00-683-9014

MSDS Number: BNRQT

=== Responsible Party ===

Company Name:UNITED TECHNOLOGIES AUTOMOTIVE GROUP

Address:1218 CENTRAL INDUSTRIAL DRIVE

City:ST LOUIS

State:MO

ZIP:63110

Country:US

Info Phone Num:314-577-1100

Emergency Phone Num:314-577-1100

Preparer's Name:WILLIAM R BEN

TON

CAGE:DO719

=== Contractor Identification ===

Company Name:INMONT CORP

Address:3738 CHOUTEAU AVE

Box:City:ST LOUIS

State:MO

ZIP:63110-2546

Country:US

CAGE:77464

Company Name:UNITED TECHNOLOGIES AUTOMOTIVE GROUP

Address:1218 CENTRAL INDUSTRIAL DRIVE

City:ST LOUIS

State:MO

ZIP:63110

Phone:314-577-1100

CAGE:DO719

===== Composition/Information on Ingredients =====

Ingred Name:POLYISOBUTYLENE

CAS:9003-27-4

RTECS #:UD1010000

Fraction by Wt: 20-60%

Other REC Limits:NONE SPECIFIED

Ingred Name:CALCIUM CARBONATE
CAS:471-34-1
RTECS #:FF9335000
Fraction by Wt: 20-60%
Other REC Limits:10 MG/M3

Ingred Name:TALC
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 10-30%
Other REC Limits:2 MG/M3

Ingred Name:PIGMENTS
CAS:9003-27-4
RTECS #:UD1010000
Fraction by Wt: TRACE
Other REC Limits:NONE SPECIFIED

Ingred Name:OCTADECANOIC ACID, ALUMINUM SALT
CAS:637-12-7
RTECS #:WI2820000
Fraction by Wt: 1-5%
Other REC Limits:10 MG/M3

Ingred Name:CELLULOSE
CAS:9004-34-6
RTECS #:FJ5691460
Fr
action by Wt: 1-5%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:NO SIGNIFICANT SIGNS OF ANY ADVERSE HEALTH
HAZARDS ARE EXPECTED TO OCCUR AS A RESULT OF INHALATION EXPOSURE OR
SKIN CONTACT. EYES AND SKIN CONTACT: LOW HAZARDS.

===== First Aid Measures =====

First Aid:EYE CONTACT: TAKE OUT AS WITH ANY OTHER FOREIGN OBJ

ECT. WASH

WITH PLENTY OF WATER FOR AT LEAST 10 MINUTES. IF ANY SYMPTOMS ARE PRESENT AFTER WASHING, GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:>200F,>93C

Extinguishing Media:CARBON DIOXIDE, ABC DRY CHEMICAL, WATER SPRAY AND FOAM.

Fire Fighting Procedures:RESPIRATORY AND EYE PROTECTION REQUIRED FOR FIRE FIGHTING PERSONNEL.

Unusual Fire/Explosion Hazard:NO UNUSUAL HAZARDS.

===== Accidental Release Measures

=====

Spill Release Procedures:RECOVER SPILLED MATERIAL AND PLACE IN A PROPER CONTAINER FOR REUSE OR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL DRY PLACE. ROTATE STOCK.

Other Precautions:FOR INDUSTRIAL USE ONLY. DO NOT BREATHE DECOMPOSITION PRODUCTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. SELF-CONTAINED BREA
THING

APPARATUS REQUIRED IF EXPOSURE TO DECOMPOSITION PRODUCTS IS LIKELY.

Ventilation:GENERAL DILUTION VENTILATION--9000 CFM DILUTION AIR.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:EYE WASH AND SAFETY SHOWERS SHOULD BE NEARBY.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity:1.27 +/-0.07

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIGHT GREEN OLIVE BEAD; NEGLIGIBL

E ODOR.

Percent Volatiles by Volume: