

GENERAL ELECTRIC CO., SILICONE PRODUCT DIV. -- RTV9858 SILICONE CATALYST SOLUTION --
8030-00-123-6955

===== Product Identification =====

Product ID:RTV9858 SILICONE CATALYST SOLUTION

MSDS Date:06/29/1988

FSC:8030

NIIN:00-123-6955

Kit Part:Y

MSDS Number: BNSXS

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO., SILICONE PRODUCT DIV.

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:518-237-3330

Emergency Phone Num:518-237-3330

Preparer's Name

:DA POLSINELLI

CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

Company Name:R.H.CARLSON COMPANY,INC.

Address:41-CHESTNUT STREET

Box:1687

City:GREENWICH

State:CT

ZIP:06830-5921

Country:US

Phone:203-531-5500

CAGE:33530

===== Composition/Information on Ingredients =====

Ingred Name:DIBUTYL TIN DILAU

RATE
CAS:77-58-7
RTECS #:WH7000000
Fraction by Wt: 5-10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.1 MG/M3
ACGIH TLV:0.1 MG/M3

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50: 175 (RAT) MG/KG. DERMAL
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGESTION: HARMFUL IF SWALLOWED. SKIN
CONTACT: CAUSES MODERATE SKIN IRRITATION. INHALATION: CAUSES

MODERATE RESPIRATORY IRRITATION. EYE CONTACT: MAY CAUSE SEVERE EYE
IRRITATION.

Explanation of Carcinogenicity:PRODUCT OR ONE OF ITS INGREDIENTS
PRESENT 0.1% OR MORE IS NOT LISTED AS A CARCINOGEN OR SUSPECTED
CARCINOGEN.

Effects of Overexposure:N/K LD50: 85 MG/KG IPR (RAT) MG/KG.
Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:INGEST: INDUCE VOMITING IMMED (GIVING 2 GLASSES WATER &
STICKING FINGERS
DOWN THROAT); NEVER GIVE ANYTHING TO UNCONSCIOUS
PERSON. GET MED AID. SKIN: REMOVE CONTAM CLOTHING & LAUNDER BEFORE
REUSE. WASH W/SOAP & WATER. REMOVE CONTAM SHOES, DISCARD. GET MED
AID IF IRRIT PERSISTS. INHAL: REMOVE TO FRESH AIR. IF NOT BREATH,
GIVE ARTIF RESP (MOUTH TO MOUTH), DIFFICULT BREATH, GIVE OXYGEN.
GET MED AID.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:200F,93C
Extinguishing Media:ALL STANDARD FIRE

FIGHTING MEDIA.

Fire Fighting Procedures:WEAR RESPIRATORY PROTECTION IF IN A CONFINED AREA.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAPE, SOAK UP IN INERT MAT'L. PUT IN CNTNR FOR DISPOSAL. WASH WALKING SURFACES W/DETERGENT & WATER TO REDUCE SLIPPING HAZARD. WEAR PROPER PROTECTIVE EQUIP. WARN OTHERS OF SPILL. INCREASE AREA VENTILATION.

===== Handling and Storage =====

Handling and

Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.

AVOID BREATHING VAPORS, IF EXPOSED TO HIGH VAPOR CONCENTRATION, LEAVE AREA AT ONCE. AVOID CONTACT W/SKIN, EYES.

Other Precautions:USE ONLY IN WELL VENTILATION AREA. KEEP AWAY FROM FOOD & SMOKING MAT'LS. WASH HANDS BEFORE EATING & SMOKING. CAUTION! ENGINEERING CONTROLS: EXHAUST VENTILATION, SHOWERS, EYEWASH STATIONS. USE LOCALIZE D VENTILATION TO CONTROL DUST LEVELS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE IN A WELL VENTILATED AREA. USE APPROVED NIOSH RESPIRATORY PROTECTION IF TLV EXCEEDED OR OVER EXPOSURE IS LIKELY.

Ventilation:USE ONLY IN WELL VENTILATED AREA. MECHANICAL VENTILATION.

Protective Gloves:RUBBER GLOVES.

Eye Protection:SAFETY GLASSES, MONOGOGGLES.

Other Protective Equipment:RUBBER APRON. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING.

Supplemental Safety and Health

(EMERG FIRST AID CONT'D) EYES: IMMEDIATELY FLUSH EYES WITH PLENTY OF

WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>545F,>285C

Vapor Pres:NEGLIGIBLE

Vapor Density:NEGLIGIBLE

Spec Gravity:1.61 (WATER=1)

Evaporation Rate & Reference: