PERMAGILE INDUSTRIES INC -- PG 2154, PART B, EPOXY HARDENER ______ MSDS Safety Information ______ FSC: 8030 NIIN: 00-878-2063 MSDS Date: 06/01/1992 MSDS Num: BNTLY Product ID: PG 2154, PART B, EPOXY HARDENER MFN: 05 Kit Part: Y Responsible Party Cage: 13549 Name: PERMAGILE INDUSTRIES INC Address: 101 COMMERCIAL ST City: PLAINVIEW NY 11803 Info Phone Number: DAY 516-349-1100/OTHE R 800-645-7546 Emergency Phone Number: 800-424-9300 CHEMTREC Preparer's Name: ABDUL QUERSHI Proprietary Ind: Y Review Ind: Y Published: Y ______ Preparer Co. when other than Responsible Party Co. ______ Cage: 13549 Name: PERMAGILE INDUSTRIES INC Address: 101 COMMERCIAL STREET City: PLAINVIEW NY 11803 ______ Contractor Summary _____ Cage: 13549 Name: PERMAGILE INDUSTRIES INC Address: 101 COMMERCIAL STREET City: PLAINVIEW NY 11803 Phone: 516-349-1100/800-424-9300(CHEMTREC) ______ Item Description Information ______ Item Manager: GSA Item Name: SEALING COMPOUND Unit of Issue: KT UI Container Qtv: 1

Type of Container: KIT

Ingredients ======

Name: *** PROPRIETARY ***

Health Hazards Data

LD50 LC50 Mixture: LD50 ORAL (RAT) 2330 MG/KG, LD50 DERMAL

Route Of Entry Inds - Inhalation: YES

Skin: YES Ingestion: YES

Effects of Exposure: VAPORS MAY IRRITATE EYES, RESP TRACT. CONTACT IRRITATING

TO EYES. SKIN SENSITIZATION, OTHER ALLERGIC RESPONSES. SEVE

RE SKIN IRRIT.

BLINDNESS, PERMANENT EYE INJURY. BREATHING VAPORS MAY AGGRAVATE ASTHM A. SEVERE EYE/SKIN BURNS. HARMFUL IF SWALLOWED/ABSORBED THRU SKIN. IF LIQUID IS HEATED. AVOID BREATHING VAPOR.

Explanation Of Carcinogenicity: SILICONE DIOXIDE IS CLASS 2A CARCINOGEN.

Signs And Symptions Of Overexposure: N/K (RBT) 800.0 MG/KG.

First Aid: MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NECESSARY. WASH SKIN W/SOAP & WATER/WATERLESS HAND CLEANER. REMOVE CONTAM CLOTHING. DON'T INDUC

E VOMITING. DRINK LRG QTY WATER IMMED. FLUSH EYES W/WAT ER 15 MIN, GET MED AID. DRINK LRG QTY MILK MIXED W/SALT. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON. IF SWALLOWED, CONTACT PHYSICIAN IMMEDIATELY. IF BREATHING DIFFICULT, OXYGEN MAY BE GIVEN.

Handling and Disposal

Spill Release Procedures: ABSORB W/SAND. DISPOSE OF IN APPROVED MANNER. REMOVE IGNITION SOURCES. WEAR P

ROTECTIVE CLOTHING. PREVENT SPILLAGE FROM ENTERING

UNDERGROUND WATER SYSTEMS. VENTILATE AREA. FLUSH AREA W/ WATER, NOT TO S EWER. REMAINING MAT'L MAY BE EMULSIFIEDW/SOAP & DESCRIPTION OF THE PROPERTY OF THE PR

Neutralizing Agent: N/K WATER AND ABSORBED. SCOOP UP CONTAM SOIL & amp; PLACE IN DRY DRUMS.

Waste Disposal Methods: INCINERATE IN APPROVED MANNER. DISPOSE OF IN ACCORDANCE WITH LOCAL REGULATIONS. IF TRANSPORT SPILL, CALL CHEMTREC 800-424-9300. LARGE SPILLS MAY BE PUMPED TO CLOSED BUT NOT SEALED CONTAINERS.

Handl

ing And Storage Precautions: PROTECT FROM FREEZING. OVERHEATING MAY CAUSE CONTAINER TO RUPTURE. STORE IN A COOL, DRY PLACE. KEEP AWAY FROM OPEN FLAMES. KEEP CNTNRS CLOSED.

Other Precautions: STORE IN TIGHTLY CLSD CNTNRS. STORE AWAY FROM FOOD AND BEVERAGE. WASH THOROUGHLY AFTER HANDLING. CHECK ALL CONTAINERS FOR LEAKS. WEAR PROTECTIVE CLOTHING. AVOID PROLONGED BREATHING OR SKIN CONTACT.

Fire and Explosion Hazard Information

=======

Flash Point Method: PMCC Flash Point Text: 250F,121C

Lower Limits: 1.4

Extinguishing Media: WATER FOG, FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY

CHEMICAL.

Fire Fighting Procedures: USE WATER FOG TO COOL CNTNRS. WEAR PROTECTIVE

CLOTHING. FIGHT FIRE FROM SAFE DISTANCE. CLOSE ALL VALVES TO AREA. SHUT OFF

POWER. USE EMERG LIGHTS. WEAR SCBA.

Unusual Fire/Explosion Hazard: UNDER FIRE CONDITIONS IRRITATING AND/OR TOXIC GASES MAY BE PRESENT.

=======

Control Measures

Respiratory Protection: MSHA/NIOSH RESPIRATOR HIGHLY RECOMMENDED. VAPOR RESPIRATION HIGHLY RECOMMENDED. SCBA IN CONC ABOVE PEL/TLV. AVOID BREATHING FUMES, MISTS, VAPORS WHICH CAN CAUSE SEVERE RESP DAMAGE. ALWAYS WORK IN AREA W/VENT TO ALLOW DISSIPATION OF FUMES.

Ventilation: PROVIDE ADEQUATE CROSS AIR CIRCULATION. EXHAUST AT POINT OF USE. MECHANICAL IN CONFINED AREAS

•

Protective Gloves: RUBBER OR NEOPRENE GLOVES.

Eye Protection: SPLASHPROOF SAFETY GOGGLES, CHEMICAL

Other Protective Equipment: EYEWASH STATION. EMERG SHOWER. BARRIER CREAM RECOMMENDED. CHEM APRON, RUBBER FOOT COVER, CLEAN LONG LEG/SLEEVE CLOTHES.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. WASH BEFORE EATING,

DRINKING, SMOKING OR USING TOILET.

Supplemental Safety and Health: KEY1:N1. WORKER GOGGLES. CHEMICAL SPLASH GOGGLES.

====

Physical/Chemical Properties

HCC: N1

Vapor Density: < AIR Spec Gravity: 1.51

Viscosity: SEE INGREDS

Evaporation Rate & Dry Reference: SLOWER THAN N-BUTYL AC

Solubility in Water: NEGLIGIBLE (

Appearance and Odor: BLACK PASTE, AMINE ODOR.

Reactivity Data

Stability Indicator: YES

Materials To Avoid: STRONG OXIDIZING AGENTS.

STRONG ACIDS. ORGANIC HALIDES. Hazardous Decomposition Products: OXIDES OF CARBON, OXIDES OF NITROGEN. TOXIC MONOMER FUMES AND/OR SHORT CHAIN HYDROCARBONS. Hazardous Polymerization Indicator: NO _____ **Toxicological Information** _____ -----Ecological Information ______ _____ _____ **MSDS** Transport Information ______ _____ Regulatory Information _____ _____ Other Information _____ _____ Transportation Information _____ _____ Responsible Party Cage: 13549 Trans ID NO: 89685

Product ID: PG 2154, PART B, EPOXY HARDENER

MSDS Prepared Date: 06/01/1992

Review Date: 08/10/1992

MFN: 5

Multiple KIT Number: 0

Kit Part IND: Y
Review IND: Y
Unit Of Issue: KT
Container QTY: 1
Type Of Container: KIT

Detail DOT Information

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRAN

SPORTATION

Detail IMO Information

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

Product ID: PG 2154, PART B, EPOXY HARDENER

Cage: 13549

Company Name: PERMAGILE INDUSTRIES INC

Street: 101 COMMERCIAL STREET

City: PLAINVIEW NY Zipcode: 11803

Health Emergency Phone: 8 00-424-9300 CHEMTREC Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998 Origination Code: G

Hazard And Precautions: VAPORS MAY IRRITATE EYES, RESP TRACT. CONTACT IRRITATING TO EYES. SKIN SENSITIZATION, OTHER ALLERGIC RESPONSES. SEVERE SKIN IRRIT. BLINDNESS, PERMANENT EYE INJURY. BREATHING VAPORS MAY AGGRAVATE ASTHM A. SEVERE EYE/SKIN BURNS. HARMFUL IF SWALLOWED/ABSORBED THRU SKIN. IF LIQUID IS HEATED, AVOID BREATHING VAPOR. N/K * (RBT) 8

0.00

MG/KG.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting wit

h any instrumentality of the United

States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.