

DYNATRON/BONDO CORP -- NO. 6292 DENT FILLER COMP B -- 8010-00-926-2133

===== Product Identification =====

Product ID:NO. 6292 DENT FILLER COMP B

MSDS Date:10/03/1991

FSC:8010

NIIN:00-926-2133

Kit Part:Y

MSDS Number: BNWPY

=== Responsible Party ===

Company Name:DYNATRON/BONDO CORP

Address:2160 HILLS AVE

City:ATLANTA

State:GA

ZIP:30318-2217

Country:US

Info Phone Num:404-696-2730

Emergency Phone Num:

404-696-2730/800-241-3386

Preparer's Name:M WHEELLOCK

CAGE:16522

=== Contractor Identification ===

Company Name:BONDO/MAR-HYDE CORP

Address:3700 ATLANTA INDUSTRIAL PKWY NW

Box:City:ATLANTA

State:GA

ZIP:30331

Country:US

Phone:404-696-2730

CAGE:16522

===== Composition/Information on Ingredients =====

Ingred Name:DIBENZOYL PEROXIDE (SARA 313)

CAS:94-36-0

RTECS #:DM8575000

Fraction by Wt: 48% OR >

Other REC Limits:5MG/M3 TWA/10HR SHFT

Ingred Name:BUTYL BENZYL PHTHALATE (SARA 313)

CAS:85-68-7
RTECS #:TH9990000
Fraction by Wt: < 30%
Other REC Limits:NONE SPECIFIED
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EYE IRRITATION, MINOR SKIN IRRITATION.
Explanation of Carcinogenicity:NONE OF THE COMPONENTS OF THIS MATERIAL AREA LISTED AS CARCINOGENS BY NTP, IARC OR OSHA.
Effects of Overexposure:EYES: MAY CAUSE EYE IRRITATION. SKIN: PROLONGED SKIN CONTACT MAY CAUSE SKIN IRRITATION AND REDNESS. INHALATION: MAY CAUSE IRRITATION OF THE NOSE, THROAT AND LUNGS. INGESTION: MAY CAUSE TOXIC EFFECTS.
Medical Cond Aggravated by Exposure:NO INFORMATION FOUND.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES & CONTACT PHYSICIAN. SKIN: WASH IMMEDIATELY WITH SOAP & WATER. CONSULT A PHYSICIAN IF DISCOMFORT DEVELOP
S. INHALATION: REMOVE TO FRESH AIR. CON SULT A PHYSICIAN IF DISCOMFORT PERSISTS. INGESTION: ADMINISTER LARGE QUANTITIES OF WATER IF PERSON IS CONSCIOUS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IMMEDIATELY CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:>200F,>93C
Extinguishing Media:WATER FOG OR SPRAY, CO2, DRY CHEMICAL FOAM.
* @ 68 F, BY WEIGHT.
Fire Fighting Procedures:EV

ACUATE AREA AND APPLY WATER FROM A SAFE DISTANCE.

Unusual Fire/Explosion Hazard:PEROXIDES AND DECOMPOSITION PRODUCTS ARE FLAMMABLE AND CAN IGNITE WITH EXPLOSIVE FORCE IF CONFINED.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID CONTACT W/SKIN. MAT'L LEFT UNCONVERED COULD INCREASE FIRE HAZARD DUE TO EVAPORATION OF WATER & LEACHING OF PLASTICIZER AWAY FROM BENZOYL PEROXIDE. DIKE TO PREVENT RUNOFF FROM ENTERING DRAINS, SE WERS , STREAMS, ETC TRANSFER INTO CNTNR.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM ALL SOURCES OF HEAT & IGNITION SUCH AS RADIATORS, STEAM PIPES & DIRECT SUNLIGHT. DO NOT STORE NEAR COMBUSTIBLES.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. DO NOT BREATHE VAPORS. KEEP CONTAINERS CLOSED. KEEP FROM FREEZING. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES. IF DISCARDED, MAT'L/CNTNR ARE CONSIDERED RCRA HAZARDOUS WASTE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED IF TLVS ARE EXCEEDED.

Ventilation:MECHANICAL.

Protective Gloves:NEOPRENE OR POLYVINYL ALCOHOL.

Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment:EYEWASH STATION SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS WITH SOAP AND WATER AFTER EVERY USAGE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3

Decomp Temp:Decomp Text:200F,93C

Spec Gravity:1.2 +/- .15 @77F

Viscosity:**

Solubility in Water: