

NILES CHEMICAL PAINT CO -- XE-9863A CARC BLACK TYPE II -- 8010-01-141-2419

=====
Product Identification
=====

Product ID:XE-9863A CARC BLACK TYPE II

MSDS Date:10/06/1991

FSC:8010

NIIN:01-141-2419

Kit Part:Y

MSDS Number: BNWTB

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT ST

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377 OR 219-236-585

6

Emergency Phone Num:616-683-3377 OR 219-236-5856

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYESTER RESIN

Fraction by Wt: 14%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:NOT ESTABLISHED

Ingred Name:METHYL ETHYL KETONE (SARA 313)

(VAPOR PRESSURE 71.2 HG @
20C)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 11%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM/300 PPM STEL

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:BUTYL ACETATE (VAPOR PRESSURE 10 MM HG @ 20C)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM

ACGIH TLV:150 PPM/200 PPM STEL

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:PM ACETATE (VAPOR PRESSURE 3.7 MM HG @ 20C)

CAS:

108-65-6

RTECS #:AI8925000

Fraction by Wt: 9%

Other REC Limits:NONE SPECIFIED

Ingred Name:METHYL ISOBUTYL KETONE (SARA 313) (VAPOR PRESSURE 15 MM HG
@ 20C)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 6%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:BLACK PIGMENT

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3

Ingred Na

me:PROPRIETARY INGREDIENTS (VAPOR PRESSURE 0 MM HG @ 20 C)

Fraction by Wt: BALANCE

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 4.56 LBS/GAL

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYES: SEVERE IRRITATION,
LACRIMATION, REDNESS, BLURRED VISION. SKIN: REDNES

S, IRRITATION,

DEFATTING OF THE SKIN LEADING TO DERMATITIS. BREATHING: NASAL &
RESPIRATORY IRRITATION, CNS DEPRESSION, ASPHYXIATION. SWALLOWING:
GASTROINTESTINAL IRRITATION. CHRONIC: HISTOLOGIC FIBROSIS OF LUNGS,
NARCOSIS, COMA.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:BREATHING: DIZZINESS, DROWSINESS, WEAKNESS,
FATIGUE, CONFUSION, NAUSEA, HEADACHE, VERTIGO, POSSIBLE
UNCONSCIOUSNESS. SWALLOWING: ABDOMINAL PAIN, NAUSEA, VOMITING,
DIARRHEA.

Medical C

ond Aggravated by Exposure:NONE KNOWN. TARGET ORGANS:

RESPIRATORY SYSTEM, CNS, LUNGS, EYES, SKIN.

=====
===== First Aid Measures =====

First Aid:INHAL: MOVE TO FRESH AIR. IF BREATHING STOPPED, START ARTIF
RESP. GET MED AID. SKIN: IMMED FLUSH W/WATER. IF MAT'L PENETRATES
CLOTHING, REMOVE CONTAM CLOTHING & FLUSH SKIN W/WATER. GET MED AID.

EYE: I MMED FLUSH W/LRG AMT WATER 15 MIN, LIFTING EYELIDS. GET MED
AID IMMED. SWALLOWING: DRINK 1-2 GLASSES

WATER. DON'T INDUCE

VOMITING. CONSULT PHYSICIAN/POISON CONTROL CENTER IMMED. TREAT
SYMPTOMATICALLY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:20.0F,-6.7C

Lower Limits:1.3

Upper Limits:10.0

Extinguishing Media:DRY CHEMICAL, FOAM, CO2

Fire Fighting Procedures:WEAR POS PRESS SCBA W/FULL FACEPIECE & FULL

PROTECTIVE CLOTHING. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO
PREVENT PRESS BLD UP & AUTO IGNIT/EXPLOS.

Unusual

Fire/Explosion Hazard:VAPOR HEAVIER THAN AIR, TRAVEL TO IGNIT SOURCE. ISOLATE FROM IGNIT SOURCE. CLSD CNTNR EXPLODE W/HEAT. APPLICATION TO HOT SURFACES REQUIRE SPECIAL PRECAUTIONS.*

===== Accidental Release Measures =====

Spill Release Procedures:NO IGNIT SOURCES. MINIMIZE BREATHING VAPORS. AVOID SKIN CONTACT. SMALL: ABSORB W/INERT MAT'L(CLAY, SOIL, COMMERC ABSORB). SHOVEL RECLAIMED LIQ & ABSORB INTO RECOVERY/SALVAGE DRUMS. LRG:DIKE(NO FURTHER MOVEMENT)& RECLAIM INTO SALVAGE DRUMS/TANK TRUCK.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMPERATURE AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. AVOID ROUGH HANDLING.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY. DO NOT WELD OR FLAME CUT ON EMPTY DRUMS. DO NOT WEAR CONTACT LENSES WHEN WORKING WITH THIS MATERIAL.

=====

= Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR APPROPRIATE (TC-23C-75) FITTED HALF-MASK OR FULL FACEPIECE RSPRTR (NIOSH/MSHA) DURING & AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS BELOW TLV. FOLLOW RESPIRATOR MFR DIR ECTIONS FOR USE.

Ventilation:PROVIDE SUFFICIENT VENTILATION (VOLUME/PATTERN) TO KEEP AIR CONC BELOW TLV PEL. REMOVE DECOMP PROD. VENT VAPOR EMITTED.

Protective Gloves:CHEM RESISTANT GLOVES-NITRILE OR VIT ON

Eye Protection:CHEM GOGGLES/SAFETY GLASSES/FACE SHIELDS

Work Hygienic Practices:WASH ANY CONTAM CLOTHING OR CLOTH THAT BECOMES WET BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING RESTROOM.

Supplemental Safety and Health
KEY1=F3.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175 TO 302F

Vapor Density:> AIR

Spec Gravity:10.84 LB/GL

Viscosity:70-85 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGH

T

Appearance and Odor:LIQUID, ODOR OF SOLVENT.

Percent Volatiles by Volume:64.14

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDS.

Stability Condition to Avoid:N/K *OVEREXPOS TO DECOMP

PROD MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMED APPARENT.
GET MED AID.

Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND/OR
CARBON DIOXIDE.

Conditions to Avoid Polymerizat

ion:HIGH TEMPERATURES, SHOCK FROM
DROPPING.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE &
LOCAL REGULATIONS. EPA HAZARDOUS WASTE CODE: D001 (IGNITABLE).

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants th
is information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.