

PLASTODENT INC -- 2251 OIL -- 6520-00-299-9643

===== Product Identification =====

Product ID:2251 OIL

MSDS Date:03/20/1989

FSC:6520

NIIN:00-299-9643

MSDS Number: BPBXZ

=== Responsible Party ===

Company Name:PLASTODENT INC

Address:2881 MIDDLETOWN RD

City:BRONX

State:NY

ZIP:10461-5306

Country:US

Info Phone Num:212-792-3554

Emergency Phone Num:212-792-3554, 713-236-6070

CAGE:GO326

=== Contractor Identification ===

Company Name:PLASTODENT INC

Address:2881 MIDDLETO

WN RD

City:BRONX

State:NY

ZIP:10461-5306

Country:US

Phone:609-893-1100

CAGE:GO326

Company Name:PLASTODENT INC.

Address:2881 MIDDLETON ROAD

Box:City:BRONX

State:NY

ZIP:10461-3306

Country:US

Phone:212-792-3554

CAGE:8P273

===== Composition/Information on Ingredients =====

Ingred Name:ACID-TREATED LIGHT PETROLEUM DISTILLATE

CAS:64742-14-9

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 OIL MIST

ACGIH TLV:5 MG/M3 OIL MIST9192

===== Hazards I

dentification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: IRRITATION.

PROLONGED CONTACT CAN CAUSE DEFATTING, DRYING, IRRITATION AND DERMATITIS. INHALATION: IRRITATION OF RESPIRATORY TRACT, CNS DEPRESSION. INGESTION: GI DISTRESS. LARGE DOSE MAY RESULT IN DROWSINESS, NUMBNESS, HEADACHE,

DIZZINESS, NAUSEA, LOSS OF

CONSCIOUSNESS, CONVULSIONS, DEATH.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION, DEFATTING, DRYING, DERMATITIS. INHALATION: RESPIRATORY TRACT IRRITATION.

CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION: GASTROINTESTINAL DISTRESS, DROWSINESS, NUMBNESS, HEADACHE, DIZZINESS AND NAUSEA. IN

EXTREME CASES, UNCONSCIOUSNESS, CONVULSIONS AND DEATH MAY OCCUR.

Medical Cond Aggravated by Exposure:PERSON WITH PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AREA WITH SOAP AND WATER. IF IRRITATION PERSISTS

GET MEDICAL

ATTENTION. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING GIVE CPR. IF BREATHING DIFFICULT GIVE OXYGEN. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:170F,77C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND FULL FACED SELF CONTAINING

D BREATHING APPARATUS. WATER MAY BE  
INEFFECTIVE BUT USE TO COOL CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE GENERATED WHILE  
BURNING. CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER OXIDES MAY BE  
GENERATED AS PRODUCTS OF COMBUSTION.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. WEAR  
APPROPRIATE PROTECTIVE EQUIPMENT. CONTAIN SPILL. DO NOT ALLOW SPILL  
TO ENTER SEWERS OR WA  
TERCOURSES. ABSORB WITH INERT MATERIAL SUCH AS  
SAND, CLAY. PLACE WASTE IN S UITABLE CONTAINERS FOR PROPER  
DISPOSAL.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, WELL VENTILATED AREA  
IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAMES, OXIDIZING  
MATERIALS. HAVE FIRE EXTINGUISHERS AVAILABLE  
Other Precautions:"EMPTY" CONTAINERS CAN CONTAIN EXPLOSIVE VAPO  
RS. DO  
NOT CUT, DRILL, GRIND, WELD OR PERFORM SIMILAR OPERATIONS ON OR  
NEAR CONTAINERS. STATIC ELECTRICITY MAY ACCUMULATE AND CREATE A  
FIRE HAZARD. GROUND CONTAINERS, FIXED AND TRANSFER EQUIPMENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED UNDER NORMAL USE. IF EXPOSURE  
EXCEEDS OCCUPATIONAL EXPOSURE LIMITS, USE A NIOSH/MSHA APPROVED  
ORGANIC VAPOR RESPIRATOR WITH A DUST AND MIST FILTER. DO NOT USE  
COMPRESSED OXY  
GEN IN HYDROCA RBON ATMOSPHERES.  
Ventilation:USE EXPLOSION-PROOF LOCAL AND/OR MECHANICAL VENTILATION.  
AVOID OPEN ELECTRICAL SOURCES NEAR PRODUCT VAPOR AREAS.  
Protective Gloves:NOT REQUIRED FOR SHORT EXPOSURES.  
Eye Protection:NOT REQUIRED FOR NORMAL USE  
Other Protective Equipment:INDUSTRIAL WORK CLOTHING TO MINIMIZE  
CONTACT. RUBBER APRON AD BOOTS AS REQUIRED. EYE BATH AND SAFETY  
SHOWER RECOMMENDED.  
Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,  
DRINKING, OR SMOKING

. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE

Supplemental Safety and Health

CONSUMPTION OF FOOD AND BEVERAGE SHOULD BE AVOIDED IN WORK AREAS WHERE  
HYDROCARBONS ARE PRESENT.

===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:375F,191C

Vapor Pres:< 1

Vapor Density:4.5

Spec Gravity:0.78

Evaporation Rate & Reference: