View NSN Online: https://aerobasegroup.es/nsn/9140-00-286-5296

CHEVRON ENVIRONMENTAL HEALTH CENTER INC. -- HEATING FUEL NO 1 -- 9140-00-286-5296

Product ID:HEATING FUEL NO 1

MSDS Date:01/03/1992

FSC:9140

NIIN:00-286-5296

MSDS Number: BPFWJ === Responsible Party ===

Company Name: CHEVRON ENVIRONMENTAL HEALTH CENTER INC.

Address:15299 SAN PABLO AVE.

Box:4054

City:RICHMOND

State:CA ZIP:94804 Country:US

Info Phone Num:415-233-373

7 OR 800-582-3835

Emergency Phone Num:415-233-3737 OR 800-457-2022

CAGE:0AHD1

=== Contractor Identification ===

Company Name: CHEVRON ENVIRONMENTAL HEALTH CENTER INC

Address:15299 SAN PABLO AVE

Box:4054

City:RICHMOND

State:CA ZIP:94804 Country:US

Phone:800-582-3835

CAGE:0AHD1

======= Composition/Information on Ingredients ========

Ingred Name: ALIPHATIC PETROLEUM SOLVENT/KEROSENE

CAS:8008-20-6

RTECS #:OA5500000

Other REC Limits: NONE RECOMMENDED

Ingred Name: KEROSENE/KEROSENE HYDRODE

SULFURIZED
CAS:64742-81-0
Other REC Limits:NONE RECOMMENDED

Ingred Name:DISTILLATES, HYDROSULFURIZED MIDDLE

CAS:64742-80-9

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name: DISTILLATES, STREIGHT RUN MIDDLE

CAS:64741-44-2 RTECS #:LX3296000 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name: KEROSENE, HYDRODESULFURIZED

CAS:64742-81-0

Other REC Limits: NONE SPECIFIED

Ingred Name:LIGHT HYDROCARBON BLEND

CAS:64741-59-9

Other REC Limits: NONE SPECIFIED


LD50 LC50 Mixture:ORAL LD50 (RAT) IS > 5ML/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-INHALED:IRRITATES RESPIRATORY TRACT,HEADACHE,NAUSEA,DIZZINESS,LOSS OF APPETITE,WEAKNESS,LOSS OF COORDINATION.EYES:IRRITATION.SKIN:PROLONGED/REPEATED CONTACT CAN CAUSE PAIN,SWE

LLING,BLISTERING.IN GESTION:MAY IRRITATE DIGESTIVE TRACT.ASPIRATION INTO THE LUNG MAY CAUSE LUNG DAMAGE.CHRONIC-SKIN DISCOLORATION,BLISTERS.

Explanation of Carcinogenicity: THE NIOSH HAS RECOMMENDED THAT WHOLE DIESEL EXHAUST BE REGARDED AS POTENTIALLY CAUSING CANCER.

Effects of Overexposure:INHALATION CAUSES IRRITATION OF RESPIRATORY TRACT, HEADACHE, NAUSEA, DIZZINESS, LOSS OF APPETITE, WEAKNESS, AND LOSS OF COORDINATION. IRRITATES EYE. PROLONGED OR REPEATED SKIN CONTACT C



Spill Release Procedures:REMOVE SOURCE OF HEAT,SPARKS,FLAME,FRICT ION &

ELECTRICITY,INCLUDING INTERNAL COMBUSTION ENGINE.USE EXPLOSION-PROOF EQUIPMENT TO CLEAN UP.DIKE SPILL.PREVENT LIQUID FROM ENTERING SEWERS,WATERWAYS/LOW AR EAS.SOAK UP WITH SAWDUST,SAND,OIL DRY.SHOVEL/SWEEP

========== Handling and Storage ============

Handling and Storage Precautions:STORAGE-STORE IN COOL, DRY WELL-VENTILATED AREA IN CLOSED CONTAINER AWAY FROM HEAT, IGNITION SOURCES & OXIDIZERS.

Other Precautions: COMBUSTIBLE LIQUID. USE WITH AD

EQUATE VENTILATION.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. GROUND AND BOUND CONTAINERS TO PREVENT STATIC SPARKS. USE EXP LOSION-PROOF ELECTRICAL SERVICES.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:IN SITUATION WHERE VAPOR CONCENTRATIONS MAY EXCEED THE RECOMMENDED EXPOSURE LIMITS, A NIOSH-APPROVED ORGANIC VAPOR CARTRIDGE RESPIRATOR SHOULD BE WORN. USE SELF-CONTAINED SUPPLIED

-AIR RESPIRATOR FOR E MERGENCIES.

Ventilation:GENERAL DILUTION OR MECHANICAL VENTILATION/EXPLOSION-PROOF LOCAL EXHAUST TO KEEP VAPOR BELOW RECOMMENDED EXPOSURE LIMITS

Protective Gloves: NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection: USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:EYE WASH STATION.BARRIER CREAMS SPECIFIC FOR PETROLEUM-BASED MATERIALS MAY BE USED WHEN GLOVES ARE IMPRACTICAL. Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.

WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PIN A SAME NSN. EMPTY CONTAINERS MAY CONTAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE TO HEAT, F LAME; THEY MAY EXPLODE. DO NOT USE PRESSURE TO EMPTY DRUM OR DRUM MAY RUPTURE WITH EXPLOSIVE FORCE.

=======================================	Physical/Chemical Properties	
---	------------------------------	--

HCC:F

1

Boiling Pt:B.P. Text:400F,204C

Spec Gravity:0.85

Solubility in Water: INSOLUBLE

Appearance and Odor:PALE YELLOW LIQUID WITH MILD PETROLEUM ODOR

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS SUCH AS CHLORATES, NITRATES, PEROXIDES, ETC. Stability Condition to Avoid:HIGH HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations ==========

Waste Disposal Methods:WASTE MAY BE BURNED IN AN APPROVED INCINERATOR. TREATMENT, STORAGE, TRANSPORTATION AND DISPOSAL MUST BE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or

implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.