

J & R INDUSTRIES INC. -- WS-516A ACCELERATOR -- 8030-00-684-8790

===== Product Identification =====

Product ID:WS-516A ACCELERATOR

MSDS Date:01/01/1987

FSC:8030

NIIN:00-684-8790

Kit Part:Y

MSDS Number: BPFYX

=== Responsible Party ===

Company Name:J & R INDUSTRIES INC.

Address:800 EAST ANAHEIM STREET

City:WILMINGTON

State:CA

ZIP:90744

Country:US

Info Phone Num:213-830-9904

Emergency Phone Num:213-8

30-9904

CAGE:DO380

=== Contractor Identification ===

Company Name:J & R INDUSTRIES, INC

Address:800 EAST ANAHEIM STREET

City:WILMINGTON

State:CA

ZIP:90744

Phone:310-476-7121

CAGE:DO380

Company Name:J AND R INDUSTRIES (FACTORY LOCATION)

Address:800 E. ANAHEIM ST

Box:City:WILMINGTON

State:CA

ZIP:90744

Country:US

Phone:310-476-7121

CAGE:7X230

===== Composition/Information on Ingredients =====

Ingred Name:LEAD DIOXIDE

CAS:1309-60-0

RTECS #:OG0700000

Fraction by Wt: 70%

Other REC

Limits:NONE SPECIFIED

Ingred Name:PLASTICIZER TERPHENYL  
Fraction by Wt: 26%  
Other REC Limits:NONE SPECIFIED

Ingred Name:ZINC STEARATE  
CAS:557-05-1  
RTECS #:ZH5200000  
Fraction by Wt: 2%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:STEARIC ACID  
CAS:57-11-4  
RTECS #:WI2800000  
Fraction by Wt: 2%  
Other REC Limits:NONE SPECIFIED

===== First Aid Measures =====

First Aid:WASH WITH PLENTY OF SOAP AND WATER.

=

===== Fire Fighting Measures =====

Flash Point:400F,204C  
Extinguishing Media:STANDARD COMMERCIAL EXTINGUISHER  
Fire Fighting Procedures:STANDARD  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:WASH WITH PLENTY OF WATER.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINS TOXIC LEAD COMPOUND. AVOID  
CONTACT WITH SKIN AND

INGESTION. ALWAYS WASH HANDS BEFORE EATING & SMOKING.

Other Precautions:IF ACCELERATOR CONTACTS SKIN FLUSH AREA WITH WARM WATER. IN CASE OF INGESTION OBTAIN MEDICAL ATTENTION. STORE IN CLOSED CONTAINERS AWAY FROM HEAT OR FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE ADEQUATE VENTILATION.

Protective Gloves:USE PROTECTIVE GLOVES

Eye Protection:USE GOGGLES

Supplemental Safety and Health

KEY1;D2.HMIS(LEVIEN) NOTES THAT LEAD DIOXID

E IS DOT CLASS 5.1(OXIDIZER)

AND REQUIRES A LABEL.

===== Physical/Chemical Properties =====

HCC:F4

Spec Gravity:1.5

Evaporation Rate & Reference:NONE

Solubility in Water:NONE

Appearance and Odor:BROWN PASTE

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID CONTACT WITH SKIN. CONTAINS LEAD.

===== Disposal Considerations =====

Waste Disposal Methods:SAME PROCEDURES AS FOR TOXIC LEAD PRODUCTS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verif

y and  
assume responsibility for the suitability of this information to their  
particular situation.