

AMOCO OIL CO -- MULTI-PURPOSE GEAR LUBRICANT NO. 140 -- 9150-01-035-5395

=====
Product Identification
=====

Product ID: MULTI-PURPOSE GEAR LUBRICANT NO. 140

MSDS Date: 08/15/1986

FSC: 9150

NIIN: 01-035-5395

MSDS Number: BPGDL

=== Responsible Party ===

Company Name: AMOCO OIL CO

Address: 200 EAST RANDOLPH DR

City: CHICAGO

State: IL

ZIP: 60601

Country: US

Info Phone Num: 312-856-3907

Emergency Phone Num: 800-44

7-8735; 800-424-9300 (CHEMTREC)

Preparer's Name: STEPHEN A. ELBERT

CAGE: 15958

=== Contractor Identification ===

Company Name: AMOCO CHEMICALS CORP

Address: 200 E RANDOLPH DR MC 4001

Box: City: CHICAGO

State: IL

ZIP: 60601-6401

Country: US

CAGE: 15965

Company Name: AMOCO OIL CO

Address: 200 E RANDOLPH DR

Box: City: CHICAGO

State: IL

ZIP: 60601-6401

Country: US

Phone: 312-856-3907- EM HLTH: 800 447-8735

CAGE: 15958

=====
Composition/Information on Ingredients
=====

Ingred Name: MINERAL OIL PETROLEU

M DISTILLATES HYDROTREATED HEAVY
PARAFFINIC;(HYDROFINISHED,SOLVENT REFINED PARAFFINIC PETROLEUM OIL)
CAS:64742-54-7
RTECS #:PY8035500
Other REC Limits:5 MG/M3 OIL MIST

Ingred Name:SOLVENT REFINED RESIDUUM
CAS:64742-01-4

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN:NONE EXPECTED FOR SINGLE
SHORT-TERM EXPOSURES. PROLONGED OR REPEATED CONTACT MAY PRODUCE
SOME IRRITATION. EYE: NO SIGNIFICANT IRRITATION EXPECTED.
INGEST:RELATIVELY NON-TOXIC. INHAL:NONE EXPECTED UNDER NORMAL
CONDITIONS OF USE.
Effects of Overexposure:EYE IRRITATION
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYE:FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.
SKIN:FLUSH WITH
COPIOUS AMOUNTS OF WATER. CALL MD . INHAL:MOVE TO
FRESH AIR. SUPPORT BREATHING (GIVE O2/ARTF RESP) . INGEST:IF A LARGE
AMOUNT IS SWALLOWED, INDUCE VOMITING. GET MD.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:>400F,>204C
Extinguishing Media:AGENTS APPROVED FOR CLASS B HAZARDS (E.G., DRY
CHEMICAL, CARBON DIOXIDE, HALOGENATED AGENTS, FOAM, STEAM) OR WATER
FOG.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL
PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:NONE.

=====
Accidental Release Measures
=====

Spill Release Procedures:TREAT AS AN OIL SPILL. CONTAIN AND REMOVE BY
MECHANICAL MEANS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID STRONG OXIDIZERS.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
Exposure Controls/Personal
=====

Protection =====

Respiratory Protection:NONE REQUIRED FOR NORMAL CONDITIONS OF USE.

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.89 (WATER=1

)

Solubility in Water:NEGLIGIBLE (