

STA-LUBE INC -- COMPRESSOR OIL #22133 -- 9150-00-147-9018

===== Product Identification =====

Product ID:COMPRESSOR OIL #22133

MSDS Date:03/28/1991

FSC:9150

NIIN:00-147-9018

MSDS Number: BPHGH

=== Responsible Party ===

Company Name:STA-LUBE INC

Address:3039 ANA ST

City:RANCHO DOMINGUEZ

State:CA

ZIP:90221

Country:US

Info Phone Num:213-537-5650

Emergency Phone Num:213-664-2121,800-424-9300(CHEMTREC)

Preparer's Name:D.C.MARKIE

CAGE:33876

=== Contractor Identification ===

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

Company Name:STA-LUBE INC

Address:3039 ANA ST

Box:City:RANCHO DOMINGUEZ (PART OF COMPTON)

State:CA

ZIP:90221

Country:US

Phone:310-664-2121/800-424-9300(CHEMTREC)

CAGE:33876

Company Name:UNI-KEM INTERNATIONAL

Address:1001 HARIMAW COURT EAST

Box:City:METAIRIE

State:LA

ZIP:70001

C

country:US
Phone:504-835-7600/FAX:504-835-7608
CAGE:4S446

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT REFINED LIGHT NAPHTHENIC DISTILLATES
CAS:64741-97-5
RTECS #:PY8041000
Other REC Limits:5 MG/M3 OIL MIST
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:5 MG/M3 OIL MIST9293

Ingred Name:SOLVENT REFINED HEAVY NAPHTHENIC DISTILLATE
CAS:64741-96-4
RTECS #:PY8040000
Other REC Limits:5 MG/M3 OIL MIST
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:5 MG/M3 OIL MIST9293

Ingred Name:MINERAL OIL
CAS:8012-95-1
RTECS #:PY8030000
Other REC Limits:5 MG/M3 OIL MIST
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:5 MG/M3 OIL MIST9293

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PETROLEUM MIXTURES DO NOT USUALLY
PRESENT A HEALTH RISK UNDER NORMAL CONDITIONS OF USE. EYES:
IRRITATION, TEARING, REDNESS. SKIN: IRRITATION,
DERMATITIS.
INHALATION: OIL MISTS OR VAPORS GENERATED AT HIGH TEMPERATURES MAY
IRRITATE NOSE, THROAT, UPPER RESPIRATORY TRACT. INGESTION:
IRRITATION OF STOMACH, INTESTINAL TRACT.
Explanation of Carcinogenicity:DATA PER MSDS
Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION. INHALATION:
IRRITATION OF UPPER RESPIRATORY TRACT. INGESTION: NAUSEA, VOMITING,
DIARRHEA.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN CONDITIONS,
PRE-EXISTING RESPIRATORY CONDITI

ONS IF MISTS OR FUMES ARE
GENERATED.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AREA WITH SOAP AND WATER. IF ADVERSE SYMPTOMS DEVELOP, GET MEDICAL ATTE NTION. INHALATION: MOVE TO FRESH AIR. IF ADVERSE SYMPTOMS DEVELOP, GET MEDICAL ATTENTION. INGESTION: IF VICTIM IS CONSCIOUS AND ALERT, GIVE MILK OR WATER TO DRINK. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>400F,>204C
Autoignition Temp:Autoignition Temp Text:>400F
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY. WATER SPRAY OR FOAM MAY CAUSE FROTHING.
Fire Fighting Procedures:USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS, DILUTE AND DISPERSE VAPORS, PROTECT PERSONNEL, AND FLUSH UNIGNITED MATERIAL SPILLS AWAY FROM FIRE.
Unusual
Fire/Explosion Hazard:PRODUCT CAN IGNITE/BURN WHEN HEATED ABOVE FLASH POINT. EMPTY CONTAINERS RETAIN MATERIAL RESIDUE AND MAY, IF HEATED, GENERATE VAPORS WHICH CAN IGNITE OR EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE ADEQUATE VENTILATION. DO NOT ALLOW SPILLS TO ENTER SEWERS, STREAMS OR SURFACE WATERS. DIKE AND CONTAIN SPILLS. PICK UP LARGE SPILLS FOR LATER RECLAMATION AND DISPOSAL. PICK UP RESIDUE/SMALL SPILLS WITH INERT ABSORBENT. COLLECT FOR DISPOSAL.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE/USE IN CLOSED CONTAINERS IN COOL, DRY, WELL VENTILATED AREA AWAY FROM HEAT AND STRONG OXIDIZING AGENTS. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.
Other Precautions:MISUSE OF EMPTY CONTAINERS CAN BE HAZARDOUS. COMPLETELY DRAIN AND COMMERCIALY CLEAN BEFORE REUSE. KEEP CLOSED AND DO NOT US

E TO STORE OR MIX OTHER MATERIALS BEFORE COMMERCIALY
CLEANING. DO NOT CUT, WELD, DRILL, OR EXPOSE TO HEAT OR FLAME.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED. USE NIOSH/MSHA APPROVED
PARICULATE RESPIRATOR IN SITUATIONS WHERE MISTS CONCENTRATIONS MAY
EXCEED RECOMMENDED EXPOSURE LIMITS. USE SELF-CONTAINED SUPPLIED-AIR
RESPIRATORS FOR EMER GENCIES.

Ventilation:GENERAL VENTILATION OR LOCAL EXHAUST RECOMMENDED TO

MAINTAIN MIST/FUME CONCENTRATIONS BELOW RECOMMENDED EXPOSURE
LIMITS.

Protective Gloves:PROTECTIVE GLOVES RECOMMENDED.

Eye Protection:SAFETY GOGGLES RECOMMENDED.

Other Protective Equipment:AN EYE WASH STATION AND A SOURCE OF RUNNING
WATER SHOULD BE AVAILABLE TO FLUSH OR WASH THE EYES AND SKIN.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED

EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO

NOT BREATHE VAPORS OR MISTS.

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres:NEGLIGIBLE

Vapor Density:>1.0

Spec Gravity:0.85-0.95

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AN AMBER COLORED OILY LIQUID. A FAINT PETROLEUM
ODOR.

Percent Volatiles by Volume:NEG

=====
===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:STABLE UNDER NORMAL CONDITIONS OF STORAGE
AND HANDLING. AVOID HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES.

Hazardous Decomposition Products:BURNING PRODUCES CARBON MONOXIDE,
CARBON DIOXIDE, AND POSSIBLE TRACE AMOUNTS OF OXIDES OF SULFUR AND
NITROGEN.

Conditions to Avoid Polymerization:THIS MATERIAL DOES NOT POLYMERIZE.

=====
===== Disposal Considerations =====

====

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. EMPTY CONTAINERS SHOULD BE COMMERCIALY CLEANED AND RECONDITIONED BEFORE REUSE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.