

=====  
Product Identification  
=====

Product ID:UNLEADED GASOLINE

MSDS Date:08/01/1991

FSC:9130

NIIN:00-148-7103

MSDS Number: BPHGL

=== Responsible Party ===

Company Name:KERR-MCGEE CORP KERR-MCGEE CENTER

Box:25861

City:OKLAHOMA CITY

State:OK

ZIP:73125

Country:US

Preparer's Name:KEITH W. BUNSELMEYER

CAGE:50848

=== Contractor Identification ===

Company Name:KERR-MCGEE CORP KERR-MCGEE CENTE

R

Box:25861

City:OKLAHOMA CITY

State:OK

ZIP:73125

Country:US

CAGE:50848

Company Name:LAKESIDE OIL CO INC

Address:2817 W STARK

Box:City:MILWAUKEE

State:WI

ZIP:53209-5419

Country:US

Phone:414-445-6464

CAGE:8P890

=====  
Composition/Information on Ingredients  
=====

Ingred Name:GASOLINE (MIXTURE)

CAS:8006-61-9

RTECS #:LX3300000

Fraction by Wt: 85-100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM/500 STEL

ACGIH TLV:300 PPM/500STEL;9293

Ingred Name:METHYL TERT-BUTYL ETHER (SA

RA III)  
CAS:1634-04-4  
RTECS #:KN5250000  
Fraction by Wt: 0-15%  
Other REC Limits:NONE RECOMMENDED  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:BENZENE (SARA III)  
CAS:71-43-2  
RTECS #:CY1400000  
Fraction by Wt: UP 2%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1PPM/5STEL;1910.1028  
ACGIH TLV:10 PPM; A2; 9293  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: UP 10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV  
:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: UP 10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO  
Health Hazards Acute and Chronic

:CHRONIC: INHALATION-NERVOUS SYSTEM, KIDNEY, LIVER & BLOOD DISORDERS, INCLUDING ANEMIA & LUKEMIA. SKIN-DERMATITIS. ACUTE: INHALATION-RESPIRATORY IRRITATION, CENTRAL NERVOUS SYSTEM DEPRESSION. SKIN-IRRI TATION. EYES-IRRITATION. INGESTION-ASPIRATION HAZARD, PULMONARY EDEMA, CENTRAL NERVOUS SYSTEM DEPRESSION.

Explanation of Carcinogenicity:OSHA REQUIRES LABEL: DANGER, CONTAINS BENZENE, CANCER HAZARD.

Effects of Overexposure:INHALATION-HEADACHE, NAUSEA, DROWSINESS, BREATH

LESSNESS, FATIGUE, CONVULSION & LOSS OF CONSCIOUSNESS.

INGESTION-HEADACHE, NAUSEA, DROWSINESS, FATIGUE, PNEUMONITIS, CONVULSION AND LOSS OF CONSCIOUSNESS .

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH EXPOSED AREA WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. MAY CAUSE CHEMICAL PNEUMONITIS. CALL A PHYSICIAN. INHALATION

: SHOULD

SYMPTOMS NOT ED UNDER EXPOSURE OCCUR, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. (REMOVE GASOLINE-SOAKED CLOTHING)

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:-45F,-43C

Autoignition Temp:Autoignition Temp Text:536F

Lower Limits:1.4 %

Upper Limits:7.6 %

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, OR FOAM. WATER STREAM MAY SPREAD FIRE, USE WTAER SPRAY ONLY TO COOL FIRE EXPOSED

CONTAINER

Fire Fighting Procedures:IF LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS.

Unusual Fire/Explosion Hazard:CAN FORM FLAMMABLE MIXTURES WITH AIR & FLASH AT ROOM TEMP. EXPLOSION HAZARD IN FIRE SITUATION. VAPORS HEAVIER THAN AIR & MAY TRAVEL SOME DISTANCE & FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:NOTIFY EMERGENCY RESPONSE PERSONNEL. EVCUATE AREA & REMOVE IGNITION SOURCES. BUILD DIKE TO

CONTAIN FLOW. REMOVE

FREE LIQUID, DO NOT FLUSH TO SEWER OR OPEN WATER. PUCK UP WITH INERT ABSORBENT AND PLACE IN CLOSED CONTAINER FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE WITH STRONG OXIDIZERS. STORE AS OSHA IB FLAMMABLE LIQUID.

Other Precautions:WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF INHALED & MAY CAUSE DELAYED LUNJ INJURY. ASPIRATION HAZARD IF

SWALLOWED. CANCER HAZARD - CONTAINS BENZENE. KEEP AWAY FROM HEAT, SPARKS AND FLAMES. AVOID BREATHING VAPORS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:UP TO 10 PPM BENZENE, HALF-MASK ORGANIC VAPOR RESPIRATOR. UP TO 50 PPM BENZENE, FULL-FACE ORGANIC VAPOR RESPIRATOR OR FULL-FACE SUPPLIED AIR RESPIRATOR. GREATER THAN 50 PPM BENZENE, SELF-CONTAINED BREATHING APPARATUS WITH POSITIVE PRESSURE.

Ventilation:MAIN TAIN LOCAL OR DILUTION VENTILATION TO KEEP AIR CONCENTRATION BELOW 300 PPM GASOLINE AND 1 PPM BENZENE.

Protective Gloves:NITRILE, NEOPRENE

Eye Protection:CHEMICAL-TYPE GOGGLES, FACE SHIELD

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health AVOID CONTACT WITY EYES, SKIN AND CLOTHING.

=====  
Physical/Chemical Properties  
=====

HCC:F2

Boiling Pt:B.P. Text:78.0F,25.6C

Melt/F

reeze Pt:M.P/F.P Text:NOT GIVEN

Decomp Temp:Decomp Text:N.A.

Vapor Pres:7-14 MMHG

Vapor Density:3 - 4.0

Spec Gravity:0.7 - .76

pH:N.A.

Viscosity:N.A.

Evaporation Rate & Reference:1.5 X SLOWER ETHYL ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR TO RED LIQUID

Percent Volatiles by Volume:100 %

Corrosion Rate:N.A.

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS

Stability Condition to Avoid:HEAT, SP

ARKS, FLAME AND OTHER SOURCES OF  
IGNITION.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON  
MONOXIDE AND VARIOUS HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:UTILIZE LICENSED WSTE DISPOSAL COMPANY. CONSIDER  
RECYCLING OR INCINERATION. UTILIZE PERMITTED HAZARDOUS WASTE  
DISPOSAL SITE OR INDUSTRIAL WASTE DISPOSAL SITE AS APPROPRIATE.

Disclaimer (provided with this information by the compiling agenci  
es):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.