

GATES ENERGY PRODUCTS INC -- SEALED LEAD ACID BATTERY CLOSED CYLINDRICAL --
6140-01-159-2241

===== Product Identification =====

Product ID:SEALED LEAD ACID BATTERY CLOSED CYLINDRICAL

MSDS Date:03/01/1990

FSC:6140

NIIN:01-159-2241

MSDS Number: BPHSJ

=== Responsible Party ===

Company Name:GATES ENERGY PRODUCTS INC

Address:441 HWY N

Box:861

City:GAINESVILLE

State:FL

ZIP:32602

Country:US

Info Phone Num:904-462-3911 / FAX 904-462-4726

Emergency Phone Num:904-462-39

11

CAGE:19209

=== Contractor Identification ===

Company Name:ADVANCED INDUSTRIES INC

Address:415 NORTHCUTT STREET

Box:5666

City:LONGVIEW

State:TX

ZIP:75608

Country:US

Phone:214-236-4101

CAGE:0GA21

Company Name:ENERGIZER POWER SYSTEMS (FORMALLY GATES ENERGY PRODUCTS
INC)

Address:US HWY 411 N

Box:147114

City:GAINESVILLE

State:FL

ZIP:32614-7114

Country:US

Phone:904-462-3911

CAGE:19209

Company Name:GATES ENERGY PRODUCTS AFFIL OF GATES RUBBER CO

Address:1050 S BROADWAY

Box:5887

City:DENVER

State:

CO
ZIP:80217
Country:US
CAGE:57053
Company Name:PRECISION CABLE MFG CO INC
Address:1290 E I 30
Box:1448
City:ROCKWALL
State:TX
ZIP:75087-1448
Country:US
Phone:972-771-1233
CAGE:54840

===== Composition/Information on Ingredients =====

Ingred Name:LEAD (SARA III)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 69%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:SULFURIC ACID (SARA III)

CAS:7664-93-9
RTECS #:WS5600000
Fraction by Wt: 21%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:NON-HAZARDOUS INGREDIENTS

Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards

Acute and Chronic:ELECTROLYTE-ACUTE: MAY CAUSE IRRITATION OF RESPIRATORY TRACT, EYES, SKIN OR GI TRACT. MAY CAUSE BURNS OF SKIN, EYES, OR GI TRACT. MAY CAUSE CORNEAL DAMAGE OR BLINDNESS. CHRONIC: TOOTH EROSION, INFLAMMATION OF NOSE, THROAT AND BRONCHIAL TUBES.

Explanation of Carcinogenicity:THE ELECTROLYTE IS NOT LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALATION: BURNING SENSATION IN NOSE, THROAT AND LUNGS, COUGHING, WHEEZING, SHORTNESS OF BREATH. EYES: REDNESS, TEARING, BLURRED VISION, BURNS, SEVERE PAIN. SKIN: SEVERE PAIN, BURNS, REDNESS, RASH, ITCHING. INGESTION: BURNS OF MOUTH, THROAT, AND ESOPHAGUS, SEVERE STOMACH PAIN, NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE RESPIRATORY TRACT OR TEETH MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET PROMPT MEDICAL ATTENTION. SKIN :REMOVE CONTAMINATED CLOTHING. WASH WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NO
N-FLAMMABLE

Extinguishing Media:USE DRY CHEMICAL, CARBON DIOXIDE

Fire Fighting Procedures:USE OF WATER IN EXTINGUISHING BURNING BATTERIES MAY CAUSE SPATTERING DUE TO THE PRESENCE OF MOLTEN LEAD. WEAR SCBA AND FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:AFTER ELECTROLYTE IS ADDED AND BATTERY IS BEING CHARGED, HYDROGEN GAS IS PRODUCED. BATTERY MAY EXPLODE IF HYDROGEN GAS TRAPPED INSIDE THE CASE SHOULD IGNITE.

===== Accidental Release Measures =====

===

Spill Release Procedures:SHOULD A BATTERY BREAK OPEN, ISOLATE AREA.
ELECTROLYTE SHOULD BE ABSORBED WITH A NON-ORGANIC TYPE ABSORBENT
SUCH AS DRY SAND OR EARTH. AVOID DILUTION WITH WATER. LEAD SPILLED
FROM THE BATTERY SHOULD B E VACUUMED, DO NOT SWEEP OR USE
COMPRESSED AIR.
Neutralizing Agent:USE SODA ASH OR BAKING SODA TO NEUTRALIZE THE
ELECTROLYTE.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID THE USE OF UNI
NSULATED TOOLS. IF
THEY ARE REQUIRED, TAKE CARE NOT TO ELECTRICALLY SHORT THE
TERMINALS. REMOVE METAL JEWELRY BEFORE SERVICING.
Other Precautions:UNDER NORMAL CONDITIONS OF USE, EXPOSURE TO LEAD OR
LEAD CONTAINING COMPOUNDS DOES NOT OCCUR. SHOULD A BATTERY BREAK
OPEN AND A LEAD SPILL OCCUR, PRECAUTIONS SHOULD BE TAKEN TO PREVENT
LEAD DUST FROM BECOMING AIR BORNE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:UNDER NORMAL CONDITI
ONS OF USE, RESPIRATORY
PROTECTION IS NOT REQUIRED. HOWEVER, IF CONDITIONS ARISE THAT
REQUIRE THEIR USE, USE ONLY NIOSH/MSHA RESPIRATORS APPROVED FOR
DUST, FUME AND MIST.
Ventilation:BATTERY CHARGING AREAS MUST BE ADEQUATELY VENTILATED TO
PREVENT HAZARDOUS CONCENTRATIONS OF FLAMMABLE GAS OR ACID MIST.
Protective Gloves:RUBBER GLOVES APPROVED FOR SULFURIC ACID
Eye Protection:CHEMICAL SPLASH GOGGLES AND FACE SHIELD
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE IMPERVIOUS WORK CLOTHING, BOOTS AND APRON AS
REQUIRED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
REFER TO WYLE SCIENTIFIC SERVICES,CERTIFICATION TEST REPORT,DATED
16JUL92,STATING THAT THIS BATTERY IS NON-DANGEROUS/NOT REGULATED
PER ICAO/IATA PROCEDURES FOR SPECIAL PROVISION A67.

===== Physical/Chemical Properties =====

=====

HCC:N1

Appearance and Odor:NO ODOR. BATTERY CASE IS SEALED. ELECTROLYTE IS
CLEAR OILY LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

CONTACT OF ELECTROLYTE WITH ORGANIC MATERIAL AND COMBUSTIBLES, STRONG
ALKALIS, REDUCING AGENTS, STRONG OXIDIZING AGENTS

Stability Condition to Avoid:OVERCHARGING, SOURCES OF IGNITION

Hazardous Decomposition Products:SULFURIC ACID MIST, SULFUR DIOXIDE AND
CARBON MONOXIDE MAY

BE RELEASED WHEN ELECTROLYTE DECOMPOSES.

===== Disposal Considerations =====

Waste Disposal Methods:BOTH ELECTROLYTE AND SCRAP BATTERIES ARE

REGULATED HAZARDOUS WASTE. SCRAP BATTERIES CONTAIN MATERIALS WHICH
ARE RECYCLABLE AND MUST BE RETURNED TO AUTHORIZED RECYCLER.

ELECTROLYTE SHOULD BE HAULED TO A PERMITTED TREATMENT FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by ele

ments of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.