

AKZO COATINGS INC -- 463-07-0027 EPOXY-POLYAMIDE PRIMER-GREEN -- 8010-01-050-4082

=====
Product Identification
=====

Product ID:463-07-0027 EPOXY-POLYAMIDE PRIMER-GREEN

MSDS Date:10/26/1992

FSC:8010

NIIN:01-050-4082

Kit Part:Y

MSDS Number: BPJHG

=== Responsible Party ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

City:ORANGE

State:CA

ZIP:92661

Country:US

Info Phone Num:714-637-1750

Emergency Phone Num:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

=== Contractor Identification ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

Box:City:ORANGE

State:CA

ZIP:92661

Country:US

Phone:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 15.8%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

E

PA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CYCLOHEXANONE (SARA III)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 7.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 L
BS

Ingred Name:AMORPHOUS SILICA
CAS:112926-00-8
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:6 MG/M3 TWA
ACGIH TLV:10 MG/M3 TWA

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:IRON OXIDE
CAS:1317-61-9
Fraction by Wt: 5-10%
Other REC Limits:10 MG/M3 TWA

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV73

25000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:CHROMIUM(VI) OXIDE
CAS:1333-82-0
RTECS #:GB6650000
Fraction by Wt: 4.4%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 MICRO GRAMS/M3
ACGIH TLV:50 MICRO GRAMS/M3

Ingred Name:IRON OXIDE HYDRATE
CAS:51274-00-1
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICA, CRYSTALLINE - QUARTZ
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: AIR
Evaporation Ra
te & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:48

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS.
Stability Condition to Avoid:HIGH TEMP, OPEN FLAMES.
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
SMOKE, OXIDES OF NITROGEN AND METAL OXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL POLLUTION CONTROL REQUIREMENTS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability

ty of this information to their particular situation.