

ROSE TALBERT PAINT CO. -- PREMIUM VELVET VINYL LATEX FLAT-LTB -- 8010-00-598-5734

===== Product Identification =====

Product ID:PREMIUM VELVET VINYL LATEX FLAT-LTB

MSDS Date:10/30/1992

FSC:8010

NIIN:00-598-5734

MSDS Number: BPMSX

=== Responsible Party ===

Company Name:ROSE TALBERT PAINT CO.

Address:901 FRINK STREET

City:CAYCE

State:SC

ZIP:29033

Country:US

Info Phone Num:803-796-0324

Emergency Phone Num:800-255-3924

Preparer's Name:DAVID KELLY

CAGE:4792X

=== Co

ntractor Identification ===

Company Name:ROSE TALBERT PAINT CO.

Address:901 FRINK STREET

Box:City:CAYCE

State:SC

ZIP:29033

Country:US

Phone:800-255-3924

CAGE:4792X

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 15.42%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 1.8

2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 50 PPM
ACGIH TLV:C 50 PPM,VAPOR; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:LEAD (SARA III)
CAS:7439-92-1
RTECS #:OF7525000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CHROMATES
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of E
ntry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: PULMONARY EDEMA MAY
DEVELOPE WITH INHALATION OF HIGH CONCENTRATIONS. THIS MATERIAL MAY
CAUSE NOSE AND THROAT IRRITATION. EYES: THIS PRODUCT CAN BE
IRRITATING TO THE EYES. SKIN: MAY CAUSE S KIN IRRITATION AND
DRYING/DEFATTING OR CRACKING AND DERMATITIS ON REPEATED OR
PROLONGED EXPOSURE TO THE SKIN.
Explanation of Carcinogenicity:MANUFAC
TURER STATE THIS PRODUCT CONTAINS
NO REPORTED CARCINOGENS OR SUSPECTED CARCINOGENS.
Effects of Overexposure:EYE, SKIN AND LUNG IRRITATION. CONTINUED
BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT CAUSING
HEADACHE, NAUSEA AND DIZZINESS. THIS PRODUCT MAY BE FATAL FROM
SWALLOWING LARGE AMOUNTS. MAY CAUSE N AUSEA, VOMITING, HEADACHES,
DIZZINESS, STUPOR, AND KIDNEY DAMAGE. INHALING THE CONTENTS MAY BE
HARMFUL OR FATAL.
Medical Cond Aggravated by Exposure:PERSONS WITH A HIS

TORY OF AILMENTS

OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN,
RESPIRATORY TRACT OR KIDNEY MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NOT
BREATHING. CONTACT A PHYSICIAN IMMEDIATELY. EYES: IMMEDIATELY FLUSH
WITH LUKE WARM WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN:
REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. CONTACT A
PHYSICIAN IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. RINSE
MOUTH IMMEDIATELY. GIVE 6 TO 8 OUNCES OF WATER IF CONSCIOUS. GET
PHYSICIAN IMMEDIATE

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:241F,116C
Lower Limits:3.2
Upper Limits:15.3
Extinguishing Media:CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE
USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP
AND
POSSIBLE AUTOIGNITION. USE FOG NOZZLES WITH WATER.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE
FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CLOSED
CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:STAY UPWIND AND AWAY FROM SPILL UNLESS WEARING
APPROPRIATE PROTECTIVE EQUIPMENT. STOP AND/OR CONTAIN DISCHARGE IF
IT MAY BE DONE SAFELY. KEEP AL
L SOURCES OF IGNITION AWAY. VENTILATE
AREA OF SPILL. USE NON-SPARKING TOOLS FOR CLEANUP.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP PRODUCT CONTAINERS COOL, DRY AND
AWAY FROM SOURCES OF IGNITION. USE AND STORE WITH ADEQUATE
VENTILATION. DO NOT SMOKE IN STORAGE AREA.
Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN
EMPTIED. NOTICE: REPORTS HAVE ASS

OCIATED REPEATED AND PROLONGED
OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND
NERVOUS SYSTEM DAMAGE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORS TO REMOVE
SOLID AIRBORNE PARTICLES OF OVER SPRAY DURING SPRAY APPLICATIONS.
IN RESTRICTED VENTILATION AREAS USE NIOSH/MSHA APPROVED RESPIRATOR
DESIGNED TO REMOVE BO TH PARTICLES AND VAPOR.

Ventilation:SUFFICIENT VENTILATION IN VOLUME
AND PATTERN SHOULD BE

PROVIDED TO KEEP AIR CONTAMINATION BELOW OSHA'S CURRENT PELS.

Protective Gloves:NATURAL RUBBER, NEOPRENE, NITRILE

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT BY USING AN
APRON.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING
WASHROOM FACILITIES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICAL SU
BJECT TO THE

REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40 CFR 372. ETHYLENE
G LYCOL, CAS NUMBER 107-21-1, % BY WEIGHT=1.82%.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:379F,193C

Vapor Pres:10 @68F

Appearance and Odor:LIQUID

Percent Volatiles by Volume:47

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoi

d:YES

STRONG ACIDS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION

Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES, INCLUDING
CARBON DIOXIDE, CARBON MONOXIDE AND OXIDES OF NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. DO NOT INCINERATE
CLOSED CONTAINERS.

Disclaimer (provided with this inf

ormation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.