

ROYAL LUBRICANTS COMPANY INC. -- ROYCO 13E -- 9150-00-935-4019

===== Product Identification =====

Product ID:ROYCO 13E

MSDS Date:07/18/1995

FSC:9150

NIIN:00-935-4019

MSDS Number: BPMTS

=== Responsible Party ===

Company Name:ROYAL LUBRICANTS COMPANY INC.

Address:MERRY LANE

Box:518

City:EAST HANOVER

State:NJ

ZIP:07936

Country:US

Info Phone Num:201-887-7410

Emergency Phone Num:201-887-7411 800-424-93

00(CHEMTREC)

CAGE:6V632

=== Contractor Identification ===

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

Company Name:ROYAL LUBRICANTS CO INC (REPLACED BY CAGE CODE 07950)

Address:MERRY LANE

Box:518

City:EAST HANOVER

State:NJ

ZIP:07936

Country:US

Phone:201-887-7410

CAGE:6V632

Company Name:ROYAL LUBRICANTS COMPANY INC.

Address:215 MERRY LN

Box:518

City:EAST HANOVER

State:NJ

ZIP:07936

Country:US

Phone:973-887-7411/7410
CAGE:07950
Company Name:SDB CONSULTANTS LTD
Address:401 WHITNEY AVE SUITE 120
Box:City:GRETNA
State:LA
ZIP:70056
Country:US
Phone:504-366-9105
CAGE:0PGK2

===== Composition/Information on Ingredients =====

Ingred Name:SILICONE
CAS:63148-52-7
Fraction by Wt: 50-60%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYTETRAFLUORO ETHYLENE (TEFLON)
CAS:116-14-3
RTECS #:KX4025000
Fraction by Wt: 40-45%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUS
T
ACGIH TLV:10 MG/M3 TDUST

Ingred Name:MINOR ADDITIVES
Fraction by Wt: 200F,>93C(EST)
Lower Limits:NOT GIVEN
Upper Limits:NOT GIVEN
Extinguishing Media:WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.DO
NOT USE DIRECT STREAM OF WATER.PRODUCT FLOATS & REIGNITES ON
SURFACE
Fire Fighting Procedures:USE PROTECTIVE EQUIPMENT AND SELF-CONTAINED
BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZA
RDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:TAKE UP WITH AN ABSORBANT MATERIAL AND PLACE
IN AN APPROPRIATE DISPOSAL CONTAINER. WASH AREA WITH SOAP AND
WATER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. KEEP
CONTAINERS CLOSED WHEN MATERIAL IS NOT IN USE. KEEP

AWAY FROM
IGNITION SOURCES. AVOID PROLONGED OR REPEATED CONTACT.
Other Precautions:THIS PRODUCT IS CONSIDERED TO BE AN OIL UNDER EPA
SECT. 311,SPILL INTO OR LEADING TO SURFACE WATERS THAT CAUSE A
SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER AT
800-424-8802.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:OVEREXPOSURE-USE NIOSH RESPIRATOR.PER
29CFR1910.134 USE EITH AN ATMOSPHERE SUPPLYING RESPIRATOR OR AN AIR
PURIFYIN
G RESPIRATOR FOR ORGANIC VAPORS AND PARTICULATES.
Ventilation:NO SPECIAL REQUIREMENT. NONE NORMALLY REQUIRED.
Protective Gloves:NEOPRENE OR NITRILE RUBBER GLOVES
Eye Protection:SAFETY GLASSES - CHEMICAL SPLASH GOGGLES
Other Protective Equipment:WEAR INDUSTRIAL WORK CLOTHING. USE RUBBER
APRON OR BOOTS IF NEEDED. HAVE EMERGENCY EYE WASH AND SAFETY SHOWER
AVAILABLE.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHI
NG BEFORE
REUSE.
Supplemental Safety and Health
AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO
NOT BREATHE VAPORS OR MIST. DO NOT INGEST. READ PRECAUTIONS ON
LABEL BEFORE USE.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:NOT GIVEN
Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN
Decomp Temp:Decomp Text:NOT GIVEN
Vapor Pres:NOT GIVEN
Vapor Density:NOT GIVEN
Spec Gravity: