MOBIL OIL CORP ENVIRONMENTAL AFFAIRS & TOXICOLOGY -- MOBIL DTE OIL LIGHT --9150-01-043-9063

Product ID:MOBIL DTE OIL LIGHT MSDS Date:11/30/1993 FSC:9150 NIIN:01-043-9063 MSDS Number: BPMVN === Responsible Party === Company Name: MOBIL OIL CORP ENVIRONMENTAL AFFAIRS & TOXICOLOGY Address: PENNINGTON-ROCKY HILL RD **City:PENNINGTON** State:NJ ZIP:08534 Country:US Info Phone Num:800-662-4525 OR 227-0707 X3265 **Emergency Phone Num:609-**737-4411 CAGE:0AHK0 === Contractor Identification === Company Name: MOBIL CHEMICAL CO., CHEMICAL COATINGS DIV. Address: RT 27 AND VINEYARD RD. Box:250 City:EDISON State:NJ ZIP:08818-0250 Country:US Phone:609-737-4411 OR 800-424-9300 CAGE:77988 Company Name: MOBIL OIL CORP ENVIRONMENTAL AFFAIRS & TOXICOLOGY Address: PENNINGTON-ROCKY HILL RD Box:City:PENNINGTON State:NJ ZIP:08534 Country:US CAGE:0AHK0

Ingred Name: DISTILLATES, HYDRO

TREATED HEAVY PARAFFINIC CAS:64742-54-7 RTECS #:PY8035500 Other REC Limits:NONE RECOMMENDED OSHA PEL:300 PPM ACGIH TLV:300 PPM

Ingred Name:REFINED HEAVY PARAFFINIC DISTILLATES CAS:64741-88-4 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:TRICRESYLPHOSPHATE CAS:1330-78-5 RTECS #:TD0175000 Fraction by Wt: 0.05% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:NONTOXIC BASED ON SIMILAR PRODUCTS Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SEVERELY SOLVENT REFINED AND SEVERELY HYDROTREATED MINERAL BASE OILS HAVE BEEN TESTED BY DERMAL APPLICATION TO RATS AT DOSES SIGNIFICANTLY HIGHER THAN THOSE EXPECTED DURING NORMAL INDUSTRIAL EXPOSURE. EXTENSIVE EVALUATIONS SHOWED NO ADVERSE EFFECTS. Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER. E ffects of Overexposure:SLIGHT SKIN IRRITATION. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYE CONTACT: FLUSH THOROUGHLY WITH WATER. IF IRRITATION PERSISTS, CALL A PHYSICIAN. SKIN CONTACT: WASH AREA WITH SOAP AND WATER. INHALATION: NOT EXPECTED TO BE A PROBLEM. INGESTION: NOT EXPECTED TO BE A PROBLEM WHEN INGESTED. IF UNCOMFORTABLE SEEK MEDICAL ASSISTANCE.

Flash Point Method:COC Flash Point:>405F,>207C Lower Limits:0.6 Upper Limits:7.0 Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO KEEP EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE. PREVENT RUNOFF. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER. ============ Accidental Release Measures _____ Spill Release Procedures: REPORT SPILL TO COAST GUARD TOLL FREE NUMBER 800-424-8802. ADSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH, ETC. SHOVEL UP AND DISPOSE OF AT AN APPROPRIATE WASTE DISPOSAL FACILITY. Handling and Storage Precautions: STORE IN COOL, DRY AND WELL VENTILATED AREA. KEEP AWAY FROM HEAT AND OPEN FLAMES; KEEP CONTAINER CLOSED WHEN NOT IN USE **Other Precautions:NO** SPECIAL PRECAUTIONS REQUIRED. Respiratory Protection: NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE WITH ADEQUATE VENTILATION. Ventilation: NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION. Protective Gloves: NO SPECIAL REQUIREMENTS

Eye Protection:NORMAL INDUSTRIAL EYE PROTECTION

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: GOOD PERSON

AL HYGENIC PRACTICES

Supplemental Safety and Health

PN IND A IS FOR MSDS DATED 12 JAN. 89.

HCC:V6 Boiling Pt:B.P. Text:>600F/316C Vapor Pres: