Product ID:F-76 MARINE FUEL

MSDS Date:07/01/1992

FSC:9140

NIIN:00-255-7764

MSDS Number: BPNXY === Responsible Party ===

Company Name: SUNKYONG LIMITED

Box:1780

City:SEOUL, KOREA

Country:KO CAGE:1Y204

=== Contractor Identification ===

Company Name: SUNKYONG LIMITED

Address:C P O BOX 1780 Box:City:SEOUL REPUBLIC

CAGE:1Y204

====== Composition/Information on Ingredie

nts =======

Ingred Name:PETROLEUM MID-DISTILLATE (DIESEL MARINE FUEL)

CAS:68476-34-6

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name: ANTI-SETTING AGENT

Other REC Limits: NONE RECOMMENDED

Ingred Name:FLOW IMPROVER

Other REC Limits: NONE RECOMMENDED

Ingred Name: MANUFACTURER DID NOT GIVE A SPECIFIC INGREDIENT LISTING;

HMIS TECHNICIAN DERIVED FROM ADDITIVES LIST

RTECS #:9999999ZZ

Other REC Limits: NONE RECOMMENDED

==== Hazards Identification ===========
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Health Hazards Acute and Chronic:ACUTE: CONTACT WITH LIQUID OR MIST MAY CAUSE IRRITATION OF SKIN AND EYES. INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION AND CENTRAL NERVOUS SYSTEM EFFECTS. SWALLOWING MAY CAUSE ASPIRATION INTO LUN GS WHICH CAN BE FATAL. HIGH PRESSURE INJECTION MAY BE HARMFUL TO SKIN. Explanation of Carcinogenicity:NO INGREDIENTS LISTED BY MANUFACTURER.
HMIS TECHNICIAN UNABLE TO DETERMINE FROM AVAILABLE DATA. Effects of Overexposure:INHALED: COUGHING, WHEEZING, SHORTNESS OF BREATH, DROWSINESS, HEADACHE, NAUSEA. EYES: REDNESS, BURNING SENSATION, TEARING. SKIN: SWELLING, DISCOLORED, PAIN. INGESTED: NAUSEA, VOMITING. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================

First Aid:INHALED: REMOVE TO FRESH AIR. SEE DOCTOR. SKIN: WASH WITH SOAP A

ND WATER. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES. SEE DOCTOR. INGESTED: DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE 2-4 OZ VEGATAB LE OR OLIVE OIL AND 1-2 OZ OF ACTIVATEDCHARCOAL. GET IMMEDIATE MEDICAL AID. IF HIGH PRESSURE INJECTION OCCURS, GET IMMEDIATE MEDICAL ATTENTION.

Flash Point:>140F,>60C

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, AND WATER.

Fire Fighting Procedures: WEAR SELF-CONTAIN

ED BREATHING APPARATUS AND

BUNKER GEAR. USE WATER TO COOL FIRE EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard: MISTING FROM HANDLING OR HEATING MAY
CAUSE A FUEL/AIR MIXTURE WHICH IS COMBUSTIBLE; MAY IGNITE IF
EXPOSED TO SOURCES OF IGNITION.

======== Accidental Release Measures ==========

Spill Release Procedures:STOP FLOW. ELIMINATE ALL SOURCES OF IGNITION.
VENTILATE AREA. WEAR PROPER PROTECTIVE CLOTHES. ABSORB WITH INERT
MATERIALS AND PLACE IN A CONTA

siderations ========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek comp etent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.