

=====
===== Product Identification =====

Product ID:DUST BUSTER

MSDS Date:11/21/1991

FSC:7930

NIIN:00-582-4195

MSDS Number: BPPBS

=== Responsible Party ===

Company Name:BEXAR CHEMICAL & SUPPLY, INC.

Address:15303 TRADESMAN

City:SAN ANTONIO

State:TX

ZIP:78249

Country:US

Info Phone Num:512-493-3171

Emergency Phone Num:512-493-3171

Preparer's Name:JOHN WOOD

CAGE:0HXU7

=== Contractor Identification ===

Com

pany Name:BEXAR CHEMICAL & SUPPLY, INC

Address:15303 TRADESMAN

Box:City:SAN ANTONIO

State:TX

ZIP:78249

Country:US

Phone:512-493-3171

CAGE:0HXU7

=====
===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SEAL OIL

CAS:64741-44-2

RTECS #:LX3296000

Fraction by Wt: 96%

Other REC Limits:NONE SPECIFIED

OSHA PEL:OIL MIST TWA 5 MG/M

ACGIH TLV:10 MG/M STEL

Ingred Name:PRIMARY AMYL ACETATE

CAS:628-63-7

RTECS #:AJ1925000

Fraction by Wt: 3%

Other REC Limits:NONE SPECIFIED

ACG

IH TLV:100 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:OPE-10 EMULSIFYING AGENT
CAS:9016-45-9
RTECS #:MD0900000
Fraction by Wt: 1%
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:POSSIBLE HEADACHE, NAUSEA AND/OR
FATIGUE.
Effects of Overexposure:NONE

=====
===== First Aid Measures =====

First Aid:MOVE EXP
OSED PERSON TO FRESH AIR, IF BREATHING HAS STOPPED,
PERFORM ARTIFICIAL RESPIRATION, GET MEDICAL ATTENTION AS SOON AS
POSSIBLE.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:410F,210C
Extinguishing Media:DRY CHEMICAL OR FOAM
Fire Fighting Procedures:ONLY DRY FOAM/DRY CHEMICAL. INCOMPLETE
COMBUSTION CAN YIELD CARBON MONOXIDE/VARIOUS HYDROCARBONS.
SELF-CONTAINED BREATHING APPARATUS IN POSITIVE PRESSURE MODE.
Unusual Fire/Ex
losion Hazard:USE WATER SPRAY ONLY TO COOL CONTAINERS
EXPOSED TO FIRE. WATER STREAM MAY SPREAD FIRE IF LEAK OR SPILL HAS
NOT IGNITED. USE WATER SPRAY TO DISPENSE VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:PICK UP WITH INERT ABSORBENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AS OSHA CLASS 1118 COMBUSTIBLE
LIQUID.
Other Precautions:DO NOT STORE WITH STRONG O

XIDIZERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE
Ventilation:NONE/LOCAL VENTILATION
Protective Gloves:NONE
Eye Protection:NONE
Other Protective Equipment:NONE
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:475 TO 610F
Melt/Freeze Pt:M.P/F.P Text:148F,64C
Vapor Density:8 (AIR=1)
Spec Gravity:.81 (WATER=1)
pH:7
Viscosity:37.6 SUS 100F
Evaporation Rate &
Reference:BUTYL ACETATE SLOWER
Solubility in Water:STABLE
Appearance and Odor:CLEAR LIQUID WITH BANANA ODOR
Corrosion Rate:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:DO NOT STORE WITH STRONG OXIDIZERS. STORE
AS OSHA CLASS 1118 COMBUSTIBLE LIQUID.
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:UTILIZE L
ICENSED WASTE DISPOSAL COMPANY.
CONSIDER RECYCLING OR INCINERATION. UTILIZE PERMITTED INDUSTRIAL
WASTE DISPOSAL SITE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competen

t professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.