

WHITTAKER ORDANCE INC SUB OF WHITTAKER CORP -- 4199 PRESSURE CARTRIDGE ASSEMBLY
-- 1680-01-021-8442

===== Product Identification =====

Product ID:4199 PRESSURE CARTRIDGE ASSEMBLY

MSDS Date:02/22/1991

FSC:1680

NIIN:01-021-8442

MSDS Number: BPPMT

=== Responsible Party ===

Company Name:WHITTAKER ORDANCE INC SUB OF WHITTAKER CORP

Address:2751 SAN JUAN RD

Box:148

City:HOLLISTER

State:CA

ZIP:95024

Count

ry:US

Info Phone Num:408-637-5851

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:JIM HART

CAGE:10640

=== Contractor Identification ===

Company Name:WHITTAKER ORDANCE INC SUB OF WHITTAKER CORP

Address:2751 SAN JUAN RD

Box:148

City:HOLLISTER

State:CA

ZIP:95024

Country:US

CAGE:10640

===== Composition/Information on Ingredients =====

Ingred Name:ZIRCONIUM

CAS:7440-67-7

RTECS #:ZH7070000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3/10 STEL

ACGIH TLV:5 MG/M3/10 S

TEL:9293

Ingred Name:AMMONIUM DICHROMATE (BICHROMATE) (SARA III)

CAS:7789-09-5

RTECS #:HX7650000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.1PPM CRO3;CEILING

ACGIH TLV:0.05 MG CR/M3

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:AMMONIUM PERCHLORATE

CAS:7790-98-9

RTECS #:SC7520000

Other REC Limits:NONE RECOMMENDED

Ingred Name:BARIUM DICHROMATE

Other REC Limits:NONE RECOMMENDED

Ingred Name:MIXTURE OF NITROCELLULOSE AND RDX SMOKELESS POWDER

Other REC Limits:NONE RECOMMENDED

=====

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CONTACT MAY IRRITATE SKIN AND EYES. INHALATION OF VAPORS FROM COMBUSTION MAY CAUSE REPIRATORY IRRITATION.

Explanation of Carcinogenicity:CHROMIUM IS LISTED AS A KNOWN CARCINOGEN BY IARC AND NTP.

Effects of Overexposure:INHALED: COUGHING, WHEEZING, SHORTNESS OF BREATH. SKI

N: REDNESS, ITCHING. EYES: REDNESS, TEARING, BLURRED VISION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALED: REMOVE TO FRESH AIR. GIVE RESPIRATORY ASSISTANCE AS NEEDED. SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES. SEE DOCTOR.

===== Fire Fighting Measures =====

Autoignition Temp:Autoignition Temp

Text:310F

Extinguishing Media:MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND BUNKER GEAR. FOLLOW DOT RESPONSE GUIDE #50 FOR EXPLOSIVES. EVACUATE ALL PERSONNEL 1500 FEET IN ALL DIRECTIONS.

Unusual Fire/Explosion Hazard:MODERATE FIRE HAZARD. DO NOT STORE WITH HIGH EXPLOSIVES. KEEP AWAY FROM FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:IF UNIT BECOMES DAMAGED SO AS TO EXPOSE

INTERNAL EXPLOSIVES, CONTACT WHITAKER ORDNANCE ENGINEERS FOR GUIDANCE (408-637-5851).

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AUTHORIZE HANDLING ONLY BY TRAINED, QUALIFIED PERSONNEL. HANDLE AND TRANSPORT AS A CLASS C EXPLOSIVE (UN/DOD, CLASS 1, DIV 4).

Other Precautions:KEEP UNIT SHUNTED UNTIL CONNECTION TO CIRCUITRY. NEVER ATTEMPT TO DISASSEMBLE, MACHINE OR OTHERWISE MODIFY UNITS OR PHYSICAL INJURY MAY RESULT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSED TO COMBUSTION PRODUCTS IN A CONFINED AREA; USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE. USE IN ACCORDANCE WITH 29 CFR 1910.134.

Ventilation:USE LOCAL EXHAUST VENTED TO OUTSIDE ATMOSPHERE OR, BE IN OPEN/OUTDOORS AREA.

Protective Gloves:NONE NORMALLY REQUIRED.

Eye Protection:SAFETY GLASSES

Other Protective

Equipment:FLAME RETARDANT,COTTON CLOTHING;CONDUCTIVE FOOTWEAR RECOMMENDED WHEN HANDLING UNITS.WEAR HEARING PROTECTION DURING USE.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. NO SMOKING IN AREA OF USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:E2

Net Prop Wt for Ammo:170MG

Appearance and Odor:A SEALED CARTRIDGE CONTAINING EXPLOSIVES

===== Stability and Reactivity Data =====

a =====

Stability Indicator/Materials to Avoid: YES

FLAMMABLE LIQUIDS, STRONG MINERAL ACIDS, OR STRONG ALKALIS.

Stability Condition to Avoid: AVOID FLAMES, HIGH TEMPERATURES,

ELECTROSTATIC DISCHARGE, IMPACT, ELECTRICAL CURRENT, OR RF ENERGY.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE,

HYDROGEN CHLORIDE, AND OXIDES OF NITROGEN, CHROMIUM, BARIUM AND ZIRCONIUM.

===== Disposal Considerations =====

Waste Disposal Methods:

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND

FEDERAL REGULATIONS DEALING WITH CLASS C EXPLOSIVES. MANUFACTURER

RECOMMENDS THERMAL TREATMENT AT AN APPROVED, PERMITTED FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use

. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.