

ATLANTIC RICHFIELD CO. LYONDELL PETROCHEMICAL DIV. -- UNBRANDED UNLEADED REGULAR
GASOLINE -- 9130-00-264-6218

===== Product Identification =====

Product ID:UNBRANDED UNLEADED REGULAR GASOLINE

MSDS Date:06/12/1985

FSC:9130

NIIN:00-264-6218

MSDS Number: BPQSJ

=== Responsible Party ===

Company Name:ATLANTIC RICHFIELD CO. LYONDELL PETROCHEMICAL DIV.

Address:1200 MILAM,SUITE 3500

City:HUSTON

State:TX

ZIP:77002

Info Phone Num:213-486-8258

Emergency Phone Num:312-210

-3000

CAGE:56242

=== Contractor Identification ===

Company Name:ATLANTIC RICHFIELD CO

Address:515 S. FLOWER ST

Box:2451

City:LOS ANGELES

State:CA

ZIP:90071-2201

Country:US

Phone:213-486-2687

CAGE:56242

Company Name:ATLNTIC RICHFIELD CO

Box:2451

City:HOUSTON

State:TX

ZIP:77001

Country:US

Phone:713-584-6000

CAGE:4H945

Company Name:WESTERN FUEL OIL CO

Address:180 E OCEAN BLVD SUITE 800

Box:City:LONG BEACH

State:CA

ZIP:90802-4760

Country:US

CAGE:7V053

===== Composition/Information on Ingre

dients =====

Ingred Name:HYDROCARBONS WITH BOILING POINT RANGE OF 70F TO 440F.

Fraction by Wt: 89-99%

Other REC Limits:NONE RECOMMENDED

Ingred Name:METHYL TERT-BUTYL ETHER (SARA III)

CAS:1634-04-4

RTECS #:KN5250000

Fraction by Wt: 0-11%

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TERT-BUTYL ALCOHOL (SARA III)

CAS:75-65-0

RTECS #:EO1925000

Fraction by Wt: 0-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100PPM 9394

Ingred Name:E

THYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 0-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9293

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 0-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:S,200PPM/250STEL

ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: LT 5%

Other REC Limits:NONE RECOMM

ENDED
OSHA PEL:1PPM/5STEL;1910.1028
ACGIH TLV:10 PPM; A2; 9293
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:INHALATION-EXPOSURE CAN CAUSE
IRRITATION TO THE NOSE, THROAT & LUNGS & SIGNS OF CNS DEPRESSION.
EYE-MILD EYE IRRITATION. SKIN-SKIN IRRITATION, CAN CAUSE NERVOUS
SYSTEM D
EPRESSION. INGESTION-IRRITATION OF THE MOUTH, THROAT &
GASTROINTESTINAL. ASPIRATION INTO LUNGS WILL CAUSE CHEMICAL
PNEUMONIA.
Explanation of Carcinogenicity:CONTAINS BENZENE;LISTED BY ALL THREE,
ALSO,AN API STUDY FOUND LIVER CANCER IN MICE EXPOSED TO GASOLINE
VAPORS.
Effects of Overexposure:INHALATION-DIZZINESS, DROWSINESS

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:-45F,-43C
Autoignition Temp:Autoignition Temp Text:>
600F
Lower Limits:1.3
Upper Limits:8.2
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL, HALON. CONSULT
FOAM MANUFACTURERS FOR APPROPRIATE MEDIA, APPLICATIONS RATES, ETC.
Fire Fighting Procedures:DO NOT ENTER ANY CONFINED SPACES WITHOUT
SELF-CONTAINED BREATHING APPARATUS. WATER FOG OR SPRAY MAY BE USE
TO COOL FIRE EXPOSED CONTAINERS OR TANKS.
Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE! MATERIAL RELEASES
VAPORS THAT WHEN MIXED WITH AIR & IGNITED WILL EXPLODE OR BURN IN

OPENB. VAPORS ACAN TRAVEL, IGNITE & FLASBACK & BURN.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:70-440F
Vapor Pres:8-15 PSIA
Spec Gravity:0.72-0.77
Appearance and Odor:COLORLESS TO STRAW-COLORED LIQUID; PETROLEUM
NAPHTHA ODOR.
Percent Volatiles by Volume:APPREC

===== Stability and Reactivity Data =====

St

ability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH WATER. REACTS WITH STRONG ACIDS AND STRONG OXIDIZING MATERIALS.

Stability Condition to Avoid: HEAT, SPARKS AND OPEN FLAMES.

Hazardous Decomposition Products: BURNING OR EXCESSIVE HEATING MAY PRODUCE CARBON MONOXIDE & OTHER HARMFUL GASES AND VAPORS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America

in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.