HULS AMERICA INC -- MIL-L-6085B/PQ RUST PREVENTIVE 160 -- 9150-00-753-4667 Product ID:MIL-L-6085B/PQ RUST PREVENTIVE 160 MSDS Date:01/16/1989 FSC:9150 NIIN:00-753-4667 MSDS Number: BPRJY === Responsible Party === Company Name: HULS AMERICA INC Address:80 CENTENNIAL AVE Box:456 City:PISCATAWAY State:NJ ZIP:08855-0456 Country:US Info Phone Num:201-980-6800 Emergency Phone Num:201-980-6800 Preparer's Name:P.A. PARKER CAGE:63182 = == Contractor Identification === Company Name: HULS AMERICA INC Address:TURNER PLACE Box:365 City:PISCATAWAY State:NJ ZIP:08855 Country:US Phone:201-763-7173 CAGE:63182 ======= Composition/Information on Ingredients ======== Ingred Name: SULFONIC ACIDS, PETROLEUM, SODIUM SALTS CAS:68608-24-4 Fraction by Wt: 100.0% Other REC Limits: NONE SPECIFIED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Ca

rcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:LOW ORAL AND DERMAL TOXICITY;MIST OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE AND SKIN IRRITATION,NAUSEA, VOMITING,RESPIRATORY TRACT IRRITATION. Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA. Effects of Overexposure:EYE IRRITATION, SKIN IRRITATION, NAUSEA, VOMITING, RESPIRATORY TRACT IRRITATION. Medical Cond Aggravated by Expo sure:PRE-EXISTING CONDITIONS MAY BE WORSEN.
======================================
First Aid:SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH PLENTY OF WATER FOR ABOUT 15-20 MINUTES; SEEK MEDICAL HELP. INHALATION: REMOVE TO FRESH AIR; SEEK MEDICAL HELP. INGESTION: DO NOT INDUCE VOMITING, CALL A PHYSICIAN.
======================================
Flash Point Method:COC Flash Point:440F/227C Lower Limits:NOT GIVEN Upper Limits:NOT GIVEN
Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM OR CARBON DIOXIDE Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.
Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS;COOL WITH WATER SPRAY.
========= Accidental Release Measures ============
Spill Release Procedures:USE PROPER PERSONAL PROTECTION;REMOVE ALL IGNITION SOURCES;CONTAIN FREE MATERIAL;USE SUITABLE INERT ABSORBENT MATERIAL
AND RECOVER FOR PROPER DISPOSAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions:STORE IN COOL, DRY AND WELL VENTILATED AREA. OPERATING TEMPERATURES BELOW 440F; DO NOT USE ABOVE THIS TEMPERATURE. Other Precautions:NONE SPECIFIED BY MANUFACTURER.
====== Exposure Controls/Personal Protection =========
Respiratory Protection:NORMALLY NOT NEEDED;IF OVER HEATED;USE NIO

SH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE PEL/TLV.

Ventilation: USE LOCAL/GENERAL TO MAINTAIN ADEQUATE CFM.

Protective Gloves:IMPERVIOUS.

Eye Protection: CHEMICAL GOGGLES/FACESHIELD.

Other Protective Equipment: EYE-WASH FOUNTAIN, SAFETY SHOWER.

Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health AVOID EYE/SKIN CONTACT.

======== Physical/Chemical Properties ========

====

HCC:V6
Boiling Pt:B.P. Text:>450F/232C
Vapor Pres:1.0
Spec Gravity: