

PLASTI-KOTE COMPANY, INC. -- AEROSOL SPRAY PAINT GRAY 36440 -- 8010-00-935-7085  
===== Product Identification =====

Product ID:AEROSOL SPRAY PAINT GRAY 36440

MSDS Date:01/31/1990

FSC:8010

NIIN:00-935-7085

MSDS Number: BPRLW

=== Responsible Party ===

Company Name:PLASTI-KOTE COMPANY, INC.

Address:1000 LAKE RD.

City:MEDINA

State:OH

ZIP:44256

Country:US

Info Phone Num:216-725-4511

Emergency Phone Num:

216-725-4511

CAGE:DO534

=== Contractor Identification ===

Company Name:PLASTI-KOTE COMPANY, INC

Address:1000 LAKE RD

City:MEDINA

State:OH

ZIP:44256

Phone:216-725-1511

CAGE:DO534

Company Name:TEMPO PRODUCTS CO A PLASTI-KOTE CO INC

Address:1000 LAKE ROAD

Box:City:MEDINA

State:OH

ZIP:44256

Country:US

Phone:330-725-4511

CAGE:07708

===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION\_INGREDIENT

===== Hazards Identifica

tion =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:INHALE: EXCESSIVE INHALATION OF VAPORS  
CAN CAUSE NASAL/RESPIRATORY  
IRRITATION/DIZZINESS/WEAKNESS/FATIGUE/NAUSEA/HEADACHE/POSSIBLE  
UNCONSCIOUSNESS/ASPHYXIATION. EYE: SEVERE  
IRRITATION/REDNESS/TEARING/B LURRED VISION. INGEST:  
GASTROINTESTINALIRRITATION/NAUSEA/VOMITING/DIARRHEA. SKIN:  
IRRITATION FOR SOM

E PERSONS. \*\*\*

Explanation of Carcinogenicity:METHLENE CHLORIDE SUSPECTED CARCINOGEN.

Effects of Overexposure:\*\*\*REPORTS ASSOCIATE REPEAT/PROLONG  
OCCUPATIONAL OVEREXPOSURE TO SOLVENTS W/PERMANENT BRAIN/NERVOUS  
SYSTEM DAMAGE. SEVERE OVEREXPOSURE IN LAB AMINALS HAS ALSO CAUSED  
LIVER ABNORMALITIES/DAMAGE TO KIDN EYS/LUNGS/SPLEEN. INTENTIONAL  
MISUSE BYDELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY  
BE HARMFUL OR FATAL.

Medical Cond Aggravated by Exposure:CAN CAUSE ALLERG  
IC RESPIRATORY/SKIN  
REACTIONS.

===== First Aid Measures =====

First Aid:INHALE: MOVE TO FRESH AIR. OXYGEN/ARTIFICIAL RESPIRATION AS  
NEEDED. SEEK MEDICAL HELP. EYE: FLUSH W/WATER 15 MINUTES,  
OCCASIONALLY LIFT LIDS. GET MEDICAL ATTENTION. INGEST: DO NOT  
INDUCE VOMITING. (AS PIRATION OF MATERIAL INTO LUNGS CAN CAUSE  
CHEMICAL PNEUMONITIS-FATAL. KEEP PERSON WARM/QUIET. GET MEDICAL  
ATTENTION/POISON CONTROL CENTER. SKIN: WASH W/SOAP/WATER/  
VARIOUS  
HAND CLEANERS/WASH CLOTHES.

===== Fire Fighting Measures =====

Flash Point:NR

Lower Limits:1

Extinguishing Media:"ALCOHOL" FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures:WATER SPRAY INEFFECTIVE-USED TO COOL CLSD

CNTNRS-PREVENT PRESSURE

BUILD-UP/AUTOIGNITION/EXPLOSION-EXPOSED-EXTREME HEAT. FOG NOZZLE.

SCBA/FULL FACEPIECE, \*

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS

EXPLODE/AUTOIGNITE-EXPOSED-EXTREME HEAT. VAPORS HE

AVIER THAN

AIR-TRAVEL ALONG GROUND/VENTILATION MOVED/IGNITED BY PILOT LIGHTS/FLAMES/SPARKS\*\*

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. VENTILATE AREA. ABSORB LIQUID ON PAPER/VERMICULITE/FLOOR ABSORBENT/OTHER AND TRANSFER TO CLOSED CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE IN AREAS ABOVE 120F OR IN DIRECT SUNLIGHT, OR NEAR HEAT OR OPEN FLAMES. DO NOT PUNCTURE OR INCINERATE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CASUAL/OCCASIONAL USE: AVOID INHALING VAPORS/SPRAY MIST/OPEN WINDOWS/DOORS/ENSURE FRESH AIR ENTRY DURING APPLICATION/DRYING. IF EYE WATERING/HEADACHES/DIZZINESS IS EXPERIENCED: INCREASE FRESH AIR/WEAR RESPIRATORY PROTECTION/LEAVE AREA.

Ventilation:REGULAR/CONTINUOUS USE: PROVIDE SUFFICIENT MECHANICAL (GENERAL)/LOCA

L EXHAUST VENT TO MAINTAIN EXPOSURE BELOW TLV'S.

Protective Gloves:CHEMICAL RESISTANT SUCH AS NEOPRENE

Eye Protection:CHEMICAL SPLASH GOGGLES-OSHA REGS

Other Protective Equipment:WHERE SPECIAL OR UNUSUAL CONDITIONS EXIST THE EXPERT ASSISTANCE OF AN INDUSTRIAL HYGIENIST SHOULD BE SOUGHT.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING WASHROOM. AS WITH ALL CHEMICALS, MINIMIZE PERSONAL CONTACT/BREATHING OF VAPORS.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:104 TO 331F

Melt/Freeze Pt:M.P/F.P Text:1500 F MIN

Vapor Density:>AIR

Spec Gravity: