

PERMATEX INDUSTRIAL DIV OF LOCTITE CORPORATION -- ULTRA BLUE (TM) NO LEAK SILICONE  
RTV GASKET -- 8030-01-299-1762

===== Product Identification =====

Product ID:ULTRA BLUE (TM) NO LEAK SILICONE RTV GASKET

MSDS Date:09/11/1991

FSC:8030

NIIN:01-299-1762

MSDS Number: BPRQY

=== Responsible Party ===

Company Name:PERMATEX INDUSTRIAL DIV OF LOCTITE CORPORATION

Address:705 N MOUNTAIN RD

Box:11915

City:NEWINGTON

State:CT

ZIP:06111

Country:US

Info Phone Num:203-278-1280

Emergency Phone Num:203-278-1280

Preparer's Name:STEPHEN REPETTO

CAGE:62377

=== Contractor Identification ===

Company Name:PERMATEX INDUSTRIAL

Address:HARTFORD SQUARE N 10 COLUMBUS BLVD

Box:City:HARTFORD

State:CT

ZIP:06106

Country:US

Phone:877-376-2839

CAGE:62377

===== Composition/Information on Ingredients =====

Ingred Name:SILICON FLUID

CAS:63148-62-9

Fraction by Wt: 10-15%

Other REC Limits:NONE SPECIFIED

Ingred Name:POLYDIMETHYLSILOXANE

CAS:70131-67-8

Fraction by Wt: 35-

40%  
Other REC Limits:NONE SPECIFIED

Ingred Name:CALCIUM CARBONATE  
CAS:471-34-1  
RTECS #:FF9335000  
Fraction by Wt: 30-35%  
Other REC Limits:NONE SPECIFIED

Ingred Name:MODIFIED SILICONE DIOXIDE  
CAS:71889-01-5  
Fraction by Wt: 5-10%  
Other REC Limits:NONE SPECIFIED

Ingred Name:VINYL OXIMINOSILANE  
CAS:2224-33-1  
Fraction by Wt: 3-5%  
Other REC Limits:NONE SPECIFIED

Ingred Name:SUBSTITUTED ALKYL SILYL UREA  
CAS:18418-53-6  
Fraction by Wt: 1-3%  
Other REC Limits:NONE SPECIFIED

===== Hazard  
s Identification =====

Effects of Overexposure:METHYL ETHYL KETOXIME PRODUCED DURING CURE IS  
TOXIC AND IRRITATES EYES, NOSE, AND THROAT.  
Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First Aid:INGEST: DO NOT INDUCE VOMITING. KEEP INDIVIDUAL CALM. OBTAIN  
MEDICAL ATTENTION. INHALE: MOVE TO FRESH AIR. IF SYMPTOMS PERSIST,  
OBTAIN MEDICAL ATTENTION. SKIN: WIPE OFF PASTE W/PAPER TOWEL OR  
CLOTH. F  
LUSH AT LEAST 15 MIN W/SOAP/WATER. EYE:FLUSH AT LEAST 15  
MIN W/WATER. OBTAIN MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:>200F,>93C  
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:WIPE OR SCRAPE UP SPILLED MATERIAL. MAINTAIN  
GOOD VENTILATION FOR LARGE SPILLS. PLACE SCRAP MA

TERIAL IN WELL  
VENTILATED AREA AND ALLOW TO CURE TO RUBBER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A DRY AREA BELOW 90F. KEEP  
CONTAINERS CLOSED WHEN NOT IN USE. AVOID AND EYE CONTACT. AVOID  
BREATHING VAPOR.

===== Exposure Controls/Personal Protection =====

Ventilation:PROVIDE LOCAL VENTILATION FOR PROLONGED USE IN A CONFINED  
AREA.

Protective Gloves:RUBBER/PLASTIC

Eye Protection:SAFETY GLA

SSES/GOGGLES. NO CONTACT LENS

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Pres: