

EVEREADY BATTERY CO INC -- MERCURY CELL BATTERY -- 6135-00-043-4312

===== Product Identification =====

Product ID:MERCURY CELL BATTERY

MSDS Date:03/19/1991

FSC:6135

NIIN:00-043-4312

MSDS Number: BPXTS

=== Responsible Party ===

Company Name:EVEREADY BATTERY CO INC

Address:CHECKERBOARD SQ

City:ST LOUIS

State:MO

ZIP:63164

Country:US

Info Phone Num:216-835-7368

Emergency Phone Num:417-625-3333, 1-800-526-4727

CAGE:83740

=== Contractor Identification ===

Company Na

me:ARJAY ELECTRONICS CORP

Address:525 W CHESTER PIKE SUITE 314

Box:City:HAVERTOWN

State:PA

ZIP:19083-4539

Country:US

Phone:215-449-3600

CAGE:64812

Company Name:EVEREADY BATTERY CO INC

Address:CHECKERBOARD SQ

Box:City:ST LOUIS

State:MO

ZIP:63164

Country:US

Phone:216-835-7368

CAGE:83740

===== Composition/Information on Ingredients =====

Ingred Name:MANGANESE DIOXIDE

CAS:1313-13-9

RTECS #:OP0350000

Fraction by Wt: 0-15%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG MN/M3 CEILI

NG
ACGIH TLV:5 MG MN/M3

Ingred Name:MERCURY (SARA III)
CAS:7439-97-6
RTECS #:OV4550000
Fraction by Wt: 0.3-1.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, C, 0.1 MG/M3
ACGIH TLV:S, 0.05 MG/M3; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:MERCURIC OXIDE (SARA III)
CAS:21908-53-2
RTECS #:OW8750000
Fraction by Wt: 20-50%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG HG/M3;SKIN;C
ACGIH TLV:0.1 MG HG/M3; 9293

Ingred Name:POTASSIUM HYDROXIDE (SARA III)
CAS:1310-58-3
RTECS #:TT210000
0
Fraction by Wt: 0-6%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C, 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM HYDROXIDE (SARA III)
CAS:1310-73-2
RTECS #:WB4900000
Fraction by Wt: 0-6%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:C 2 MG/M3; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ZINC (SARA III)
CAS:7440-66-6
RTECS #:ZG8600000
Fraction by Wt: 5-15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG ZNO/M3
A

CGIH TLV:10 MG ZNO/M3; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXPOSURE TO MERCURY-ACUTE:

SKIN:IRRITATION, ANURIA. EYE:IRRITATION, CORNEAL INJURY OR BURNS.

INGESTION:IMMEDIATE NECROSIS IN MOUTH, THROAT, ESOPHAGUS & STOMACH.

DEATH MAY OCCURE. INHALATION:DYSPNEA, COUGH, F

EVER, NAUSEA &

VOMITING, DIARRHEA, STOMATITIS, SALIVATION & METALLIC TASTE.

CHRONIC: CNS DISTURBANCES.

Explanation of Carcinogenicity:MERCURY, ZINC AND AMMONIUM CHLORIDE ARE

NOT LISTED BY IARC, NTP, OR OSHA AS CARCINOGENS.

Effects of Overexposure:TREMORS, CONVULSIONS & OTHER CNS DISTURBANCES,

PNEUMONITIS, CHEST PAINS, DYSPNEA, COUGHING, STOMATITIS, GINGIVITIS

AND LOOSENING OF TEETH, SALIVATION, LOSS OF MEMORY, METALLIC TASTE,

DIZZINESS, CLUMSINESS, SLURRED SPEECH, DIARRH

EA, PAIN & NUMBNESS

IN EXTREMITIES, NEPHRITIS, ANXIETY, HEADACHE, WEIGHT LOSS, AND

INSOMNIA.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF

ALCOHOLISM, CHRONIC KIDNEY DISEASE OR KNOWN ALLERGY TO MERCURY MAY

BE AT INCREASED RISK FROM EXPOSURE TO MERCURY IF THE BATTERY IS

RUPTURED.

===== First Aid Measures =====

First Aid:IF EXPOSED TO RUPTURED BATTERY-INHALATION:REMOVE TO FRESH

AIR. IF NOT BREATHING GIVE CPR/OXYGEN. GET

MEDICAL ATTENTION.

EYE:IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES. GET

MEDICAL ATTENTION. SKIN: WASH SKIN WITH PLENTY OF SOAP & WATER.

INGESTION: GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY

CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &

FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER

SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS AND/OR MAY CAUSE
EXPLOSION.

===== Accidental Release Measures =====

Spill Release Procedures:PICK UP ALL BATTERIES. FOR A SMALL SPILL OF A
RUPTURED BATTERY: COLLECT THE DUST WITH A VACUUM CLEANER AND
DISPOSE OF BAG. WASH THE AREA.
Neutralizing Agent:NONE

===== Handling and
Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED
AREA AWAY FROM HEAT. STACK CARTONS NO MORE THAN 4 LAYERS HIGH ON A
PALLET AND NO MORE THAN 3 PALLETS HIGH.
Other Precautions:DO NOT SEAL BATTERIES IN AIR TIGHT OR WATERTIGHT
CONTAINERS OR COMPARTMENTS. DO NOT RUPTURE OR THROW BATTERIES IN
FIRE. DO NOT RECHARGE BATTERIES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT R
EQUIRED. WEAR MASK WHEN HANDLING
DUST FROM RUPTURED BATTERY.
Ventilation:GENERAL/LOCAL EXHAUST VENTILATION.
Protective Gloves:RUBBER, IF HANDLING RUPTURED BATTERY.
Eye Protection:NONE
Other Protective Equipment:NONE REQUIRED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES.
Supplemental Safety and Health
THESE BATTERIES ARE MANUFACTURED "ARTICLES", WHICH DO NOT RESULT IN
EXPOSURE TO A HAZARDOUS CHEMICAL UNDER NORMAL CONDITIONS OF USE, AS
DEFINED IN OSHA HCS 1910.1200(C). WHEN HANDLING RUPTURED BATTERY
DO NOT GET ON SKIN, IN EYES OR ON CLOTHING. DO NOT BREATHE VAPORS.

===== Physical/Chemical Properties =====

HCC:N1
Appearance and Odor:CYLINDRICAL /D/
Percent Volatiles by Volume:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:HIGH TEMPERATURES.
Hazardous Decomposition Products:THERMAL DECOMPOS

ITION PRODUCTS INCLUDE
TOXIC MERCURY VAPORS AND AMMONIUM CHLORIDE FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE, BURY IN LANDFILL IN
ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied,
warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.