

HULS AMERICA INC -- MIL-H-46170B (AMEND 1) -- 9150-00-111-6255

===== Product Identification =====

Product ID:MIL-H-46170B (AMEND 1)

MSDS Date:03/18/1991

FSC:9150

NIIN:00-111-6255

MSDS Number: BQCNJ

=== Responsible Party ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08854

Country:US

Info Phone Num:201-980-6800

Emergency Phone Num:201-763-7173

Preparer's

Name:P.A.PARKER

CAGE:63182

=== Contractor Identification ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

===== Composition/Information on Ingredients =====

Ingred Name:NON HAZARDOUS INGREDIENT-PROPRIETARY MIXTURE

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS UNKNOWN.

Route

s of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:LOW ORAL AND DERMAL TOXICITY. MISTS OR
FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE AND SKIN IRRITATION,
NAUSEA, VOMITING, RESPIRATORY TRACT IRRITATION.
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.
Effects of Overexposure:EYE AND SKIN IRRITAT
ION, NAUSEA, VOMITING,
RESPIRATORY TRACT IRRITATION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION
PERSISTS GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING.
WASH AREA WITH SOAP AND WATER. IF IRRITATION DEVELOPS GET MEDICAL
ATTENTION. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING GIVE
CPR. IF BREATHING DIFFICU
LT GIVE OXYGEN. GET MEDICAL ATTENTION.
INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:450F,232C
Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM, CARBON DIOXIDE.
Fire Fighting Procedures:BURNING PRODUCES TOXIC FUMES. WEAR
SELF-CONTAINED BREATHING APPARATUS AND FULL TURN-OUT GEAR TO FIGHT
FIRE. AVOID SPREADING LIQUID AND FIRE BY WATER FLOODING.
Unusual Fire/Explosion H
azard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN
CLOSED CONTAINERS. COOL WITH WATER SPRAY.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL AND COVER WITH AN INERT
ABSORBENT. COLLECT WASTE IN CONTAINERS FOR PROPER DISPOSAL. DO NOT
PERMIT SPILL TO ENTER DRAINS OR SEWERS OR CONTAMINATE ANY LAKES,
STREAMS, PONDS, OR UNDERGROUND WATER SUPPLY.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling an

d Storage =====

Handling and Storage Precautions:DO NOT USE OIL ABOVE MAXIMUM
RECOMMENDED OPERATING TEMPERATURE OF 450F. MAY SOFTEN SOME PLASTIC
AND PAINT SURFACES. WIPE UP SPILLS IMMEDIATELY.
Other Precautions:AVOID EYE AND SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF OVERHEATED, USE APPROPRIATE NIOSH-APPROVED
RESPIRATORY PROTECTIVE EQUIPMENT.

Ventilation:LOCAL EXHAUST AND MECHANICAL(GENERAL) VENTILAT
ION ARE
RECOMMENDED.

Protective Gloves:IMPERMEABLE GLOVES TO PROTECT SKIN.

Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment:HAVE EMERGENCY EYE WASH STATION AND SAFETY
SHOWER AVAILABLE.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Spec Gravity: