

CONOCO INC CONOSTAN DIV -- SUPER UNLEADED GASOLINE/PREMIUM UNLEADED --
9130-00-148-7104

===== Product Identification =====

Product ID: SUPER UNLEADED GASOLINE/PREMIUM UNLEADED

MSDS Date: 04/25/1986

FSC: 9130

NIIN: 00-148-7104

MSDS Number: BQDYK

=== Responsible Party ===

Company Name: CONOCO INC CONOSTAN DIV

Address: 1000 S PINE ST

Box: 1267

City: PONCA CITY

State: OK

ZIP: 74602

Country: US

Info Phone Num: 405-767-2287

Emergency Phone Num: 405-767-2287

CAGE: 59548

=== Contra

ctor Identification ===

Company Name: CONOCO INC CONOSTAN DIV

Address: 1000 S PINE ST

Box: 1267

City: PONCA CITY

State: OK

ZIP: 74602

Country: US

Phone: 405-767-2287

CAGE: 59548

===== Composition/Information on Ingredients =====

Ingred Name: HYDROCARBON MIXTURE (AROMATIC & PARAFFINIC)

Other REC Limits: NONE RECOMMENDED

Ingred Name: BENZENE (SARA III)

CAS: 71-43-2

RTECS #: CY1400000

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 1PPM/5STEL; 1910.1028

ACGIH TLV: 10 PPM; A2; 9293

EPA Rpt Qty: 10 L

BS
DOT Rpt Qty:10 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >25 ML/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:HIGH VAPOR LEVELS MAY CAUSE EYE IRRITATION. THE LIQUID IS SLIGHTLY IRRITATING TO THE SKIN. PROLONGED OR REPEATED CONTACT CAN RESULT IN DEFATTING AND DRYING WHICH MAY RESULT IN SKIN IRRITATION AND DERM ATIT
IS. INHALATION OF VAPORS MAY BE IRRITATING TO NOSE & LUNGS. MAY CAUSE CNS DEPRESSION. INGESTION MAY CAUSE VOMITING
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.
Effects of Overexposure:EYE, SKIN & RESPIRATORY TRACT IRRITATION. CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION MAY BE EVIDENCED BY GIDDINESS, HEADACHE, DIZZINESS AND NAUSEA. IN EXTREME CASES, UNCONSCIOUSNESS AND DEATH MAY OCCUR. ASPIRATION OF VOMITUS INTO THE LUNGS MAY CAUSE COUGHING, LABORED BREATHING, CYANOSIS AND IN SEVERE CASES, DEATH.
Medical Cond Aggravated by Exposure:PREEXISTING EYE, SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. GIVE MOUTH-TO-MOUTH RESUSCITATION IF NOT BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. KEEP HEAD BELOW HIPS IF VOMITING OCCURS. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:-50F,-46C
Lower Limits:NOT GIVEN
Upper Limits:NOT GIVEN
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY

CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. DO NOT ENTER ENCLOSED OR CONFINED SPACE WITHOUT PROPER PROTECTION.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION.

WEAR APPROPRIATE RESPIRATOR & PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK IF SAFE TO DO SO. DIKE TO CONTAIN. REMOVE WITH VACUUM OR PUMP TO STORAGE/SALVAGE VESSELS. ABSORB RESIDUE WITH INERT MATERIAL. WATER FLUSH AREA.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP LIQUID/VAPOR AWAY FROM HEAT, SPARKS & FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION. IGNITED VAPORS MAY EXPLODE.

Other Precautions:"EMPTY" CONTAINERS CAN CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, DRILL, GRIND, WELD OR PERFORM SIMILAR OPERATIONS ON OR NEAR CONTAINERS. STATIC ELECTRICITY MAY ACCUMULATE AND CREATE A FIRE HAZARD. GROUND CONTAINERS, FIXED & TRANSFER EQUIPMENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID PROLONGED OR REPEATED BREATHING OF VAPORS. IF EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS, USE A NIOSH/MSHA APPROVED RESPIRATOR.

EITHER AN AIR-SUPPLIED OR AIR-PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGES IS RECOMMENDED.

Ventilation:USE EXPLOSION-PROOF LOCAL AND/OR MECHANICAL VENTILATION. AVOID OPEN ELECTRICAL SOURCES NEAR PRODUCT VAPOR AREAS.

Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:INDUSTRIAL WORK CLOTHING TO MINIMIZE CONTACT. RUBBER APRON AND BOOTS AS REQUIRED. EYE BATH AND SAFETY SHOWER RECOMMENDED

NDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER USING PRODUCT AND BEFORE EATING, DRINKING OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

STUDIES WITH RODENTS HAVE SHOWN THAT PETROLEUM DISTILLATES HAVE CAUSED KIDNEY DAMAGE AND KIDNEY OR LIVER TUMORS. HOWEVER, THE KIDNEY EFFECTS WERE NOT SEEN IN SIMILAR STUDIES INVOLVING GUINEA PIGS, DOGS OR MONKEYS. SEVERAL STUDIES EVALUATING PETROLEUM WORKERS HAVE NOT SHOWN SIGNIFICANT INCREASES OF KIDNEY DAMAGE.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:85-437F

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:275-475

Vapor Density:NOT GIVEN

Spec Gravity:0.77

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:INSOLUBLE

Appearance and Odor:RED LIQUID, GASOLINE ODOR.

Percent Volatiles by Volume:100 %

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG

OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND OTHER HYDROCARBON COMPOUNDS DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.