

MOBIL OIL CORP -- MOBILOIL AERO RED BAND -- 9150-01-007-9134

===== Product Identification =====

Product ID:MOBILOIL AERO RED BAND

MSDS Date:02/14/1993

FSC:9150

NIIN:01-007-9134

MSDS Number: BQKQV

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Box:1025

City:PRINCETON

State:NJ

ZIP:08540

Country:US

Info Phone Num:800-662-4525

Emergency Phone Num:609-737-4411

CAGE:6A687

=== Contractor Identification ===

Company Name:MOBIL OIL CORP

Box:1025

City:PRINCETON

State:NJ

ZIP:08540

Country:US

Phone:609-737-4411

CAGE:6A687

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT, DEWAXED RESIDUAL OIL (PETROLEUM)

CAS:64742-62-7

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:D

ISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY
PARAFFINIC

CAS:64742-65-0

RTECS #:PY8038500

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5G/KG ESTIMATED

Routes of Entry: In

halation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ON RARE OCCASIONS, PROLONGED AND
REPEATED EXPOSURE TO OIL MIST POSES A RISK OF PULMONARY DISEASE
SUCH AS CHRONIC LUNG INFLAMMATION. THIS CONDITION IS USUALLY
ASYMPTOMATIC AS A RESULT OF REPEATED SMALL ASPIRATIONS. SHORTNESS
OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS. ASPIRATION MAY
LEAD TO CHEMICAL PNEUMONITIS.

Explanation of Carcinogenicity:IARC HAS D

ETERMINED THERE IS SUFFICIENT

EVIDENCE FOR THE CARCINOGENICITY IN EXPERIMENTAL ANIMALS OF USED
MOTOR OIL.

Effects of Overexposure:GENERALLY CONSIDERED MINIMALLY IRRITATING TO
THE EYES AND MILDLY IRRITATING TO THE SKIN. PROLONGED AND REPEATED
CONTACT MAY RESULT IN VARIOUS SKIN DISORDERS SUCH AS DERMATITIS,
FOLLICULITIS OR OIL AC NE. INHALATION OF VAPOR OR OIL MIST MAYCAUSE
MILD UPPER RESPIRATORY TRACT IRRITATION. SLIGHTLY TOXIC IF
SWALLOWED.

Medical Cond Aggravated by

Exposure:PREEXISTING SKIN AND RESPIRATORY

DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER.
GET MEDICAL ATTENTION IF IRRITATION DEVELOPS. INHALATION: REMOVE TO
FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION.
EYE : IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING
EYELIDS OPEN. GET MEDICAL ATTENTION. I

NGESTION: MAY ACT AS A
LAXATIVE. DO NOT INDUCE VOMITING. RELATIVELY NON-TOXIC UNLESS
ASPIRATED.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:>470F,>243C
Lower Limits:0.6
Upper Limits:7.0
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER
SPRAY.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL IMMEDIATELY. DO NOT ALLOW SPILL
TO ENTER SEWERS OR WATERCOURSES, REMOVE ALL SOURCES OF IGNITION.
ABSORB WITH APPROPRIATE INERT MATERIAL SUCH AS SAND, CLAY, ETC.
LARGE SPILLS MAY BE PICKE D UP USING VACUUM PUMPS, SHOVELS,
BUCKETS, ETC.

===== Handling and Storage =====

Handling and Storage Precaut
ions:DO NOT TRANSFER TO UNMARKED
CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN
FLAME, OR OXIDIZING MATERIALS. COMBUSTIBLE LIQUID.
Other Precautions:MINIMIZE SKIN CONTACT. WASH WITH SOAP AND WATER
BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.
LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF
CONTAMINATED LEATHER ARTICL ES THAT CAN NOT BE DECONTAMINATED.

===== Exposure Controls/Personal Protection =====

Resp

iratory Protection:USE NIOSH/MSHA APPROVED AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS AND PARTICULATES OR AN ATMOSPHERE-SUPPLYING RESPIRATOR IF REQUIRED. PROTECTION IS NOT REQUIRED UNDER NORMAL USE CONDITIONS.

Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE. MECHANICAL EXHAUST RECOMMENDED IF USED IN ENCLOSED AREA.

Protective Gloves:CHEMICAL RESISTANT GLOVES (NITRILE BEST)

Eye Protection:WEAR CHEMICAL SAFETY GOGGLES

Other Protective Equipment:WEAR PROTECTIVE CLOTHING, APRON AND BOOTS AS REQUIRED TO MINIMIZE SKIN CONTACT.

Work Hygienic Practices:MINIMIZE SKIN CONTACT. WASH WITH SOAP AND WATER BEFORE EATING, DIRNKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

THIS PRODUCT IS CLASSIFIED AS AN OIL UNDER SECTION 311 OF THE CLEAN WATER ACT. SPILLS ENTERING SURFACE WATERS OR ANY WATER COURSES OR SEWERS ENTERING/LEADING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER. 800-42

4-8602

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Melt/Freeze Pt:M.P/F.P Text:10F,-12C

Vapor Pres: