

PRATT AND LAMBERT INC; INDUSTRIAL COATINGS DIV -- LAC ACR RED 11136 ID 794104 --
8010-00-935-7062

===== Product Identification =====

Product ID:LAC ACR RED 11136 ID 794104

MSDS Date:09/24/1992

FSC:8010

NIIN:00-935-7062

MSDS Number: BQMHD

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer'

s Name:W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:CYCLOHEXANONE (SOLVENT) (SARA III) (VAPOR PRESSURE 2 MM HG
@ 20C) (LFL 1.1)

CAS:108-94-1

RTECS #:GW1050000

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 L

BS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (SOLVENT) (SARA III) (VAPOR PRESSURE 70
MM HG @ 20C) (LFL 2.0; UFL 10.0)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/STEL 300 PPM
ACGIH TLV:200 PPM/STEL 300 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SOLVENT) (SARA III) (VAPOR PRESSURE 22 MM HG @
20C) (LFL 1.7; UFL 7.1)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ACRYLATE (SARA III) (VAPOR PRESSURE 29 MM HG @ 20C)
(SKIN) (LFL 1.0; UFL 14.0)
CAS:140-88-5
RTECS #:AT0700000
Fraction by Wt: 15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S,25 PPM/15 STEL
ACGIH TLV:5 PPM/15 STEL,A2 93
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL BENZYL PHTHALATE (ADDITIVE) (SARA III) (LFL 0.3)
CAS:85-68-7
RTECS #:TH9990000
Fraction by Wt: 200 CST
Ev

aporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:72

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>115F) AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, WILL PRODUCE SMOKE, CARBON MONOXIDE, AND CARBON DIOXIDE. OXIDE S OF CHROMIUM AND LEAD MAY BE GENERATED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORD W/FED, STATE, LOCAL LAWS/REGS. INCINERATE IN EPA PERMITTED FACILITY. DONT INCINERATE CLOSED CONTAINERS. OBEY PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS. DISPOSE OF CONTAM ABSORB NT IN HAZARDOUS WASTE LANDFILL. RCRA D001, D008.

Disclaimer (provided with this information by the compiling agencies):

This information is fo

rmulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.