

PRATT AND LAMBERT INC; INDUSTRIAL COATINGS DIV -- LAC ACR RED 11136 ID 794104 --
8010-00-935-7062

=====
===== Product Identification =====

Product ID:LAC ACR RED 11136 ID 794104
MSDS Date:09/24/1992
FSC:8010
NIIN:00-935-7062
MSDS Number: BQMHD
=== Responsible Party ===
Company Name:PRATT AND LAMBERT INC; INDUSTRIAL COATINGS DIV
Box:2153
City:WICHITA
State:KS
ZIP:67201
Country:US
Info Phone Num:316-733-1
361
Emergency Phone Num:716-873-6000/DOT: 800-255-3924
Preparer's Name:W. A. ELLISON
CAGE:61196
=== Contractor Identification ===
Company Name:PRATT AND LAMBERT INC
Box:6027
City:CLEVELAND
State:OH
ZIP:44101-1027
Country:US
Phone:216-566-2902
CAGE:61196

=====
===== Composition/Information on Ingredients =====

Ingred Name:CYCLOHEXANONE (SOLVENT) (SARA III) (VAPOR PRESSURE 2 MM HG
@ 20C) (LFL 1.1)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 20%
Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (SOLVENT) (SARA III) (VAPOR PRESSURE 70
MM HG @ 20C) (LFL 2.0; UFL 10.0)

CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/STEL 300 PPM
ACGIH TLV:200 PPM/STEL 300 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SOLVENT) (SARA III) (VAPOR PRESSURE 22 MM HG @
20C) (LFL 1.7; UFL 7.1)

CAS:108-88-3
RTECS
#:XS5250000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ACRYLATE (SARA III) (VAPOR PRESSURE 29 MM HG @ 20C)
(SKIN) (LFL 1.0; UFL 14.0)

CAS:140-88-5
RTECS #:AT0700000
Fraction by Wt: 15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S,25 PPM/15 STEL
ACGIH TLV:5 PPM/15 STEL,A2 93
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL BENZYL PHTHALATE (ADDITIVE) (SARA III) (L

FL 0.3)
CAS:85-68-7
RTECS #:TH9990000
Fraction by Wt: 200 CST
Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER
Solubility in Water:SLIGHT
Appearance and Odor:LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:72

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>115F) AND SOURCES
OF IGNITION.
Hazardous Decomposition Products:BURNING, WILL
PRODUCE SMOKE, CARBON
MONOXIDE, AND CARBON DIOXIDE. OXIDES OF CHROMIUM AND LEAD MAY BE
GENERATED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORD W/FED, STATE, LOCAL LAWS/REGS.
INCINERATE IN EPA PERMITTED FACILITY. DONT INCINERATE CLOSED
CONTAINERS. OBEY PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS.
DISPOSE OF CONTAM ABSORB NT IN HAZARDOUS WASTE LANDFILL. RCRA D001,
D008.

Disclaimer (provided with this
information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.